

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP IN	FOR	MATION					
MODE YEAF		EST GROUP	GROUP VEHICLE CLASS(ES)					FUEL C	ATEGORY		FUEL TYPE		
2020	20 LGMXT01.5090 LDT2							DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USEFU	LIFE (miles)	VEH	ICLE EMISS	ATE	GORY	INTERIM / IN	INTERIM / INTERMEDIATE IN-USE STD					
EXH	I/ORVR	EVAP			FTP	TP SFTP			FTP		SFTP		
15	150000 150000 LEV3 ST			SULEV30	LEV	3 CC	MPOSITE	*		*			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	EN	ENGINE DISPLACEMENT		
1	1 DFI, HO2S(2), TC, CAC, TWC							FULL	*	and a second sec			
*	*							ARTIAL	ALL MODELS	1.5			
*	* *							RTIAL WITH *					
		E	VAPO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	INFORMATIO	N			
EVA	P / ORV	R FAMILY	EVA	PORATIVE	E STD CATE	GORY	,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
I	LGMXR0(9537C	L	EV 3 OPTI	CON2 WITH	FEL		LI)T2		HCT		
				I	EMISSION C	REDIT	INFO	ORMATION			3		
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON-I ZERO-EVAP							ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS		
	N N						-		N		N		
				NMOG	AND FLEET	T AVE	RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO	C HCHO/NMHC RATIO NMOG+NOX FLI PC+LDT (0-375 (g/mi)			0-375							
*	*	1.10		*	0	.065		0.074			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



GENERAL MOTORS LLC.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 24^{40} day of May 2019.

Allen Lyons, Chief Emissions Compliance, Automotive Regulations and Science Division



FUEL TYPE

GENERAL MOTORS LLC. Executive Order: A-006-2203 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		UELI															
				NMOG+NOx (g/mi)				CO (g/mi)		-	NOx g/mi)		HCH (mg/r		PM (g/mi)		
				CER	г ѕт	D	CER	г ст	D	CERT	STD	CEF	т	STD	CERT	STD	
FTP@5	0K	*		*	*	- 7	*	*		*	*	*		*	*	*	
FTP@I		ASOLII		0.01	4 0.0	30	0.4	1.	0	*	*	*		4	1 *		
50°F @		ASOLII		0.01	3 0.0	60	0.2	1.	0	*	*	*		8			
indugan tengen Ja					EUEI	TVD	=			N	NMOG+NOx (g/mi)			CO (g/mi)			
				FUEL TYPE				CERT		STD		CERT		STD			
HWFET @ 50K		ж			*						* *			energian and regardle	and and		
HWFET @ UL			GASOLINE-TIER3 E10					0.	001	0.030							
20°F	@ 50k	(C	OLD C	O E10	0 REGULAR GASOLINE (TIER3)			R3)					0.6		12.5		
				SFTP E	XHAUST	EMI	SSION	STAND	ARDS	AND C	ERTIFIC	ATION L	EVEL	S	-		
				US06						SC03			COMPOSITE				
	FUEI	L TYPE		5.05	OG+NOx (g/mi)		CO (g/mi)	1000	PM g/mi)		G+NOx /mi)	CO (g/mi)		OG+NOx (g/mi)	MPOSITE CO	PM (mg/mi)	
@ 4K		*		* CERT		*		*				*	*				
			STD		*		*				*	*					
			CER	Г	*		*		*		*	*	(0.011	(g/r CERT * CO (g/mi) CO (g/mi) CO (g/mi) 2.0 4.2 S (g/mi) @ F	*	
@ UL		LINE- 3 E10	STD		*	×	*		*		*	*	0	0.083	4.2	*	
			BIN							Sector 1			(0.050			
		W	HOLE	/EHICL	E EVAP	ORA'	TIVE E	MISSION	N STA	NDARD	S AND C	ERTIFIC	ATIO	N LEVELS	5		
						WH	IOLE V	EHICLE	EVA	PORAT	IVE TEST	ING					
	ORAT		VE FUEL TYPE		3DHS (g/test) @ UL			2DHS (g/test)		@ UL	R		_ (g/mi) @ UL				
			pe		CERT	S	TD	FEL	CE	RT	STD	FE	L	CERT		STD	
LGMXF	R00953	1701	GASOL: FIER3		0.201	0.	400	0.375	0.3	164	0.400	0.3	75	0.00		0.05	
C	ORVR	FUEL	ONLY	CANI	STER BL	EED	EVAP	ORATIV	EEMI	SSION	STANDA	RDS AN	D CEI	RTIFICATI	ON LEVE	ELS	
									F	UEL OI	NLY EVA	P & CAN	ISTE	R BLEED		3	

				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K				
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD			
LGMXR009537C	GASOLINE- TIER3 E10	0.02	0.20	GASOLINE- TIER3 E10	*	*	*	*	0.004	0.020			

CALIFORNIA

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)								
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD					
LGMXR009537C	LGMXR009537C-LK1	*	0.02					

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION												
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD					
CHEVROLET	EQUINOX AWD	LDT2	1.5	A6	LGMXR009537C	1	P					
CHEVROLET	EQUINOX FWD	LDT2	1.5	A6	LGMXR009537C	1	P					
GMC	TERRAIN FWD	LDT2	1.5	A9	LGMXR009537C	1	P					