

# GENERAL MOTORS LLC.

Executive Order: A-006-2222

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	IFORI	MATION						
MODE		EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE			
202	) Lo	LGMXT03.0351 LDT4						DEDICATED SINGLE FUEL VEHICLE			DIESEL			
USEFUL LIFE (miles) VEHICLE EMISSION							ON CATEGORY INTERIM /				NTERMEDIATE IN-USE STD			
EX	I/ORVR	EVAP	FTP				SFTP		FTP		SFTP			
150000 *				LEV3	LEV160 LEV 3 COMPOS			MPOSITE	State Court	PM		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							OBD			D STATUS		ENGINE DISPLACEMENT (L)		
OC+DPF-SCRC, SCRC+NH3OC, DFI, CAC, TC, HP-EGR, LP-EGR, EGRC, NOXS(3), PMS, RDQS								FULL		*				
*	180		*			5.02230	Р	ARTIAL	Ī	*		3.0		
*				PARTIAL WITH			ALL MODELS							
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR										SION STD CLASS	5	SPECIAL FEATURES		
	1	,	*					*			*			
			-	E	MISSION C	REDI <sup>*</sup>	TINF	ORMATION						
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY  NMOG CREDIT FOR I ZERO-EVAI							ZEV	NMOG CREDIT FOR DO			R OPTIONAL EXH. STD FOR WORK TRUCKS			
N N									N					
				NMOG	AND FLEE	TAVE	RAG	E INFORMA	ΑT	TION				
NMO(		FTP NMOG/NMH RATIO	С	CHO/NMHC RATIO	P(.+1 D) 10=3/30			LVW) LDT		OG+NOX FLEET ST DT (3751 LVW-8500 VWR) + MDPV (g/mi)				
*	*	*		(	0.065	i	0.074				*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



GENERAL MOTORS LLC. Executive Order: A-006-2222 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

#### BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have eleven (11) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of three hundred seventy five dollars (\$375) per vehicle for the third through eleventh deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of Jul

Allen Lyons, Chief

TEmissions Certification and Compliance Division



GENERAL MOTORS LLC.

Executive Order: A-006-2222 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

							Α	ГТАС	НМ	ENT									
	EXHAL	JST	AND	EVAP	ORA	TIVE	EMIS	SION	ATE	NDAR	OS AND	CERT	IFIC	ATION	LEVI	ELS			
	E	XHA	UST E	MISSIO	N STA	ANDA	RDS A	ND CER	ΓΙFΙC	ATION L	.EVELS (	FTP, H\	VFET,	50°F, 20	0°F)				
	FUEL	_ TYF	mo ad OF 10	onoxide justmer RVR (a	; NOx: nt facto HC/ga	oxide or; 2Dh llon di	s of niti HS/3DH spense	rogen; H IS [g HC d]: on-bo	CHO: /test]: oard re	formald 2/3 day efueling	hydrocart ehyde; Pl s diurnal- vapor rec st procedu	M: partic hot-soa overy; c	:ulate r k; RL [ <sub>::</sub> gram	matter; F g HC/mi i; mg: mi	RAF: re i]: runn illigram	activi ing lo	ty ss;		
					MHC+NOx (g/mi)		(	CO g/mi)		NOx (g/mi)			HCH( (mg/m			PM (g/mi)			
			CER.				CERT		0	CERT	STD	CE	CERT		CEF	RT	STD		
FTP@50	K *			*	7	k	*	*		*	*			*	*		*		
FTP@U			PA C	.113	0.1	160	0.1	4.:	2	*	*	* *		4	0.000		0.003		
50°F @4		* .		*	,	*	*	*		*	*	*		*			14.1		
										N	MHC+NC	) [		CO (g	CO (g/mi)				
				FUEL TYPE					•		CERT		)	CERT		STD			
HWFET	@ 50K			*							*		- 100						
HWFE.	T@UL				DIESE	CL-EP	A			0.027		0.16	0.160				de Arbantina in Maria		
20°F @ 50K				*										*		*			
	<u> </u>		SE	TD FY	PALIS	TEMI	SSION	STAND	ΔRDS	S AND C	ERTIFIC	ATION	FVFI	S					
V V				11 LX	IIAGO		S06	OTAILD	11100	7	SC03		1		OMPO	SITE			
	FUEL TY	/PE		NMHC+I					M <sub>J</sub> /mi)		NMHC+NOx (g/mi)				/IHC+NOx (g/mi) (g		PM (mg/mi)		
@ 41/		* C		CERT			*		*	T.			*		*				
@ 4K	•			*		_	*	, pc			*	*							
				*			*	0	. 3	*		*	* 0.130		0.1		*		
@ UL	DIESEL-	EL-EPA STD BIN					* 6		6	*		*	* 0.083		4.2		*		
														0.180					
		WH	OLE VE	HICLE	EVAF	PORA	TIVE E	MISSION	STA	NDARD	S AND C	ERTIFI	CATIO	N LEVE	LS				
						WH	IOLE V	EHICLE	EVA	PORAT	VE TEST	ING			p	22 85	*		
EVAPORATIVE FUEI			UEL TY	. TYPE 3DHS (			g/test) @ UL			2DHS (g/test)		@ UL		RL (g/i		mi) @ UL			
LAMIL					CERT S		TD	FEL	CE	ERT	RT STD		EL	CERT		STI			
	. *		*	*			*	*			*		*		*		*		
	ORVR / FU	JEL (	ONLY /	CANIS	TER B	LEED	EVAP	ORATIV	E EM	ISSION	STANDA	RDS A	ND CE	RTIFICA	ATION	LEVE	ELS		
									F	FUEL O	NLY EVA								
EVAPORATIVE FAMILY		ORVR (g/		(g/gallo	gallon) @ UL		FUEL TYPE			OHS RIG TEST (g/test) @ UL		2DHS RIG (g/test) @				EED CANISTER ST (g/test) @ 4K			
FF	ZIVIIL I	FUEL T		YPE CERT		STD	FUE	LIIFE		ERT	STD	CER	<del>- i -</del>	STD		CERT			
*		+	*	*		*	*		+-	*	*	*	*		*		*		
		EFF	ECTIV	E LEA	K DIA	AMET	ER ST	ANDA	RD A	ND CE	RTIFICA	TION L	EVEL	(INCH	ES)				
EVAF	PORATIVE				LEAK					CEF					STD				
	*			*					*					*					



GENERAL MOTORS LLC. Executive Order: A-006-2222

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: \_DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	
GMC	SIERRA 4WD	LDT4	3.0	A10	*	1	\$	
GMC	SIERRA 4WD AT4	LDT4	3.0	A10	*	1	\$	