

Executive Order: A-003-0711

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	IFORI	MATION					
MODI YEA		TEST GROUP			VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE		
202	2020 LMBXD02.1HD2				MDV5				SINGLE FUEL HICLE		DIESEL		
USEFUL LIFE (miles)				VEHICLE EMISSION CATEGOR				ORY	INTERIM / IN	TERM	RMEDIATE IN-USE STD		
EXH/ORVR EVAP					FTP			TP	FTP		SFTP		
150000 *			LEV3			HOT14 A92),		NMHC+NOX ANI		PM			
SPI	SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1	DFI,	TC,TC,CAC,EG (2),WR-H				3		FULL	*				
*	*							ARTIAL	ALL MODELS	1	2.1		
*	* *							TIAL WITH FINES	*				
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EV	EVAP / ORVR FAMILY EVAPORATIVE S					E STD CATEGORY			SSION STD E CLASS	SP	SPECIAL FEATURES		
	,	ł .		*				*		*			
EMISSION CREDIT INFORMATION													
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY					OG CREDIT FOR NON-PZEV ZERO-EVAP			NMOG C	REDIT FOR DO		OPTIONAL EXH. STD FOR WORK TRUCKS		
N N							N				N		
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	CH4 RAF	FTP NMOG/NMH0 RATIO		HO/NMHC RATIO	NMOG+NOX FLE LDT (3751 LVW-85 + MDPV (g/i				G+NOX FLEET STE (8501-10000 GVWR (g/mi)		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	*	* 0.018 *						0.228		0.349		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-003-0711

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

# BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

# BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

## BE IT FURTHER RESOLVED:

The fuel-fired heater incorporated in the listed vehicle models must not operate at ambient temperature above 40 °F (13 CCR Section 1961.2(a)(13) (Emission Standard for a Fuel-Fired Heater]).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 16th day of December 2020.

Allen Lyons, Chief

**Emissions Certification and Compliance Division** 

Executive Order: A-003-0711 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

# **ATTACHMENT**

	FYH/	1116.	T AND	FVΔ	P∩R	ΔΤΙ	/E EMI	SSION	STA	NDARI	DS AN	D CEE	TIFIC	CATION	I I F\	/FI S		
																LLG	<b>,</b>	
	FUE			CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP														
					HC+NOx g/mi)			CO (g/mi)			NOx (g/mi)		HCH (mg/i			PM (g/mi)		
						STD	CER.	ГЅ	TD	CERT	ERT STD		RT	STD	CERT		STD	
FTP@5	P@50K *					*	*		*	*	*		*	*	*		*	
FTP@L	_	SEL-	EPA	0.150	0	.230	0.1	_	.2	*	*		0	6	0.0	002	0.010	
50°F @	4K	*		*	* *		*		*			*		* *				
					FUE	EL TY	PE			_	MHC+NOx (g/m		-			CO (g/mi)		
											CERT		D	CERT		STD		
HWFE	Г @ 50K			*							*	*						
HWFET @ UL					DIE	SEL-I	PA		0.	014	0.2	30						
20°F	@ 50K	*											*		,		*	
	SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS																	
							US06				SC03			COMPOSITE				
	FUEL T			NMHC+NOx		Ох	co		PM		NMHC+NOx		- 1			CO	PM	
				<u> </u>	(g/mi)		(g/mi) (m		ıg/mi)	(g/	(g/mi)		<u> </u>	(g/mi) (g		J/mi)	(mg/mi)	
@ 4K	*		CERT		*		*	*			*							
		S			*		*	*			*	*						
		CEF IESEL-EPA STI			*		*		*	*		*	0.157		0.1		2	
@ UL	DIESEL				*		*		*		*		0.350		4.0		7	
														*				
		WH	IOLE V	EHICL	E EVA								CATIO	ON LEVE	LS			
	op 4=== ==	_			WHOLE VEHICLE EVAPORATIVE TESTING							<b>⊣</b> _	DI /a/m:\ @ !!!					
	ORATIVE MILY			YPE	3DHS (g/test) @		UL		2DHS	2DHS (g/test)		@ UL		KL (g/n	. (g/mi) @ UL			
					CER	T	STD	FEL		ERT	RT STD		EL	CERT		STD		
*			*		*					* *			**		* *			
-	ORVR / F	UEL	ONLY /	CANIS	STER	BLEE	D EVAP	ORATI						RTIFICA		LEVE	ELS	
	OD 47" "	_		(alas!	on\ @									R BLEE		-D 0	ANIOTED	
EVAPORATI Family				(g/gaii	on) @ UL		FUE	L TYPE	_ I _	DHS RIG (g/test) (			2DHS RIG (g/test) @			ED CANISTEI T (g/test) @ 4		
				YPE CERT		STD	<b>⊣</b> '	, , , , , , , , , , , , , , , , , , , ,		ERT			RT	STD CE			STD	
	*	*			* *			*		* *		*		*	* *		*	
	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)																	
EVAF	PORATIV	E FA	MILY		LEAP	< FAN	IILY			CER	Т				STD			
*				*					*					*				



Executive Order: A-003-0711

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW: MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; JLEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission: CV: continuously variable transmission: SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FREIGHTLINER	SPRINTER 3500 XD	MDV5	2.1	A7	*	1	P
FREIGHTLINER	SPRINTER 4500	MDV5	2.1	A7	*	1	P
MERCEDES-BENZ	SPRINTER 3500 XD	MDV5	2.1	A7	*	1	P
MERCEDES-BENZ	SPRINTER 4500	MDV5	2.1	A7	*	1	P