- 0			
(X)	CAL	IFOR SOURCES	NILA
A	CAL		NIA
$M \subset M $	AIR RE	SOURCES	BOARD

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	FORMA	TION				
MODE		EST GROUP	VEHIC	FUEL CATEGORY			FUEL TYPE				
2020 LMBXV04.0U2A PC								SINGLE FUEL HICLE	GASOLINE		
	USEFU	LIFE (miles)	VEH	ICLE EMIS	SION C	ATEGO	RY	INTERIM / INT	ERMEDIATE IN-USE STD		
EXH	EXH/ORVR EVAP FTP							FTP	SFTP		
15	0000	150000	LEV3	ULEV125	LEV	3 COME	POSITE	*	PM		
SPE	CIAL FI	EATURES & EXI SYS	HAUST EMISSIO	ON CONTRO	DL	n tegari Profesio	OBD S	TATUS	ENGINE DISPLACEMENT		
1 DFI, 2TC, 2CAC, 2WR-HO2S, 2HO2S, 2TWC(2)						FL	JLL	*			
*	* *						PARTIAL *		4.0		
*	* Lucinona in a luna mitrifu k ini goti inazira Albakara in						AL WITH NES	ALL MODELS	Adalah sebahan katalah sebahan katalah sebahan sebahan sebahan sebahan sebahan sebahan sebahan sebahan sebahan Adalah sebahan s		
		EV	APORATIVE &	REFUELING	G (EVA	P/ORVF	R) FAMILY	INFORMATION			
EVA	P / ORV	R FAMILY	EVAPORATIVE	E STD CATE	GORY	E		SSION STD E CLASS	SPECIAL FEATURES		
. 1	MBXR01	170LNS	LEV 3 OPTI	CON2 WITH	FEL	er distant and an PC embed by the r			antan in S t érapan Mana		
			E	EMISSION C	REDIT	INFOR	MATION	a Arte Carto da Social	netta na selente con setem nas Tre		
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY					PZEV NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N		N	e	N			N		
			NMOG	AND FLEE	TAVE	RAGE I	FORMA	ΓΙΟΝ			
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO				LDT (+NOX FLEET STI (3751 LVW-8500 R) + MDPV (g/mi)	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	0.018		0.065	CREE .		0.074	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)

ALIFORNIA AIR RESOURCES BOARD

DAIMLER AG

A then for a conversion and the topology

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

NEDG+ROCK FLETT

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of May 2019.

Unever.

*A*Emissions Compliance, Automotive Regulations and Science Division yernells,donoiser重要的的问题。如果你可以不可以能能能能。

r Parentest, 0900 Concretende, Emission Standerde and Cenerication Envelsionen and Armerikation (Armerik reservejator officer (PDC robrec 14.000 pc. robrin 1917/AR folodir Shie Executive Celor and officer of programmeda in 17.008 pastical PRC (Celoration to MC) parametric to 18.008 Berlann 1956,8m2



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			20.00	1 1	1 53 6	1. 1. 1. 1 ×	6.27 147 . 12	111	12.20	al the state	1.00		1. C. T.			
				DG+NO> g/mi)		CO (g/mi)			lOx J/mi)		HCHO (mg/mi)			M mi)		
				CERT	ST	D CEF	RT ST	D	CERT	STD	CER	T	STD	CERT	STD	
FTP@5	0K	*		*	*	*	*	1.44	*	*	*	20	*	* *	****	
FTP@L	JL TIE	SOLIN ER3 E PREM	2000-02	0.069	0.1	25 0.	4 2.	1	*	*	0.4	1	4	0.001	0.003	
50°F @	4K	*	- 23- C	* * *	*	*	*		*	*	*	-	*	对的书稿 :《选	REFERENCES	
inter Altack					ELLE!		- 24 - 24 - 27 		N	MOG+N	Dx (g/mi)		the state of the state	CO (g/mi)	na gin da	
					FUEL	TYPE			CE	ERT	STD	9	CERT		STD	
HWFE	FET @ 50K *							2	1	*	*	2440 UK UK UK	and the second	naiseni saiseni	nabodyna (imreisi	
HWFE	T @ UL		c	GASOLINE-TIER3 E10 PREM						027	0.125	5				
20°F	@ 50K	cc	DLD CO	O E10 PREMIUM GASOLINE (TIER3)					後進高計	的,我能以	Nacio		0.7		10.0	
			S	FTP EX	KHAUST	EMISSIO	N STAND	ARDS	AND C	ERTIFIC	ATION L	EVEL	S	10 (1997) - 1 (1997) 17 (1997) - 18 (1997) - 18 (1997)	and the second	
			4的1		1	US06		na a serena	1 1 1 5.4 1	SC03			CO	POSITE		
	FUEL T	YPE		NMOG+NOx (g/mi)		CO (g/mi		PM g/mi)	NMOG+NOx (g/mi)		CO (g/mi)	NMOG+NOx (g/mi)		CO (g/mi)	PM (mg/mi	
@ 4K	*		CERT		*	*	i lan sala	n		*	*	i dilapo Neniri 1571	(18) 1917 - 1916 - 1917 1917 - 1916 - 1	talayana ing	al de las re-	
			STD		*		4.5		*		*				an and a strange of the strange of t	
		CERT *		T *		*	1	1.0					0.065	0.4	*	
@ UL	GASOLI TIER3 PRE	E10	STD		*	*		6		*	*		0.083	4.2	*	
			BIN		$= (g_{ij}^{\rm M},g_{ij}^{\rm M}) \log$						dialet (* j		0.080	1.2.3.3.4.3	(Argental A	
		WH	OLE V	EHICLI	EEVAP	ORATIVE	EMISSION	STAI	NDARD	S AND C	ERTIFIC	ATIC	N LEVEL	S		
						WHOLE	VEHICLE	EVAP	ORATI	VE TEST	ING					
		[■] F	UEL TY	(PE	3DH	S (g/test)	@ UL		2DHS	S (g/test)	@ UL		RL	(g/mi) @	UL	
					CERT	STD	FEL	CE	RT	STD	FEI	_	CER	r	STD	
LMBXR	0170LN		ASOLII LEV3 E PREM	10	0.240	0.300	0.275		,	0.300	0.27	275 0.00		0.05		

••••••••		Enleononternation	BO MID OLIVINIO	
-		FUEL ONLY EVAI	P & CANISTER BLEE	D
EVAPORATIVE	ORVR (g/gallon) @ UL	3DHS RIG TEST	2DHS RIG TEST	BLEED CANISTER

FAMILY				FUEL TYPE	(g/test)@UL	g/test)@UL	TEST (g/t	est) @ 4K
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD
LMBXR0170LNS	GASOLINE- TIER3 E10 PREM	0.01	0.20	GASOLINE- LEV3 E10 PREM	*	*	*	*	0.017	0.020

CALIFORNIA AIR RESOURCES BOARD	
LICALIFURNIA	
ALT AIR RESOURCES BOARD	

ANY CRURE

现于国家资源。

EFFECTIV	E LEAK DIAMETER STANDA	RD AND CERTIFICA	TION LEVEL (INCHES)
EVAPORATIVE FAMILY		CERT	STD
LMBXR0170LNS	KMBXR0170LNS-LNS	NEWS IN STREET, NA TH	0,02
LDT<6000#GVWR,3751-5750 B500#ALVW; MDV: medium-o duty passenger vehicle; HDV: emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3: continuous/periodic trap oxidi: heated/oxygen sensor; WR-H RDQS: reductant quality sens secondary air injection (belt d direct/indirect fuel injection; TO fines on-board diagnostic; DC suffix: series; CNG/LNG: com E10: "10%" ethanol ("90%"gai continuously variable transmis	0#LVW; LDT3: LDT 6001-8500#G duty vehicle; MDV4: MDV 8501-10 heavy-duty vehicle; ECS: emission vehicle weight rating; LVW: loaded ver ULEV; ZEV: zero-emission veh AC: HC adsorbing catalyst; WU: w selective catalytic reduction-urea/ zer; DPF: diesel particulate filter (a 02S or AFS: wide range/linear/hea- or; NH3S: ammonia sensor; EGR: riven)/(electric driven); PAIR: pulse C/SC: turbo/super charger; CAC: co R: direct ozone reducing; HCT: hy pressed/liquefied natural gas; LPG soline) fuel; A: automatic (with lock seion: SCV/ selectable continuous)	AWR,3751-5750#ALVW; 200#GVWR; MDV5: MD' n control system; CERT: vehicle weight; ALVW: a icle; TZEV: transitional Z arm-up catalyst; NAC: N ammonia; NH3OC: amm ctive); GPF: PM filter for ated air-fuel ratio sensor; exhaust gas recirculatio d AIR; SFI/MFI: sequent harge air cooler; FFH: fud drocarbon trap; BCAN: b :: liquefied petroleum gas up); M: manual transmission; y variable transmission; ion; AER; all-electric ran	tial/multiport fuel injection; DFI/IFI. Jel fired heater; F/P/\$: full/partial/partial wit bleed carbon canister; prefix 2: parallel; (2) s; E85: "85%" ethanol ("15%"gasoline) fuel sion; SA: semi-automatic transmission; CN AM: automated manual transmission; AMS lige; EAER: equivalent AER; PHEV: plug-ir

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MERCEDES BENZ	AMG GT (COUPE)	PC	4.0	AMS7	LMBXR0170LNS	1	\$
MERCEDES BENZ	AMG GT (ROADSTER)	PC	4.0	AMS7	LMBXR0170LNS	1	\$
MERCEDES BENZ	AMG GT C (COUPE)	*:)/: PC) ***/	4.0	AMS7	LMBXR0170LNS	1	\$
MERCEDES BENZ	AMG GT C (ROADSTER)	PC	4.0	AMS7	LMBXR0170LNS	1.1	\$
MERCEDES BENZ	AMG GT R (COUPE)	PC	4.0	AMS7	LMBXR0170LNS	1	\$
MERCEDES BENZ	AMG GT R (ROADSTER)	PC	4.0	AMS7	LMBXR0170LNS	1	\$

STORAGE AN ADMAT 2 MOREONE BURNAME TATE OF THE REPORT