

Executive Order: A-003-0677 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	NFOR	MATION						
MODE	1 1	ST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE			
2020	LMI	BXV03.0HY4			DC .				D ELECTRIC EHICLE			GASOLINE		
	USEFUL	LIFE (miles)	VEH	ICLE EMISS	ATE	GORY	INTERIM / I	MEDIATE IN-USE STD						
EXH	I/ORVR	EVAP	FTP			SF	FTP FTP			SFTP				
15	0000	150000		LEV3	3 ULEV50 LEV 3 COM			MPOSITE	PM			PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD STATUS				ENGINE DISPLACEMENT (L)		
1 DFI, TC, CAC, WR-HO2S, HO2S, TWC(2)								FULL	*					
*					P	ARTIAL	*			3.0				
*					PAR	TIAL WITH FINES	ALL MODELS	3						
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	P / ORV	R FAMILY	STD CATE	GORY	1		EVAP EMISSION STD VEHICLE CLASS SPECIAL FE			ECIAL FEATURES				
:	LMBXR01	55LNA	L	EV 3 OPTI	ON2 WITH	FEL		I	PC			*		
				E	EMISSION C	REDI	TINFO	ORMATION		1				
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY  NMOG CREDIT FOR NON- ZERO-EVAP							NIMOC CREDIT FOR DOD			PTIONAL EXH. STD OR WORK TRUCKS			
		N	N			N N								
				NMOG	AND FLEET	Γ AVE	RAGI	INFORMA	TION					
NMOG CH4 RAF NMOG/NMHC RATIO					PC+LDT (	IMOG+NOX FLEET STD PC+LDT (0-3750 LVW) (g/mi)			NMOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)			NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	* * 1.10 0.018 0.065								0.074 *					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-003-0677

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

### BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have four (4) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the third and fourth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of July 2019.

Allen Lyons, Chief

**Emissions Certification and Compliance Division** 



Executive Order: A-003-0677

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

0.014

0.020

									TTAC											
	EXH												CERTI				ELS			
		EX	(HAI										(FTP, HW							
FUE		JEL <sup>.</sup>	mo ad OF		CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP															
								NMOG+NOx (g/mi)			CO (g/mi)		NOx (g/mi)		HCH (mg/r				PM (g/mi)	
					CERT	-	STD	CERI	STE	)	CERT	STD	CER	Г	STD	CEI	₹T	STD		
FTP@5	0K	*			*		*	*	*		*	*	*	*		*		*		
FTP@l	GASOLINE- TIER3 E10 PREM		1	0.028	3 0	.050	0.5	1.7	7	*	*	0		4	0.0	01	0.003			
50°F @	4K	*	-		*		*	*	*		*	*	*		*		- 1	evir refig		
							- TVD	_			N	MOG+N	Ox (g/mi)	0	CO (g/mi)			*		
						FUI	EL TYPI	=				ERT	STD		CER	T		STD		
HWFET @ 50K							*					* *			14 47 6 14 14 14					
HWFET@UL GASOLINE-TIE							TIER3	E10 PREM			0.	011	0.050		1 - 11 90-					
20°F @ 50K COLD CO E10					E10 PREMIUM GASOLINE (TIER3)					n já.				1.4			10.0			
-	SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS												- 1							
							ι	JS06				SC03			COMPOSITE					
	FUEL	FUEL TYPE			NMOG+NOx		- 1	CO (g/mi)	P			G+NOx	CO (g/mi)		OG+NO:		CO /mi)	PM (mg/mi)		
							(g/mi) (mg/mi		/mi)	(g/mi) *		*		(g/mi)	(9	,,,,,	(mg/m)			
@ 4K		* ST		CERT						ļ					_					
				STD			*				* .	*			+-		*			
	GASO	ASOLINE-		CERT		*		*				*	*		0.019	+-	. 4	<del>                                     </del>		
@ UL	TIER			STD		*		*		5	* .		*	0.083		4.2		*		
				BIN											0.050					
		١	NHC	DLE VE	HICL	E EV							CERTIFICA	ATIO	N LEVE	LS				
							Wi	HOLE V	EHICLE	EVAP	ORAT	IVE TEST	TING			l (aln	i) @			
	ORATI MILY	1		JEL TYPE		3DHS (g/		g/test) @ UL			2DHS (g/test		:) @ UL		RL (g/mi)		11) W	OL .		
	30-0-10 (CE-2010)3000-0-10 (E					CER	CERT STI		FEL		RT	STD	FEL		CEI	₹T	T ST			
LMBXR0155LNA		LNA		GASOLINE- LEV3 E10 0. PREM			0.351 0.300		0.375	,		0.300	0.375		0.00			0.05		
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS											LS									
						-							P & CAN							
	ORATI		E ORVR (g/gal			g/gallon) @ UL			FUEL TYPE		3DHS RIG TEST (g/test) @ UL		2DHS RIG (g/test) @		) UL	at and all and a supplementary of the supplementary and a supplementary of the supplementary		st) @ 4K		
			FUEL TYPE C			ERT	ERT STD		C		RT	STD	CERT		STD	CEF	CERT S1			

GASOLINE-

LEV3 E10

PREM

0.20

0.02

GASOLINE-

PREM

LMBXR0155LNA TIER3 E10



Executive Order: A-003-0677

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
LMBXR0155LNA	LMBXR0155LNA-LNA	*	0.02						

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT; other transmission; AER; all-electric range; EAER; equivalent AER; PHEV; plug-in hybrid electric vehicle, NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MERCEDES BENZ	CLS 450	PC	3.0	A9	LMBXR0155LNA	1	\$
MERCEDES BENZ	CLS 450 4MATIC	PC	3.0	A9	LMBXR0155LNA	1	\$