

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	IFOR	MATION					
MODE YEAI	- I TE	EST GROUP	VEHICLE CLASS(ES)					FUEL CATEGORY			FUEL TYPE		
2020		BXV02.0U2B	PC					DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION							CATEGORY INTERIM / INTERMEDIATE IN-USE S						
EXH	I/ORVR	EVAP		FTP			SF	SFTP FTP			SFTP		
15	50000	150000	LEV3	ULEV70 LEV 3 COMP			MPOSITE	PM		PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS		ENGINE DISPLACEMENT (L)		
1	1 DFI, TC, CAC, WR-HO2S, HO2S, TWC							FULL	*	Contraction of the			
*	* *							ARTIAL	ALL MODELS		2.0		
*	* *							TIAL WITH	*				
		E\	APO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	(INFORMATIO	N			
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GORY EVAP EMISSION STD SUCCESS				SPECIAL FEATURES		
	LMBXR00	95lna	LE	V 3 OPTI	ON2 WITH	FEL	L PC				*		
				E	EMISSION C	REDIT	INFO	ORMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ON-P				OPTIONAL EXH. STD FOR WORK TRUCKS			
	NN							N					
				NMOG	AND FLEET	Γ AVE	RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO		IO/NMHC RATIO	C NMOG+NOX FLE PC+LDT (0-3750 (g/mi)			V) LDT	NMOG+NOX FLEET STI LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	(	0.018	0	.065			0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this  $26^{40}$  day of July 2019.

Allen Lyons, Chief



FUEL TYPE

DAIMLER AG

Executive Order: A-003-0681 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

## ATTACHMENT

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)		1	CO (g/mi)									PM (g/mi)		
			CERT	ST	D	CER	T ST	D	CERT	STD	CER	т	STD	CEI	RT	STD	
ок	*		*	*		*	*		*	*	*		*	*		*	
GASOLINE- L TIER3 E10 PREM		817854	0.050	0.0	70	0.4	1.	7	*	*	0		4		02	0.003	
50°F @4K *			*	*		*	*		*	*	*		*		a sure		
									I	NMOG+NOx (g/mi)			CO (g/mi)				
			FUEL TYPE						C	CERT STD			CERT		STD		
T @ 50K				4	r					*	*						
T @ UL		G	ASOLI	E-TIE	IR3 I	E10 PI	REM		0	.036	0.070						
@ 50K	co	DLD CO	E10 P	REMIU	MGA	SOLIN	E (TIE	R3)		pre in a .			0.	5		10.0	
		S	FTP EX	HAUST	EMI	ISSION	STAND	ARDS	AND	CERTIFIC	ATION LE	EVEL	.s				
				US06						SC03			COMPOSITE				
FUEL	TYPE						PM NI (mg/mi)			CO (g/mi)	NMOG+NOx (g/mi)				PM (mg/mi)		
*	*		*			*			*	*							
				*		*				*	*						
	CER		*			* 2		2		*	*		0.050	C	. 4	*	
TIER3	E10	10 STD * *		6	*		*	0.083		4	. 2	*					
													0.070		in de		
	WH	IOLE VI	EHICLE	EVAP	ORA	TIVE E	MISSIO	N STA	NDAR	DS AND (	CERTIFIC	ATIC	N LEVE	ELS			
					WF	HOLE \	/EHICLE	EVAF	ORA	TIVE TEST	TING						
	E F	UEL T	PE	3DH	IS (g/	/test) @	D UL		2DH	IS (g/test)	@ UL		F	RL (g/n	1i) @	UL	
			CERT	S	STD FEL		CE	RT	STD	FEL	FEL		CERT		STD		
LMBXR0095LNA		IER3	E10 0	).289	0.	300	0.300	0.2	232	0.300	0.300		0.00		0.05		
DRVR / F	UEL	ONLY /	CANIS	ER BL	EED	EVAP	ORATIV	EEMI	SSION	STANDA	RDS AND	) CE	RTIFICA	TION	LEVE	ELS	
								F	UEL C	NLY EVA	P & CAN	STE	R BLEE	D		-	
EVAPORATIVE FAMILY		ORVR	/R (g/gallon) @ UL							(g/test) @				ED CANISTER T (g/test) @ 4K			
				RTS	TD			CI	ERT	STD	CERT		STD	CEF	T	STD	
R00951N	0.000			02 0	.20	TIE	R3 E10	R3 E10		*	*		*	0.0	12	0.020	
	GASOL T @ UL @ 50K T @ UL @ 50K FUEL T * GASOL TIER3 PRE ORATIV MILY	GASOLIN JL GASOLIN TIER3 E PREM 4K * T @ 50K T @ UL @ 50K CC FUEL TYPE * GASOLINE- TIER3 E10 PREM WH ORATIVE MILY FL CORATIVE GA	OK         *         GASOLINE- TIER3 E10 PREM         A           4K         *         I           7@ 50K         T         I           T@ UL         G         G           0         50K         COLD         CO           FUEL TYPE         SI         SI           FUEL TYPE         CERT         STD           GASOLINE- TIER3 E10 PREM         CERT         STD           GASOLINE- TIER3 E10 PREM         STD         BIN           WHOLE VI         MILY         FUEL TY           ORATIVE MILY         GASOLIN TIER3 I PREM         GASOLIN TIER3 I PREM           ORVR / FUEL ONLY /         ORVR /         GASOLIN TIER3 I PREM           ORVR / FUEL ONLY /         GASOLIN TIER3 I         I           ORATIVE MILY         GASOLINE         I	(g/           OK         *           GASOLINE- JL         0.050           JL         TIER3 E10         0.050           PREM         0.050           4K         *           4K         *           7 @ 50K         COLD CO E10 P           7 @ UL         GASOLINE           9 50K         COLD CO E10 P           FUEL TYPE         NMOO (g.           FUEL TYPE         CERT           GASOLINE- TIER3 E10 PREM         STD           GASOLINE- TIER3 E10 PREM         STD           GASOLINE- TIER3 E10 PREM         STD           GASOLINE- TIER3 E10 PREM         ORVR (g/gallo           ORATIVE MILY         GASOLINE- TIER3 E10         O           ORATIVE MILY         ORVR (g/gallo           ORATIVE MILY         GASOLINE- TIER3 E10         O	(g/mi)           CERT         ST           0K         *         *         *           0L         GASOLINE- TIER3 E10         0.050         0.0           4K         *         *         *           4K         *         *         *           7         0L         GASOLINE- PREM         GASOLINE-TIE           0         50K         COLD         COLD         FUEL           7         0L         GASOLINE-TIE         *         *           0         50K         COLD         CO         E10         PREMU           7         0L         GASOLINE-TIE         *         *         *           FUEL TYPE         CERT         *         *         *           GASOLINE- TIER3 E10         STD         *         *           GASOLINE- TIER3 E10         STD         *         *           ORATIVE         FUEL TYPE         3DH         *           GASOLINE- TIER3 E10         0.289         *         *           ORVR / FUEL ONLY / CANISTER BL         ORVR (g/gallon) @ U         *           GASOLINE- TIER3 E10         0.02         0	(g/mi)           CERT         STD           OK         *         *         *           GASOLINE- JL         GASOLINE- TIER3 E10         0.050         0.070           PREM         *         *         *           4K         *         *         *           T@ 50K         FUEL TYPE         FUEL TYPE           7@ 0L         GASOLINE-TIER3         GASOLINE-TIER3           @ 50K         COLD         CO         E10         PREMIUM GA           Ø 50K         COLD         CO         E10         PREMIUM GA           Ø 50K         COLD         CO         E10         PREMIUM GA           Ø 50K         COLD         CO         E10         PREMIUM GA           FUEL TYPE         K         CERT         *         I           GASOLINE- TIER3 E10         STD         *         I         I           ORATIVE MILY         FUEL TYPE         SDH (g         GASOLINE- TIER3 E10         0.289         0.           ORVR / FUEL ONLY / CANISTER BLEED         ORVR (g/gallon) @ UL         I         I           ORATIVE MILY         GASOLINE- TIER3 E10         0.02         0.20	(g/mi)   (g/mi)	(g/mi)         (g/mi)           OK         *         *         STD         CERT         STD           OK         *         *         *         *         *         *           IL         GASOLINE-         0.050         0.070         0.4         1.           PREM         *         *         *         *         *           IL         GASOLINE-         FUEL TYPE         FUEL TYPE         *         *           FUEL TYPE         COLD CO E10 PREMIUM GASOLINE (TIEL         ISIO         *         *           FUEL TYPE         CERT         *         VSO6         *           FUEL TYPE         CERT         *         *         *           GASOLINE-         STD         *         *         *           GASOLINE-         STD         *         *         *           IBIN         UNOG PREM         GASOLINE-         *         *<	(g/mi) (g/mi) (g/mi)   (g		(g/mi) (g/m			(g/mi) (g/m		Image: market in the state in the	

CALIF	ORNIA IRCES BOARD	DAIMLER AG	Executive Order: A-003-0681 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4								
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)											
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	RT STD								

EVAPORATIVE FAMILI	ELAN I AMILE I		state and the second second second
LMBXR0095LNA	KMBXR0095LNA-LNA	*	0.02

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR	: VEHICLE MODELS INFORMATION
-----------------	------------------------------

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MERCEDES BENZ	A 220	PC	2.0	A7	LMBXR0095LNA	1	P
MERCEDES BENZ	A 220 4MATIC	PC	2.0	A7	LMBXR0095LNA	1	P
MERCEDES BENZ	A 250	PC	2.0	A7	LMBXR0095LNA	1	P
MERCEDES BENZ	A 250 4MATIC	PC	2.0	A7	LMBXR0095LNA	1	P