

GENERAL MOTORS LLC.

Executive Order: A-006-2210-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODEL YEAR	TE	ST GROUP		VEHICL	E CLASS(E	S)		FUEL CATEGORY			FUEL TYPE		
2020	LGN	1XV01.5010			PC		1	DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSI								ORY	INTERIM / IN	TER	ERMEDIATE IN-USE STD		
EXH/0	ORVR	EVAP	FTP S			SF	FTP FTP			SFTP			
150	000	150000		LEV3	SULEV30	ULEV30 LEV 3 CO			re *		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	E STATE OF THE STA	NGINE DISPLACEMENT (L)		
1 DFI, TWC, HO2S(2), TC, CAC								FULL	*	è			
*					200	Р	ARTIAL	ALL MODELS	1.5				
*					1	0.00000	TIAL WITH FINES	*					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							, EVAP EMISSION STD VEHICLE CLASS				SPECIAL FEATURES		
LGMXR011030C LEV 2						EV 2 P					HCT		
LGMXR01103AA LEV					ON2 WITH	FEL		PC			HCT		
				E	EMISSION C	REDIT	INFO	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NOI ZERO-EVAP							ZEV	NMOG CREDIT FOR DOF			OPTIONAL EXH. STD FOR WORK TRUCKS		
N N								N N					
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	CH4 RAF RATIO HCHO/NMHC RATIO NMOG+NOX FL PC+LDT (0-37-10) (g/mi)				0-375		W) LDT (3751 LVW-8500 MDV (10			NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*	0	.065			0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



GENERAL MOTORS LLC.

Executive Order: A-006-2210-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-006-2210 dated May 30, 2019.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2511 day of October 2019.

Allen Lyons, Chief

Emissions Certification and Compliance Division



GASOLINE-

TIER3 E10

LGMXR01103AA

0.211

0.300

0.300

0.251

0.300

0.300

0.00

0.05

GENERAL MOTORS LLC.

Executive Order: A-006-2210-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

	EXH					IVE EMI						THE RESERVE	The same of the same of the same of		:LS	
		EXH				NDARDS A										
	FU	JEL TY	1	monoxio adjustm ORVR [de; NOx: ent factor g HC/gall	IMOG: non- oxides of ni r; 2DHS/3D lon dispens egrees Fahr	trogen HS [g ed]: on	; HCHO: HC/test]: i-board re	formalo 2/3 day fueling	dehyde; P /s diurnal- vapor red	M: particu +hot-soak covery; g:	late r ; RL [gram	natter; RA g HC/mi]: ; mg: milli	F: rea runni gram	activi ng lo	ty ss;
					OG+NOx g/mi)		CO (g/mi)			NOx g/mi)	1	HCH(mg/n			PM (g/mi)	
				CERT ST		D CER	RT STD		CERT	STD	CERT		STD CEI		RT.	STD
FTP@5	0K	*		*	*	*		*	*	*	*		*	*		*
FTP@L	11	SOLIN ER3 E		0.008	0.0	30 0.7		1.0	*	*	*		4	4 *		0.01
50°F @4	50°F @4K *			*	*	*		*	*	*	*	*		10/10	(在)特別學學學	
					FUEL TYPE					NMOG+NOx					(g/mi)	
1									CERT		STD			STD		
HWFE	T @ 50I	<			*	*			*		*	2000			Hickory Company	
HWFET @ UL GASOLINE-TIER3 E10								0	0.002 0.030		4,000,000					
20°F @ 50K COLD CO E10 REGULAR GASOLIN						E (T	IER3)			Y-11.	1.0		10.0			
				SFTP E	XHAUST	EMISSION	STAI	NDARDS	AND (CERTIFIC	ATION L	EVEL	.S			
				US06						SC03			COI	MPOS	SITE	
	FUEL T		23727		OG+NOx (g/mi)	CO (g/mi)	(PM (mg/mi)		G+NOx J/mi)	CO (g/mi)	NMOG+NOx (g/mi)		CO (g/mi)		PM (mg/mi)
@ 4K	@ 4K *		* CERT		RT *		*		*		*					
		8		TD *		*			*		*					
		GASOLINE- SIER3 E10		т *		*		*		*		*		0	. 7	*
						* *					*	*	(0.083		. 2
			BIN													a la desert
		WI	HOLE '	VEHICL	E EVAP	ORATIVE E	MISS	ION STA	NDAR	OS AND	CERTIFIC	ATIO	N LEVEL	S		
FVΔΡ	ORATI	VE				WHOLE		LE EVAF					RL	. (a/m	i) @	ÜL
FAMILY FU		FUEL	TYPE		S (g/test) ((g/test) @ UL			S (g/test)) @ UL	@ UL		RL (g/mi) @		JL	
					CERT	STD	FEI	_ CE	RT	STD	FE	<u> </u>	. CER		r STE	
I TOMOVONII NAMO I			GASOL TIER3		0.249	0.50	*	0.3	136	0.65	*		0.00		0.05	



CHEVROLET

GENERAL MOTORS LLC.

Executive Order: A-006-2210-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g/gallon) @) UL	FUEL TYPE		3DHS R (g/test			RIG TEST t) @ UL	BLEED C TEST (g/t	ANISTER est) @ 4K		
	FUEL TYP	E CERT	STD			CERT	STD	CERT	STD	CERT	STD		
LGMXR011030C	GASOLINE TIER3 E1	1 0 07	0.20	*		*	*	*	*	*	*		
LGMXR01103AA	GASOLINE TIER3 E1	1 0 05	0.20	GASOLINE- TIER3 E10		*	*	*	*	0.009	0.020		
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)													
EVAPORATIVE	FAMILY	LEA	K FAMIL	LY		CE	RT		STD				
LGMXR0110	3AA	LGMXR0	1103AA	-LK1		*		0.02					

t: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION **EVAPORATIVE EXH** OBD TRANS TYPE **VEH CLASS** ENGINE (L) MODEL MAKE **FAMILY ECS** LGMXR011030C 1 P 1.5 CV PC CHEVROLET MALIBU LGMXR01103AA P CV 1.5 MALIBU PC