

GENERAL MOTORS LLC. Executive Order: A-006-2226 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	IFORI	MATION					
MODE	TERTROMIO			VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE			
2020	LGMXV03.6048			PC E				DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USEFUL	LIFE (miles)		VEH	VEHICLE EMISSION CATEGOR			GORY	INTERIM / IN	TERM	RMEDIATE IN-USE STD		
EXH/ORVR EVAP				FTP			SFTP		FTP		SFTP		
15	150000 150000			LEV3	SULEV30 LEV 3 C			MPOSITE *			*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	ATUS		NGINE DISPLACEMENT (L)		
1		DFI, 2TWC, 2HO2S(2), TWC							*	\prod			
*	*							ARTIAL	ALL MODELS		3.6		
*	* PARTIAL WITH FINES							*					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
1	LGMXR01	33810	L	LEV 2			PC			HCT			
			100 (10) (10 (10) (10) (10) (10) (10) (1		EMISSION C	REDIT	INFO	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON ZERO-EVAP						ON-P	N-PZEV NMOG CREDIT FOR DO			OPTIONAL EXH. STD FOR WORK TRUCKS			
N N								N			N		
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	CH4 RAF RAF RATIO RATIO RHCHO/NMHC RATIO RATIO RHCHO/NMHC RATIO RMOG+NOX FL PC+LDT (0-378 (g/ml)				0-375	50 LVW) LE		NMOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		* 0.065 0.074					*				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



GENERAL MOTORS LLC. Executive Order: A-006-2226

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this day of July 2019.

Allen Lyons, Chief

Emissions Certification and Compliance Division



PREM

GENERAL MOTORS LLC.

Executive Order: A-006-2226 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

							A	TTAC	НМ	ENT				2 3 9 9-			
	EXH	AUST	TAND	EVA	POF	RATIVE	EMIS	SION	STAP	NDAR	DS AND	CERTI	FIC/	ATION	LEVEL	S	
		EXH	AUST E	EMISS	ION S	TANDA	RDS A	ND CER	TIFIC	ATION	LEVELS (FTP, HW	FET,	50°F, 20	°F)		
	FUI	-			CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP												
					NMOG+NOx (g/ml)			CO (g/mi)			NOx g/mi)	HCHO (mg/mi					
					CERT STD		CERT STD		D	CERT	STD	CERT		STD	CERT	STD	
FTP@50	Ж	*		*		#	*	*	一	*	*	*		* *		*	
FTP@U		OLIN ER3 E		0.01	0 0	0.030	0.2	1.	0	*	*	* .		4	*	0.01	
50°F @4	ıK	*		*		*	*	*		*	*	*		×			
					FUEL TYPE					. N	IMOG+NC	x (g/mi)		CO (g/mi)			
										CERT		STD		CERT		STD	
HWFET	@ 50K					*					*	*		- 1. - 1.			
HWFE	HWFET @ UL			GASOLINE-TIER3 E10						0.	0.002 0.030						
20°F	@ 50K	C	OLD CO	O E10 REGULAR GASOLINE (TIER3)					33)					2.7 10.0		10.0	
			S	FTP E	XHA	JST EM	ISSION	STAND	ARDS	AND	CERTIFIC	ATION LE	VEL	S			
				SFTP EXHAUST EMISSION STANDARDS US06						1	SC03			COMPOSITE			
FUEL T		YPE	YPE		NMOG+NOx (g/ml)		CO PN (g/ml) (mg/			NMOG+NOx (g/ml)		CO (g/mi)	NMOG+NOx (g/mi)		CO (g/mi	PM (mg/mi)	
@ 4K	*	* CER			*		*			*		*					
					*		*		************	#		*					
		ASOLINE- IER3 E10 BIN		•	*		* *		A	*		*	0.012		0.3	*	
@ UL					*		*		*		*			.083	4.2	*	
							Kednishbanisan temper							0.050			
		WH	IOLE V	EHIC	LE EV						DS AND C		ATIO	N LEVE	_S		
	ORATIV	E F	UEL T	YPE	WHOLE VEHICLE EVAN					2DHS (g/test) @ UL				RL (g/mi) @ UL			
FA	MILY							STD FEL		CERT STD		FEL		CERT		STD	
LGMXR0133810			ASOLI TIER3 PREM	ENE- E10 0.403			.50	* 0.2				*			0.00		
C	RVR / F	UEL	AND RESIDENCE AND RESIDENCE		STER	BLEED	EVAP	ORATIVI	E EMI	SSION	STANDA	RDS AND	CER	TIFICAT	TION I EV	/FI S	
		T	ONLY / CANISTER BLEED EVAPORA						FUEL ONLY EVAP & CANIST								
I considerate and	EVAPORATIVE FAMILY		ORVR	(g/gai	lon) @) UL	_ TYPE	30		G TEST	2DHS RIG TI (g/test) @ l		TEST BLEED CANIS				
	er en	FL	JEL TY	PE C	ERT	STD			-	ERT	STD	CERT		STD	CERT	STD	
LGMXR0133810		CONT. IN CONT.	SOLIN ER3 E	S 8	.00	0.20		*			*	*		*	*	w	



GENERAL MOTORS LLC. Executive Order: A-006-2226

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
*	*	*	*						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT; certification; STD: standard; FEL; family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic: DOR; direct ozone reducing; HCT; hydrocarbon trap; BCAN; bleed carbon canister; prefix 2; parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission: SCV: selectable continuously variable transmission: AM: automated manual transmission: AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION **EVAPORATIVE EXH** ENGINE (L) **TRANS TYPE** MAKE MODEL **VEH CLASS** OBD **FAMILY ECS** CHEVROLET 3.6 LGMXR0133810 IMPALA PC SA6 P