

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	FOR	MATION					
MOD		TEST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
202	0 L	GMXT02.0500			LDT3	DEDICATED SIN VEHICL					GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSIO						ION C	N CATEGORY INTERIM / INTERMEDIATE IN-U						
EXH/ORVR EVAP FTP						SFTP FTP				SFTP			
1	50000	150000)	LEV3	ULEV50	LEV	3 CC	MPOSITE	PM		РМ		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							-	OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1	1 DFI, TWC, WR-HO2S, HO2S, TC, CAC					たまたの何		FULL	*	10000			
*		*					P	ARTIAL	ALL MODELS	1000	2.0		
*	* *							TIAL WITH FINES	· *	-			
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EV	AP / OR	VR FAMILY	EVA	PORATIVE	E STD CATE	GORY	EVAP EMISSION STD VEHICLE CLASS			S	SPECIAL FEATURES		
	LGMXR0	15740B	LE	V 3 OPTI	ON2 WITH	FEL		LDT3			HCT		
				E	EMISSION C	REDIT	INFO	ORMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON- ZERO-EVAP						ZEV	XEV NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS			
		N			N			N N					
				NMOG	AND FLEET	T AVE	RAGI	E INFORMA	TION		-		
NMOG RAF	G CH4 RAF	FTP NMOG/NMHO RATIO		IO/NMHC RATIO	DC+1 D1 /0-3750								
*	*	1.10		*	0	.065			0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



GENERAL MOTORS LLC.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 18^{12} day of October 2019.

len Lyons, Chief

Remissions Certification and Compliance Division



FUEL TYPE

GENERAL MOTORS LLC. Executive Order: A-006-2235 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMEN	Т
-----------	---

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

The second second													
				G+NOx mi)		O mi)		Dx mi)		HO J/mi)		/M /mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL	OUL GASOLINE- TIER3 E10		0.029	0.029 0.050	1.0	1.7	*	*		4	0.001	0.003	
50°F @4K		*	*	*	*	*	*	*	*	*			
A CONTRACTOR							NN	NMOG+NOx (g/mi)			CO (g/mi)		
FUEL TYPE						CE	CERT		CEF	RT	STD		
HWFET @ 50K			*						*				
HWFET @	DUL		GASO	LINE-TIE	R3 E10		0.0	13	0.050	in Grand States			

			 的复数的 法规则 化化学 化化学	行動構成の設備に対象になる
20°F @ 50K	COLD CO E10 REGULAR GASOLINE (TIER3)	$ \begin{array}{l} (1,1,1) \\ (1,1,1) $	1.3	12.5

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS COMPOSITE **US06** SC03 PM NMOG+NOx CO NMOG+NOx co PM FUEL TYPE NMOG+NOx co (g/mi) (mg/mi) (g/mi) (g/mi) (g/mi) (g/mi) (mg/mi) (g/mi) * * CERT * * * @4K * * * STD * CERT * * 1 * * 0.021 0.8 * GASOLINE-* 6 * * 0.083 4.2 * STD * @ UL TIER3 E10 0.070 BIN

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WF	IOLE \								
EVAPORATIVE FAMILY	FUEL TYPE	3	3DHS (g/test) @ UL				HS (g/test)		RL (g/mi) @ UL			
		CER	CERT S		FEL	CERT	STD	FEL	CE	RT	STD	
LGMXR015740B	GASOLINE- TIER3 E10 0.292 0		92 0.	500	0.450	0.264 0.500		0.450 0.		00	0.05	
ORVR / FUI	ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS											
						FUEL C	UEL ONLY EVAP & CANISTER BLEED					
EVAPORATIVE FAMILY	ORVR (g/g	DRVR (g/gallon) @ UL			L TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K		
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD	
LGMXR015740B	GASOLINE- TIER3 E10	0.02	0.20		OLINE- R3 E10	*	*	*	*	0.012	0.020	

	FORNIA DURCES BOARD		NERAL MOTORS LLC.	Executive Order: A-006-2235 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4								
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE FAMILY	LEAK FAMILY		CERT	Г	STD							
LGMXR015740B	LGMXR015740B-LK1		*		0.02							
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: su ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxid heated/oxygen sensor; WR-H RDQS: reductant quality sen EGRC: EGR cooler; AIR/AIR fuel injection; DFI/IFI: direct/i full/partial/partial with fines o prefix 2: parallel; (2) suffix: si device (ex. DPF-SCRC: SCF ethanol ("15%"gasoline) fuel	LGMXR015740BLGMXR015740B-LKI*0.02** not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2:											

EAER: equivalent AER; PHEV: plug-in hybrid electric vehic credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
CADILLAC	XT5 AWD	LDT3	2.0	SA9	LGMXR015740B	1	P
CADILLAC	XT5 FWD	LDT3	2.0	SA9	LGMXR015740B	1	P
CHEVROLET	BLAZER AWD	LDT3	2.0	A9	LGMXR015740B	1	P
CHEVROLET	BLAZER FWD	LDT3	2.0	A9	LGMXR015740B	1	P
GMC	ACADIA AWD	LDT3	2.0	A9	LGMXR015740B	1	P
GMC	ACADIA FWD	LDT3	2.0	A9	LGMXR015740B	1	P