

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC		FOR	MATION					
MODE		EST GROUP VEHICLE CLASS(ES)					FUEL CATEGORY				FUEL TYPE		
2020 LGMXD02.8360 MDV4									SINGLE FUEL ICLE		DIESEL		
	USEFUL	LIFE (miles)		VEH	ICLE EMISS	ION C	CATE	GORY	INTERIM / IN	ITER	MEDIATE IN-USE STD		
EXH/ORVR EVAP				FTP			SF	TP	FTP		SFTP		
150000 *				LEV3	LEV3 ULEV250 BAG2, SCO TEST CY			CO3, FTP	FTP *		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							-	OBD S	STATUS		ENGINE DISPLACEMENT (L)		
1	OC, SCI	RC, OC+DPF, NOXS (2		TC, CAC MS, RDQS		кС,		FULL	*				
2 OC, SCRC, OC+DPF, DFI, TC, CAC, EGR, EGRC, NOXS(2), PMS, RDQS, FFH P/								PARTIAL	*		2.8		
* *							PAR	RTIAL WITH FINES					
		E	/APO	RATIVE &	REFUELING	i (EVA	AP/OR	VR) FAMIL	INFORMATIO	N			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY EVAP EMISSION STD VEHICLE CLASS							S	SPECIAL FEATURES					
* *					*				*		*		
				l	EMISSION C	REDI		ORMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON- ZERO-EVAP							PZEV NMOG CREDIT FOR DO			R	OPTIONAL EXH. STD FOR WORK TRUCKS		
	1	N			N				N		N		
				NMOG	AND FLEE	T AVE	RAG	E INFORMA	TION				
NMOG RAF	E DAE NMOG/NMHC DATIO LDT (3751 LVW-8500 GVW) MDV (8501-10000 GVWR) MDV (10,0					NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)							
*	*	*		* * 0.228 0.349						0.349			
See th	o Attook	mont for Vah		adala Ev	oporativa Ec	milu	Engi	no Dicology	mont Emissi		ontrol Systems Phase-		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



GENERAL MOTORS LLC.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the listed vehicle models has been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

BE IT FURTHER RESOLVED:

The fuel-fired heater incorporated in the listed vehicle models must not operate at ambient temperature above 40 °F (13 CCR Section 1961.2(a)(13) [Emission Standard for a Fuel-Fired Heater]).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______day of November 2019.

Allen Lyons, Chief Emissions Certification and Compliance Division

CALIFORNIA AIR RESOURCES BOARD						GE	GENERAL MOTORS LLC.				Executive Order: A-006-2238 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4							
							AT	ТАС	нм	ENT								
	EXHAL	JST	AND	EVA	POR	ATIVE	EMISS	ION S	STAR	NDAR	DS AN	D CER	TIFIC	ATION	LEV	ELS		
	E	XHA	UST E	MISSI	ON S	TANDA		CER	TIFIC	ATION	LEVELS	(FTP, H	WFET	, 50°F, 20)°F)			
	FUEL TYPE		monoxi adjustm ORVR 1000 m		le; NC ent fa g HC/	Dx: oxid ctor; 2D gallon c	G: non-Cl es of nitro HS/3DHS lispensed] es Fahren	gen; H [g HC : on-bo	CHO: /test]: oard re	formal 2/3 da efueling	dehyde; F ys diurna y vapor re	PM: parti l+hot-so covery;	culate ak; RL g: gran	matter; R [g HC/mi] n; mg: mi	AF: re]: runn lligram	activi ing lo ı; mi:	ty ss;	
				NMHC+NOx (g/mi)			CO (g/mi)				NOx g/mi)		HCH (mg/m			PM (g/mi)		
			-	CERT STD		STD	CERT	STD		CERT	STD	CE	RT STD		CERT		STD	
FTP@5	ok	*		* *		*	*	*		*	*		*	*	*		*	
FTP@L	JL DIES	EL-EF	PA	0.124 0.250		.250	0.1	6,4	4	*	*		*	6		01	0.008	
50°F @	4K	*		*		*	*	*		*	*		*	*				
	an an profes			FUEL TYPE							NMHC+NOx (g/mi					CO (g/mi)		
										C	CERT STE		D	CERT		STD		
HWFE	T @ 50K					*					*	*				63		
HWFE	T @ UL				DIE	SEL-EI	A			0	0.020 0.25		50	0				
20°F	@ 50K					*								*			*	
			S	FTP EX	KHAL	JST EM	ISSION S	TAND	ARDS	AND	CERTIFIC	CATION	LEVE	S				
		UEL TYPE				ι	S06				SC03			MPO	SITE			
	FUEL TY				NMHC+NOx (g/mi)		CO (g/mi)	P (mg			IC+NOx g/mi)	CO (g/mi)				CO /mi)	PM (mg/mi	
@ 4K	*	* CE			*		*				*	*						
			STD		*			*		-	*	*	-23 ⁴ -1	0.120				
<u> </u>		CE			*		*		k k		*	*		0.120		0.0	1	
@ UL			STD	Astronomic	*		*	1.161.2	• 	3 - 1 - K		*		*	2	2.0	7	
		WHO		EHICL	FFV			SSION	STA	NDAP		CERTIF	CATIC					
		T					HOLE VE											
EVAPORATIVE FAMILY		FUEL T		FUEL TYPE		3DHS (g/test) @) @ UL		2DHS (g/test)		t) @ UL	@ UL		RL (g/mi) @ UL			
					CEF	RT STD		FEL	CE	RT	RT STD		EL	CERT		STD		
	*		*		*		*	*		*	*		*	*			*	
(DRVR / FU	EL O	NLY /	CANIS	STER	BLEED	EVAPO	RATIV								LEVE	LS	
EVAPORATIVE FAMILY		ORVR (g/gal			/gallon) @ UL			30		OHS R	UEL ONLY EVA HS RIG TEST g/test) @ UL		2DHS RIG		TEST BLEED			
		FUEL T		YPE CERT STD		FUEL TYPE			(g/test	STD	CEF				TEST (g/test			
		FUEL ITFE			*	*	*			*	*			*		*		
		EFFE	CTIV	E LE			ER STA	NDAF			RTIFIC	ATION	EVE	L (INCH	ES)			
EVA	EVAPORATIVE FAMILY LEAK FAM													STD				
*						*			*					*				

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW: MDV: medium-duty vehicle: MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle: ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: sem -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	ОВІ
CHEVROLET	G2500 EXPRESS 2WD CARGO	MDV4	2.8	A 8	*	1	\$
CHEVROLET	G2500 EXPRESS 2WD CARGO	MDV4	2.8	A 8	*	2	\$
CHEVROLET	G2500 EXPRESS 2WD PASS	MDV4	2.8	A 8	*	1	\$
CHEVROLET	G2500 EXPRESS 2WD PASS	MDV4	2.8	A 8	*	2	\$
CHEVROLET	G3500 EXPRESS 2WD CARGO	MDV4	2.8	A 8	*	1	\$
CHEVROLET	G3500 EXPRESS 2WD CARGO	MDV4	2.8	A 8	*	2	\$
CHEVROLET	G3500 EXPRESS 2WD PASS	MDV4	2.8	A 8	*	1	\$
CHEVROLET	G3500 EXPRESS 2WD PASS	MDV4	2.8	A 8	*	2	\$
GMC	G2500 SAVANA 2WD CARGO	MDV4	2.8	A 8	*	1	\$
GMC	G2500 SAVANA 2WD CARGO	MDV4	2.8	A 8	*	2	\$
GMC	G2500 SAVANA 2WD PASS	MDV4	2.8	A 8	*	1	\$
GMC	G2500 SAVANA 2WD PASS	MDV4	2.8	A8	*	2	\$
GMC	G3500 SAVANA 2WD CARGO	MDV4	2.8	A 8	*	1	\$
GMC	G3500 SAVANA 2WD CARGO	MDV4	2.8	A 8	*	2	\$
GMC	G3500 SAVANA 2WD PASS	MDV4	2.8	A 8	*	1	\$
GMC	G3500 SAVANA 2WD PASS	MDV4	2.8	A8	*	2	\$