

FORD MOTOR COMPANY

Executive Order: A-010-2189 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	FOR	MATION					
MODE	_	ST GROUP	VEHICL	LE CLASS(ES)			FUEL C	ATEGORY		FUEL TYPE			
2020	LFI	XV02.0VEN			PC		I		SINGLE FUEL HICLE	GASOLINE			
	USEFUL	LIFE (miles)		VEH	ICLE EMISS	ION C	ATEC	ORY	INTERIM / IN	TERM	RMEDIATE IN-USE STD		
EXH	/ORVR	EVAP		FTP SFTP			ГР	FTP		SFTP			
15	0000	150000	LEV3	ULEV70 LEV 3 COMPO			MPOSITE	*		*			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	OBD STATUS		ENGINE DISPLACEMENT (L)		
1	O2S, TC,	CAC, DFI			FULL	ALL MODELS							
*								ARTIAL	*		2.0		
*	* * * * * * * * * * * * * * * * * * * *							TIAL WITH	*	*			
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								SSION STD E CLASS	SF	SPECIAL FEATURES		
LFMXR0130NDE LEV 3 OPTI					ON2 WITH	FEL	PC				HCT		
				E	EMISSION C	REDIT	INFO	RMATION					
N/N CF		EDIT FOR N ZERO-EVAP	NIM()(= (:)			G CREDIT FOR DOR		OPTIONAL EXH. STD FOR WORK TRUCKS					
N						И				И			
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	MMOG/MMHC			CHO/NMHC RATIO	NMOG+NC PC+LDT (V) LDT	NMOG+NOX FLEET ST LDT (3751 LVW-8500 GVWR) + MDPV (g/mi		MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	C	.065			0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



FORD MOTOR COMPANY

Executive Order: A-010-2189

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Allen Lyons, Chief

Emissions Certification and Compliance Division



FUEL TYPE

GASOLINE-TIER3 E10

LFMXR0130NDE

CERT

0.01

STD

0.20

GASOLINE-TIER3 E10

FORD MOTOR COMPANY

Executive Order: A-010-2189 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

							A	TTAC	HME	ENT									
	EXHA	UST	AND	EVA	PORAT	IVE	EMIS	SSIONS	STAN	DAR	DS AND	CERTI	FICA	ATION	LEVE	ELS			
		EXH	AUST	EMISSI	ON STAI	NDA	RDS A	ND CERT	IFICA	TION	LEVELS (FTP, HW	FET,	50°F, 20	°F)	***********			
	FUEL ⁻		monoxio adjustm ORVR I			oxide ; 2D on di	es of nit HS/3DI ispense	CH4 orga trogen; H0 HS [g HC/ ed]: on-bo enheit; FT	CHO: f test]: 2 ard re	formalo 2/3 day fueling	lehyde; P 's diurnal- vapor red	M: particu hot-soak covery; g:	late n ; RL [gram	natter; R g HC/mi] ; mg: mil	AF: rea : runni igram;	activi ng lo	ty ss;		
						NMOG+NOx			CO (g/mi)			NOx (g/mi)			HCHC (mg/m			PM (g/mi)	
Š.			ŀ	(g/mi) CERT STD		\rightarrow	(g/mi) CERT STD		, +	(g/mi) CERT STD		CERT		STD	CERT STD				
FTP@50K		*		*	*		*	*		*	*	*			*				
FTP@UI GASOI		OLIN	1 0 05		0.0	70	1.2	1.7	,	*	*	*	*		*		0.01		
50°F @4	K	*		*	*		*	*		*	*	*	*						
					EIIEI .	TVD	=			N	MOG+NO	x (g/mi)			CO (g	/mi)			
				FUEL TYPE						C	ERT	STD		CERT		STD			
HWFET	@ 50K			*							*	*							
HWFE	T@UL			GASOLINE-TIER3 E10						0.	023	0.070							
20°F (@ 50K	CC	OLD CO	E10	REGULA	R GA	SOLIN	E (TIER	.3)	1				1.0		1	.0.0		
				SFTP E	XHAUST	EMI	ISSION	STANDA	ARDS	AND (ERTIFIC	ATION LI	EVEL	S					
				US06						SC03			COMPOSITE						
	FUEL T	L TYPE		NMOG+NOx (g/mi)		1	CO PM (g/mi) (mg/m			NMOG+NOx (g/mi)		CO (g/mi)				o mi)	PM (mg/mi)		
@ 4K	AK *		CERT		*		*			*		*				1,4-0			
					*		*				*	*							
	CER		CERT		*		* *		r	*		*	* 0		1	. 4	*		
@ UL				SASOLINE- SIER3 E10 SI		STD *			* *		۲	*		* (0.083		. 2	*
													(0.070					
		WH	IOLE \	/EHICL	E EVAP	ORA	TIVE E	MISSION	STAN	NDAR	S AND C	ERTIFIC	ATIO	N LEVE	LS				
						WH	HOLE \	/EHICLE	EVAP	ORAT	IVE TEST	ING		_	I /I	🙃			
EVAPORATIV FAMILY				. TYPE 3DHS (g			g/test) @ UL			2DHS (g/test)		@ UL		RL (g/mi) @ UL		UL			
						STD		FEL	CE	RT STD		FE	FEL CEI		T STE		STD		
LFMXR	0130ND	GASOLINE- TIER3 E10		0.207	0.	.300	0.300	0.1	.44	0.300	0.300		0.000		0.05				
C	RVR / F	UEL	ONLY	CANI	STER BL	EED	EVAP	ORATIVE								EVE	LS		
	ORATIV	E	ORVR	/R (g/gallon) @ UL 31				3D	UEL ONLY EVAP & CANISTI DHS RIG TEST 2DHS RIG			RIG	TEST BLEED CANISTER						
FAMILY						FUEL TYPE			(g/test)	@ UL	(g/test) @ UL			TEST (g/test) @ 4K				

CERT

STD

CERT

STD

CERT

0.007

STD

0.020



FORD MOTOR COMPANY

Executive Order: A-010-2189

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
LFMXR0130NDE	LFMXR0130NDE-001	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	FUSION AWD	PC	2.0	SA6	LFMXR0130NDE	1	F
FORD	FUSION FWD	PC	2.0	SA6	LFMXR0130NDE	1	F
LINCOLN	MKZ AWD	PC	2.0	SA6	LFMXR0130NDE	1	F
LINCOLN	MKZ FWD	PC	2.0	SA6	LFMXR0130NDE	1	F