

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP IN	IFOR	MATION					
MODE		EST GROUP		VEHICL	E CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE		
2020	) LG	MXV06.2091	XV06.2091 PC						DEDICATED SINGLE FUEL VEHICLE				
USEFUL LIFE (miles) VEHICLE EMISSION							ATE	SORY	MEDIATE IN-USE STD				
EXH/ORVR EVAP					FTP SI			FTP FTP			SFTP		
15	50000	000 150000 LEV3 ULEV125 LEV 3 COMPOSITE *				*							
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	BD STATUS		ENGINE DISPLACEMENT (L)		
1		DFI, 2WR-H	102S,	2TWC, 21	HO2S	And Million		FULL	ALL MODELS	「「「「「「「」」」」			
*	*							ARTIAL	*		6.2		
*		*						TIAL WITH FINES	*				
		E	APO	RATIVE &	REFUELING	G (EVA	P/OR	VR) FAMIL	INFORMATIO	N			
EVA	AP / ORV	R FAMILY	EVA	PORATIVE	E STD CATE	GORY	ORY EVAP EMISSION S VEHICLE CLAS			SPECIAL FEATURES			
	LGMXR01	383CC	LE	EV 3 OPTI	ON2 WITH	FEL		I	2C	HCT			
				E	EMISSION C	REDIT		ORMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV	EV NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N	N			
				NMOG	AND FLEE	TAVE	RAG	E INFORMA	TION		2		
NMOG RAF	CH4 RAF					(0-375		V) LDT	IMOG+NOX FLEET STI LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)				
*	*	1.10		*	(	0.065 0.074 *					*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2220 day of January 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

**GENERAL MOTORS** LLC.

Executive Order: A-006-2237 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

## **ATTACHMENT**

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

和我们的自己的												
				G+NOx mi)				Dx mi)		HO /mi)		M mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	5	*	*	*	*	*	*	*	* *		*	*
FTP@UL	TIE	OLINE- R3 E10 PREM	0.055	0.125	0.6	2.1	*	*	*	4	0.002	0.003
50°F @4K	TIE	OLINE- R3 E10 PREM	0.049	0.250	0.4	2.1	*	*	*	16		
	1月1日 日本 1月1日日 1月1日日日						NN	IOG+NO>	(g/mi)	Τ	CO (g/mi	)
	FUEL TYPE						CE	RT	STD	CEF	т	STD
HWFET @	) 50K		*				*	* *		rasi shirin Takazin da	the states and the second s	
HWFET @ UL		GASOLINE-TIER3 E10 PREM					0.0	55	0.125			
20°F @	50K	COLD (	COLD CO E10 PREMIUM GASOLINE (TIER3)							1.	9	10.0
			SFTP EXH	AUST EM	ISSION S	TANDAR	S AND C	RTIFICA	TION LEVE	LS	energy and an and a second	

SETP EXHAUST EMISSION STANDARDS AND CERTIFICATION | EVELS

		51	IP EXHAUSI	EMISSION	STAND	ARDS AND	CERTIFIC	ATION L	EVEL	>		
				US06			SC03			COM		
	FUEL TYP	E	NMOG+NOx (g/mi)	CO (g/mi)			lOG+NOx (g/mi)	CO (g/mi)		)G+NOx g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	* * * *			* *					
-		STD	*									
		CERT	*	*		1	*	*	0.040		0.5	*
@ UL	GASOLINE TIER3 E1 PREM		*	* *		6	*	*	0.083		4.2	*
		BIN		da legiolitzation		nustral fact	ale to the or	a di santa sere	0.120		a shi shudi ket	
	٧	VHOLE VE	HICLE EVAP	ORATIVE E	MISSION	STANDA	RDS AND C	ERTIFIC	ATION	LEVELS	5	
				WHOLE	VEHICLE	EVAPORA	TIVE TEST	ING				
	ORATIVE	FUEL TYPE		3DHS (g/test) @ UL			2DHS (g/test) @ UL				RL (g/mi) @ UL	
			CERT	STD	FEL	CERT	STD	FE	L	CERT		STD
LGMXI	R01383CC	GASOLIN TIER3 E PREM	10 0.265	0.300	0.500	0.233	0.300	0.5	00	0.00		0.05

A	ALIF	ORN RCES BO	IIA DARD	GENERAL MOTORS LLC.			Executive Order: A-006-2237 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4					
ORVR / FUE	L ONLY / CA	NISTER	BLEED	EVAPORA	TIVE EMISS	ON S	STANDAF	RDS AN	ID CER	TIFICA	TION LEVI	ELS
				FUEL ONLY EVAP & C					NISTER BLEED			
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL		UL	FUEL TY			@ UL		SRIGT est)@		BLEED C/ TEST (g/te	
	FUEL TYPE	CERT	STD	IOLLII	CER		STD	CER		STD	CERT	STD
LGMXR01383CC	GASOLINE- TIER3 E10 PREM	0.04	0.20	GASOLIN TIER3 E PREM	* 10		*	*		*	0.007	0.020
E	FFECTIVE	LEAK D	IAMET	ER STANI	DARD AND	CEF	RTIFICAT	TION L	EVEL	(INCHE	ES)	
EVAPORATIVE	FAMILY	LEA	K FAMIL	Y		CER	Т		STD			
LGMXR0138	3CC -	LGMXR0	1383CC	-LK1 *					0.02			
duty passenger ver emission limit; GVV ULEV: ultra LEV; S ADSTWC: adsorbin SCRC/SCR-N or S continuous/periodid heated/oxygen ser RDQS: reductant of EGRC: EGR coole fuel injection; DFI/I full/partial/partial w prefix 2: parallel; (2 device (ex. DPF-S) ethanol ("15%"gas -automatic transmi automated manual EAE: equivaler of Y = credits, S = cre	ULEV: super ng TWC; HAC CRC-NH3: se c trap oxidizer isor; WR-HO2 juality sensor; r; AIR/AIRE: s F1: direct/indii ith fines on-bo 2) suffix: serie CRC: SCR co oline) fuel; E1 ssion; CV: co transmission AER; PHEV: p	ULEV; ZE : HC ads elective ca ; DPF: div 2S or AFS ; NH3S: a secondary rect fuel in parted DPF 0: "10%" ntinuously ; AMS: au plug-in hy	EV: zerc orbing c atalytic r esel par 5: wide r ammonia y air inje njection; nostic; [ en (-) b¢ c <sup>-</sup> ); CNG c <sup>-</sup> ); CNG v variab utomate brid ele	-emission v atalyst; WU eduction-un ticulate filter ange/linear/ a sensor; EC ction (belt d TC/SC: turl DOR: direct etween after /LNG: comp ("90%"gasc le transmiss d manual-se	ehicle; IZEV l: warm-up ca ea/ammonia; r (active); GP heated air-fu GR: exhaust g lriven)/(electri bo/super cha ozone reduci t reatment E pressed/liquef bline) fuel; A: ion; SCV: se electable tran	trans talys NH3 F: PM F: PM a rati as re c driv rger; ng; H CS in ied n autor ectat	Istitonal Zt st; NAC: No OC: amm M filter for io sensor; ecirculation ven); PAIF CAC: cha dCT: hydroc ndicates m hatural gas matic (with ble continu sion: OT: c	EV; TVV Ox ads onia ox spark-i NOXS n; HP/L rge air pcarbon ultiple f ; LPG: h lockup uously other tr	crote: a orption o didation o gnited e : NOX se .P EGR: d AIR; S cooler; l trap; B functiona liquefiec b); M: m variable ansmiss	s-way/ox catalyst; engine; F ensor; P : High/Lc SFI/MFI: FFH: fue CAN: ble alities of d petrole anual trr anual trr transmi ;jon; AEF	CTOX/PT CTOX/PT HO2S/O2S MS: PM se ow Pressur sequentia el fired hea eed carbor the after t eum gas; E ansmission ssion; AM: R; all-elect	OX: : e EGR; I/multiport ter; F/P/\$: o canister; reatment 85: "85%" ; SA: sem ric range;
	2020 M	ODEL				Т						0.00
MAKE	мс	DDEL	VE	HCLASS	ENGINE (L	TF	TRANS TYPE		FAI	MILY	ECS	OBD
CHEVROLET	CHEVROLET CORVETTE PC						SA8 LGMXR01383CC 1					F

.