

BAYERISCHE MOTOREN WERKE AG

Executive Order: A-008-0492-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP II	NFOR	MATION					
MODE		EST GROUP		VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE			
202	2020 LBMXJ03.0B5X				LDT2, PC DED				SINGLE FUEL HICLE		GASOLINE		
	USEFUL	LIFE (miles)	VEH	VEHICLE EMISSION CATEGORY				INTERIM / INTERMEDIATE IN-USE STD					
EXH/ORVR EVAP				FTP SF			TP FTP			SFTP			
150000 150000			LEV3	ULEV70	LEV 3 COMPOSITE			*		PM			
SPE	CIAL FE	ATURES & EX	(HAU		ON CONTRO	L		OBD S	TATUS		ENGINE DISPLACEMENT (L)		
1	1 TWC, WR-HO2S, HO2S, DFI, TC, CAC							FULL	*				
*	* *							ARTIAL	*	3.0			
*	* *							RTIAL WITH FINES ALL MODELS					
	-	E	VAP	ORATIVE &	REFUELING	(EVA	P/OR	VR) FAMILY	INFORMATIO	V			
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
- 1	LBMXR0150G30 LEV 3 OPT:					FEL P			PC		* * * * * * * * * * * * * * * * * * * *		
			Ŀ	E	EMISSION CI	REDI	T INFO	ORMATION	1, 1				
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON ZERO-EVAP						ON-P	ZEV	I NIMOG CDENIT EOD DOD			OPTIONAL EXH. STD FOR WORK TRUCKS		
	N N							N N					
				NMOG	AND FLEET	AVE	RAGI	INFORMA	TION				
NMOG RAF	NMOG/NMHC			CHO/NMHC RATIO	NMOG+NOX FLEET PC+LDT (0-3750 L' (g/mi))	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.065		1	0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BAYERISCHE MOTOREN WERKE AG

Executive Order: A-008-0492-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to California Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

This Executive Order hereby supersedes Executive Order A-008-0492 dated March 22, 2019.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this /U day of Ju

Allen Lyons, Chief

Emissions Compliance, Automotive Regulations and Science Division



GASOLINE-TIER3 E10

0.04

0.20

LBMXR0150G30

BAYERISCHE MOTOREN WERKE AG

Executive Order: A-008-0492-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

0.004

0.020

ATTACHMENT

			-						-		DS AND		_						
		FUEL		CH4 mon adju OR\ 1000	: metha oxide; N stment f /R [g H0	ne; NM0 lOx: oxid actor; 2 C/gallon	OG: non- des of ni DHS/3D dispens	-CH4 orga trogen; H HS [g HCa ed]: on-bo	nic ga CHO: f /test]: 2 ard re	s; HC formal 2/3 da fueling	EVELS: hydrocar dehyde; P ys diurnal- y vapor recest proced	bon; NMH M: particu +hot-soak; covery; g:	C: no late r RL [gram	n-CH4 h natter; R g HC/mi ; mg: mi	HC; CO: ca AF: reacti : running ligram; mi	vity loss;			
	14						NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)			HCHO (mg/mi			PM g/mi)	
				CE	RT	STD	CER	T STE) (CERT	STD	TD CER		STD	CERT	STD			
FTP@5	0K		*		*	*	*	*		*	*	*		*	*	*			
FTP@L	GASOLINE- TIER3 E10		10	040	0.070	0.3	1.7		*	* *			4	0.000	0.003				
50°F @4	4K	GASO TIER			033	0.140	0.3	1.7	,	*	*	* *		16					
1162469 373				FI	FUEL TYPE			NMOG+NOx (g/mi)			C		CO (g/mi	CO (g/mi)					
						FUEL TIPE				С	CERT STD		CERT		Т	STD			
HWFET @ 50K			*						*	- *		ATTENDED TO SERVICE	edisələr	da (application design)					
HWFE	Т@	UL			GASOLI	NE-TIE	R3 E10			. 0	.017	0.070		製造型					
20°F (@ 50	K	CO	LD CO E	10 REG	ULAR G	ASOLIN	E (TIER	3)	- a/M.	PERMIT			1.0		10.0			
10-007-00			-	SFT	PEXHA		IISSION US06	STANDA	ARDS	AND (SC03	ATION LE	VEL		MPOSITE				
	ELIEL		TYPE		VMOG+	IOG+NOx CO PM			VI .	NMOG+NOx CO					CO PM				
				Jacobs.	(g/mi)		(g/mi) (mg		mi)	(g/mi)		(g/mi)		g/mi)	(g/mi)	(mg/mi			
@ 4K		*	* CE		CERT		*	*		*		***		*	State of the second			NA SERVICE AND A	
				STD	*		*	2.0		*		*							
	UL GASOLIN			CERT	*		*	1			*	*	0	.039	0.4	*			
@ UL				STD	*		*	6	;		*	*	0	.083	4.2	* *			
			BIN							3,170 F 123 Se Vigad		S. Wijaul	0.070		- FR 1878	18.78 and 19.78 and			
			WH	OLE VEH	ICLE E						DS AND C		TIOI	N LEVE	<u>-S</u>				
EVAPORATIVE FAMILY		F	UEL TYPI				/HOLE VEHICLE EVAP g/test) @ UL			2DHS (g/test) @ UL			RL (g/mi) @ UL						
		I			CE	CERT STD		FEL	CERT		STD	FEL		CER	т	STD			
LBMXR0150G30			ASOLINE	10 1451 0			0.300			0.300	0.300		0.01		0.05				
C	RVF	R / FU	EL C	ONLY / CA	NISTE	BLEE	D EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CER	TIFICA	TION LEV	ELS			
					100000 100						NLY EVA								
EVAPORATIVE FAMILY			E ORVR (g/galle			lon) @ UL FUEL				OHS RIG TEST (g/test) @ UL		2DHS RIG 1 (g/test) @							
			Leu	EL TYPE	CERT	STD	1		CE	n= T	STD	CERT	1 7	STD	CERT	STD			

GASOLINE-

TIER3 E10



BAYERISCHE MOTOREN WERKE AG

Executive Order: A-008-0492-1

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
LBMXR0150G30	LBMXR0150G30-001	0.00	0.02						

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	ОВС
BMW	5401	PC	3.0	SA8	LBMXR0150G30	. 1	\$
BMW	5401 XDRIVE	PC	3.0	SA8	LBMXR0150G30	1	\$
BMW	6401 XDRIVE GRAN TURISMO	PC	3.0	SA8	LBMXR0150G30	1	\$
BMW	M340I	PC	3.0	SA8	LBMXR0150G30	1	\$
BMW	M340I XDRIVE	PC	3.0	SA8	LBMXR0150G30	1	\$
BMW	X3 M40I	LDT2	3.0	SA8	LBMXR0150G30	1	\$
BMW	X4 M40I	LDT2	3.0	SA8	LBMXR0150G30	1	\$
BMW	Z4 M40I	PC	3.0	SA8	LBMXR0150G30	1 1	\$