

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	.8			2	TEST GRO	OUP IN	IFOR	MATION					
MODE							P	FUEL C	ATEGORY		FUEL TYPE		
2020) LE	MXV03.0S55	PC DEI					SINGLE FUEL HICLE		GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSI							MISSION CATEGORY			TEI	RMEDIATE IN-USE STD		
EXH	I/ORVR	EVAP		FTP S				FTP FTP			SFTP		
15	50000	15000	LEV3	ULEV125 LEV 3 COMPOSITE			MPOSITE	*		PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS		ENGINE DISPLACEMENT (L)		
1 2WU-TWC, 2TWC, 2WR-HO2S, 2HO2S, DFI, 2TC, CAC								FULL	*				
* *							Р	ARTIAL	ALL MODELS		3.0		
* *								RTIAL WITH *					
		E	VAPO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	INFORMATIO	N			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GORY		EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
1	LBMXR01	.30N54		L	EV 2			PC			*		
				I	EMISSION CI	REDIT	INFC	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ON-P2	ZEV	EV NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N N					
				NMOG	AND FLEET		RAGE	INFORMA	ΓΙΟΝ				
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO		HO/NMHC RATIO				STD NMOG+NOX FLEET ST W) LDT (3751 LVW-8500 GVWR) + MDPV (g/mi					
*	*	1.10		*	0	.065		0.074			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-008-0493 dated March 22, 2019.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this <u>1374</u> day of February 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

BAYERISCHE MOTOREN WERKE AG Executive Order: A-008-0493-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HO /mi)		M mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K	к *		*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- TIER3 E10		0.069	0.125	0.9	2.1	*	*	*	4	0.002	0.003	
50°F @4K		SOLINE- R3 E10	0.041	0.250	0.3	2.1	*	*	*	16		The said	
A second second							N	IOG+NO	x (g/mi)		CO (g/mi)		
		FUEL TYPE						RT	STD	CEF	RT	STD	
HWFET @ 50K		*				*	* *		and the states				
HWFET @ UL			GASO	LINE-TIE	R3 E10		0.0	34	0.125			ang sang sang sang sang sang sang sang s	
20°F @	50K	COLD	CO E10 RE	EGULAR GI	ASOLINE	(TIER3)				1.	0	10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			511	PEXHAL	JSIEM	12210N	ISTANDA	ARDS AN	D CI	ERTIFIC	ATION LE	VELS	4			
$\frac{1}{\sqrt{2}} \frac{2}{\sqrt{2}} \frac{1}{\sqrt{2}} \frac{1}{\sqrt{2}$					US06					SC03		COMPOSITE				
	FUEL TYP			NMOG+NOx (g/mi)		CO PN (g/mi) (mg/i			NMOG+NOx (g/mi)		CO (g/mi)	NMOG+NC (g/mi)	X CC (g/n		PM g/mi)	
@ 4K	*	CERT		*		*			*		*		and a second sec			
•			STD	*		*				*	*		and and			
			CERT		*		* 2		*		*	0.056	0.	6	*	
@ UL	GASOLIN TIER3 E	ISIDI		*		* 6			*		*	0.083	4.	2	*	
				e antre 1876 Des Germanyseurs		lan fina Geographia	$(x_{ij})_{ij} = (x_{ij} + \alpha_i^T)^{(ij)}_{ij} + (x_{ij})^{(ij)}_{ij}$	in the second second	na n			0.120	$\frac{2}{2\pi} \frac{1}{2\pi} \frac$	in 1948 Fridden an Sa	a and a second second	
		WHC	DLE VEH	ICLE EV	APORA	TIVE E	MISSION	STANDA	ARD	S AND C	ERTIFICA	TION LEVE	LS			
					WHOLE VEHICLE EVAPORATIVE TESTING											
	EVAPORATIVE FAMILY		FUEL TYPE		DHS (g	g/test) @ UL		2DHS (g/test)		6 (g/test)	@ UL	F	RL (g/mi)		@ UL	
				CEF	CERT		FEL	CERT		STD	FEL	CE	CERT		STD	
LBMXI	LBMXR0130N54		ASOLINE- IER3 E10	103	0.30 0.		*	*		0.65	*	0.	01	0.05	5	
(ORVR / FU	EL O	NLY / CA	NISTER	BLEED	EVAP	ORATIVE	EMISSI	ON S	STANDA	RDS AND	CERTIFICA	TION L	VELS		
								FUEL		ILY EVAI	P & CANIS	TER BLEE	D			
	ORATIVE	ORVR (g/gallon) @ UL					DHS RIG TEST (g/test) @ UL			RIG TEST t) @ UL						
		FUE	EL TYPE	CERT	STD			CERT		STD	CERT	STD	CERT	S	TD	
LBMXI	R0130N54		OLINE- R3 E10	0.03	0.20		*	*		*	*	*	*	,	*	

CALI AIR RESO	FORNIA URCES BOARD		BAYERISCHE OREN WERKE AG	New Pa	Executive Order: A-008-0493-1 ssenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4
EFFECTIV	E LEAK DIAMETER	R STA	NDARD AND CER	TIFICATION L	EVEL (INCHES)
EVAPORATIVE FAMILY	LEAK FAMILY		CERT	Г	STD
*	*		*		*
LDT<6000#GVWR,3751-5750 8500#ALVW; MDV: medium-o duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxidi heated/oxygen sensor; WR-H RDQS: reductant quality sens EGRC: EGR cooler; AIR/AIRI fuel injection; DFI/IFI: direct/ir full/partial/partial with fines or prefix 2: parallel; (2) suffix: set device (ex. DPF-SCRC: SCR ethanol ("15%"gasoline) fuel; -automatic transmission; CV: automated manual transmission; CV:	0#LVW; LDT3: LDT 600 duty vehicle; MDV4: ME : heavy-duty vehicle; E0 vehicle weight rating; L per ULEV; ZEV: zero-er IAC: HC adsorbing cata : selective catalytic redu zer; DPF: diesel particu IO2S or AFS: wide rang sor; NH3S: ammonia se E: secondary air injection direct fuel injection; TO h-board diagnostic; DOF eries; a hyphen (-) betwo coated DPF); CNG/LN E10: "10%" ethanol ("9 continuously variable to ion; AMS: automated m V: plug-in hybrid electric	01-850(DV 850 CS: em VW: loa nission alyst; W uction-t ulate filt ge/linea ensor; E on (belt C/SC: tu R: direct een after 100 "gas ransmis nanual-	D#GVWR,3751-5750 1-10000#GVWR; ME ission control system aded vehicle weight; vehicle; TZEV: trans /U: warm-up catalyst urea/ammonia; NH30 ter (active); GPF: PM dr/heated air-fuel ratio EGR: exhaust gas re driven)/(electric driv urbo/super charger; (to zone reducing; H0 er treatment ECS inco pressed/liquefied na soline) fuel; A: autom ssion; SCV: selectab selectable transmiss	#ALVW; LDT4: 0V5: MDV 1000 n; CERT: certific: ALVW: adjusted sitional ZEV; TW ; NAC: NOx ads DC: ammonia ox l filter for spark-io o sensor; NOXS circulation; HP/L en); PAIR: pulse CAC: charge air CT: hydrocarbon licates multiple f tatural gas; LPG: hatic (with lockup le continuously ion; OT: other tra	kidation catalyst; CTOX/PTOX: gnited engine; HO2S/O2S: : NOx sensor; PMS: PM sensor; P EGR: High/Low Pressure EGR; d AIR; SFI/MFI: sequential/multiport cooler; FFH: fuel fired heater; F/P/\$: trap; BCAN: bleed carbon canister; functionalities of the after treatment liquefied petroleum gas; E85: "85%" b); M: manual transmission; SA: semi
2020	MODEL YEAR	: VE	HICLE MOD	ELS INFO	RMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OB
BMW	M2 COMPETITION COUPE	PC	3.0	AMS7,M6	LBMXR0130N54	1	P
BMW	M2 CS COUPE	PC	3.0	AMS7,M6	LBMXR0130N54	1	P
BMW	M4 CONVERTIBLE	PC	3.0	AMS7,M6	LBMXR0130N54	1	P
BMW	M4 CONVERTIBLE COMPETITION	PC	3.0	AMS7,M6	LBMXR0130N54	1	P
BMW	M4 COUPE	PC	3.0	AMS7,M6	LBMXR0130N54	1	P
BMW	M4 COUPE COMPETITION	PC	3.0	AMS7,M6	LBMXR0130N54	1	P
BMW	M4 CS	PC	3.0	AMS7	LBMXR0130N54	1	P