

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

		P.			TEST GRO	OUP INFO	RMATI	ON				
MODE YEAR		EST GROUP		VEHIC	LE CLASS(E	S)	F	UEL C	ATEGORY		FUEL TYPE	
2020	LB	MXJ03.0B07		PC			DEDI		SINGLE FUEL HICLE		GASOLINE	
, L	USEFUL	LIFE (miles)		VEH	ICLE EMISS	SION CAT	EGOR	(INTERIM / IN	TER	MEDIATE IN-USE STD	
EXH	/ORVR	EVAP			FTP	S	SFTP		FTP		SFTP	
15	0000	15000	0	LEV3	ULEV125	LEV 3	COMPOS	SITE	*		PM	
SPECIAL FEATURES & EXHAUST EMISSION CONTROL OBD STATUS ENGINE DISPL SYSTEMS (L)						NGINE DISPLACEMENT (L)						
1 TWC, WR-HO2S, HO2S, DFI, TC, CAC							FUL	L	*			
*	* PARTIAL ALL MODELS 3.0						3.0					
*			*			PA	RTIAL FINE		*			
		E	VAPO	RATIVE &	REFUELING	G (EVAP/C	RVR) I	AMIL	INFORMATIO	N		
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY EVAP EMISSION								SPECIAL FEATURES				
LBMXR0130F3X LEV 3 OPTION2 WITH FEL					PC			*				
L	BMXR01	50G30	LEV 3 OPTION2 WITH FEL			FEL	PC				*	
I	BMXR01	70G12	LE	LEV 3 OPTION2 WITH FEL PC *				PC			*	
				I	EMISSION C	REDIT IN	FORMA	TION				
	EDIT FO	X FLEET AVE R EXTENDED RANTY			EDIT FOR N ZERO-EVAP		/ NI	MOGC	REDIT FOR DO	R	OPTIONAL EXH. STD FOR WORK TRUCKS	
		N			N				N		N	
×.2				NMOG	AND FLEE	T AVERA	GE INF	ORMA	TION		· '	
NMOG RAF	CH4 RAF	4 FTP 4 NMOG/NMHC HCHO/NMHC NMOG+NOX FLE				(0-3750 L					D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)	
*	*	1.10		*	C	0.065			0.074		*	
0 +	A	10 101								~	ntrol Systems Bhase	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ 18^{t} day of April 2019.

Allen Lyons, Chief

Emissions Compliance, Automotive Regulations and Science Division



ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon
monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity
adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss;
ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K:
1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				6+NOx mi)	-	O mi)		Ox /mi)		:HO J/mi)		PM /mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K		*	*	*	*	*	*	*	*	*	*	*
FTP@UL		OLINE- R3 E10	0.023	0.125	0.1	2.1	*	*	*	4	0.000	0.003
50°F @4K		OLINE- R3 E10	0.030	0.250	0.1	2.1	*	*	*	16		
					F		N	MOG+N	Ox (g/mi)		CO (g/m	i)
				FUEL TYP	E		CE	RT	STD	CER	CERT * 0.000 CO (g/mi	STD
HWFET @) 50K			*				*	*			
HWFET @	DUL	-	GASO	INE-TIER	R3 E10		0.	013	0.125			
20°F @ 5	50K	COLD (CO E10 RE	GULAR GA	ASOLINE	(TIER3)				0.1	5	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC03	}	COM	POSITE	
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*			
		CERT	*	*	2	*	*	0.027	0.4	*
@ UL	GASOLINE- TIER3 E10	STD	*	*	6	*	*	0.083	4.2	*
	2	BIN						0.120		a de carela
	WH	OLE VE	HICLE EVAPO	RATIVE EM	ISSION STAI	NDARDS AND	CERTIFIC	ATION LEVELS	;	-
				WHOLE VE	HICLE EVAP	ORATIVE TES	TING			

			VIIIOLL	LUICLE	LVAFORA	IIVE IESTI	10		8
EVAPORATIVE FAMILY	FUEL TYPE	3DH	S (g/test) (@ UL	2DI	HS (g/test) (@ UL	RL (g/n	ni) @ UL
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
LBMXR0130F3X	GASOLINE- TIER3 E10	0.252	0.300	0.300	0.165	0.300	0.300	0.01	0.05
LBMXR0150G30	GASOLINE- TIER3 E10	0.195	0.300	0.300	0.226	0.300	0.300	0.01	0.05
LBMXR0170G12	GASOLINE- TIER3 E10	0.145	0.300	0.400	0.115	0.300	0.400	0.01	0.05



BAYERISCHE MOTOREN WERKE AG

ORVR / FUI	EL ONLY / CA	NISTER	BLEED	EVAPOR	ATIVE	EMISSION	STANDA	RDS AND	CERTIFICA	TION LEV	ELS	
				FUEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY	ORVR (g/	gallon) @	DUL	FUEL 7	TYPE	3DHS RI (g/test)			IG TEST) @ UL	BLEED C TEST (g/t	ANISTER est) @ 4K	
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD	
LBMXR0130F3X	GASOLINE- TIER3 E10	0.13	0.20	GASOL TIER3	2 (**	*	*	*	*	0.003	0.020	
LBMXR0150G30	GASOLINE- TIER3 E10	0.04	0.20	GASOLIN TIER3 E		*	*	*	*	0.004	0.020	
LBMXR0170G12	GASOLINE- TIER3 E10	0.04	0.20	GASOL TIER3	E10	*	*	*	*	0.010	0.020	
	EFFECTIVE	LEAK D	IAMET	ER STA	NDARI	O AND CE	RTIFICA	TION LEV	EL (INCH	IES)		
EVAPORATIVE	FAMILY	LEA	K FAMIL	_Y		CERT				STD		
LBMXR0170	G12	LBMXR0	170G12	-001 0.01				0.02				
LBMXR0150	G30	LBMXR0	150G30	-001		0.	01			0.02		
LBMXR0130	F3X	LBMXR0	130F3X	-001	0.01 0.02							
						the second s					ANT I DTO	

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

		with the second			EVAPORATIVE	EXH	
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	FAMILY	ECS	OBD
BMW	7401	PC	3.0	SA8	LBMXR0170G12	11	P
BMW	7401 XDRIVE	PC	3.0	SA8	LBMXR0170G12	1	P
BMW	M2401 CONVERTIBLE	PC	3.0	M6,SA8	LBMXR0130F3X	1	P
BMW	M240I COUPE	PC	3.0	M6, SA8	LBMXR0130F3X	1	P
BMW	M240I COUPE M PERFORMANCE	PC	3.0	M6, SA8	LBMXR0130F3X	1	P
BMW	M2401 XDRIVE CONVERTIBLE	PC	3.0	SA8	LBMXR0130F3X	1	P
BMW	M2401 XDRIVE COUPE	PC	3.0	SA8	LBMXR0130F3X	1	P
BMW	M240I XDRIVE COUPE M PERFORMANCE	PC	3.0	SA8	LBMXR0130F3X	1	P
TOYOTA	SUPRA 3.0	PC	3.0	SA8	LBMXR0150G30	1	P