

Executive Order: A-008-0498

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 5

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

		-			TEST GRO	UP INF	ORM	ATION					
MODE YEAR		ST GROUP		VEHICI	LE CLASS(E	S)		FUEL CATEGORY			FUEL TYPE		
2020	LBI	MXJ02.0B4X			PC		DE		SINGLE FUEL		GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION					ION CA	TEGO	ORY	INTERIM / IN	TEF	RMEDIATE IN-USE STD			
EXH	/ORVR	EVAP		1	FTP		SFT	,	FTP		SFTP		
15	0000	150000		LEV3	SULEV30	LEV 3	COM	POSITE	* * ,		PM		
SPE	SPECIAL FEATURES & EXHAUST EMISSION CONTROL OBD STATUS						E	ENGINE DISPLACEMENT (L)					
1	WU-TWO	, TWC, WR-H	02S,	HO2S, D	FI, TC, CA	c	F	ULL	*	7			
*	*						PA	RTIAL	*	7	2.0		
*		,	*			V		IAL WITH	ALL MODELS				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	P / ORV	R FAMILY	EVAF	ORATIVE	STD CATE	GORY	i		SSION STD E CLASS		SPECIAL FEATURES		
I	BMXR01	50G30	LE	V 3 OPTI	ON2 WITH	FEL		PC			*		
I	BMXR01	30F3X	LE	LEV 3 OPTION2 WITH FEL PC *			PC			*			
				E	EMISSION C	REDIT I	NFOF	RMATION					
	EDIT FO	X FLEET AVE. R EXTENDED RANTY	1		EDIT FOR N ZERO-EVAP		EV	NMOG C	REDIT FOR DO	R	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEE	T AVER	AGE	INFORMA	TION				
NMOG RAF	NMOG/NMHC PC+11)1 (0-3/				0-3750		the state of the s		0				
*	*	1.10		*	C	.065			0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-008-0498

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 5

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to California Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

day of April 2019.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Allen Lyons, Chief

Emissions Compliance, Automotive Regulations and Science Division



Executive Order: A-008-0498 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 5

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS	AND CERTIFICATION LEVELS	(FTP, HWFET, 50°F, 2	0°F)
----------------------------	--------------------------	----------------------	------

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	* .	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10	0.013	0.030	0.3	1.0	*	*	*	4	0.001	0.003
50°F @4K	GASOLINE- TIER3 E10	0.020	0.060	0.2	1.0	*	*	*	8		

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)		
	FUELTIFE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	*			
HWFET @ UL	GASOLINE-TIER3 E10	0.006	0.030			
20°F @ 50K	COLD CO E10 REGULAR GASOLINE (TIER3)			0.7	10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			US06			SC03	3	COMPOSITE		
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*	March Committee	*	*		0.3	Charles Street
		CERT	*	*	4	*	* .	0.024	0.3	*
@ UL	GASOLINE- TIER3 E10	STD	*	*	6	*	*	0.083	4.2	*
		BIN			The second second second	Aprile Service Control		0.050		27200

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WHOLE \						
EVAPORATIVE FAMILY	FUEL TYPE	3DHS (g/test) @ UL			2DI	HS (g/test) (RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
LBMXR0130F3X	GASOLINE- TIER3 E10	0.252	0.300	0.300	0165	0.300	0.300	0.01	0.05
LBMXR0150G30	GASOLINE- TIER3 E10	0.195	0.300	0.300	0.226	0.300	0.300	0.01	0.05



Executive Order: A-008-0498

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 5

										TIONI EN	EL 0		
ORVR / FUI	ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS												
				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYP	FUEL TYPE		3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		ANISTER est) @ 4K		
	FUEL TYP	CERT	STD			CERT	STD	CERT	STD	CERT	STD		
LBMXR0130F3X	GASOLINE TIER3 E1	1013	0.20	GASOLINE- TIER3 E10		*	*	*	*	0.003	0.020		
LBMXR0150G30	GASOLINE TIER3 E1	0.04	0.20	GASOLINE- TIER3 E10		*	*	*	*	0.004	0.020		
	EFFECTIVI	LEAK D	IAMET	ER STAI	NDAR	D AND CE	RTIFICA	TION LEV	EL (INCH	IES)			
EVAPORATIVE FAMILY LEAK FAMIL							, i	STD					
LBMXR0150G30 LBMXR0150G30		-001	-001 0.00					0.02					
LBMXR0130F3X LBMXR0130F			130F3X	-001		0.	01	0.02					

t: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
BMW	2301 CONVERTIBLE	PC	2.0	SA8	LBMXR0130F3X	1	\$
BMW	230I COUPE	PC	2.0	M6,SA8	LBMXR0130F3X	1	\$
BMW	2301 XDRIVE CONVERTIBLE	PC	2.0	SA8	LBMXR0130F3X	1	\$
BMW	2301 XDRIVE COUPE	PC	2.0	SA8	LBMXR0130F3X	1	\$
BMW	3301	PC	2.0	SA8	LBMXR0150G30	1	\$
BMW	3301 XDRIVE	PC	2.0	SA8	LBMXR0150G30	1	\$
BMW	3301 XDRIVE GRAN TURISMO	PC	2.0	SA8	LBMXR0130F3X	1	\$
BMW	430I CONVERTIBLE	PC	2.0	SA8	LBMXR0130F3X	1	\$
BMW	430I COUPE	PC	2.0	M6,SA8	LBMXR0130F3X	1	\$
BMW	4301 GRAN COUPE	PC	2.0	M6,SA8	LBMXR0130F3X	1	\$
BMW	4301 XDRIVE CONVERTIBLE	PC	2.0	SA8	LBMXR0130F3X	1	\$
BMW	4301 XDRIVE COUPE	PC	2.0	SA8	LBMXR0130F3X	1	\$
BMW	4301 XDRIVE GRAN COUPE	PC	2.0	SA8	LBMXR0130F3X	1	\$
BMW	Z4 SDRIVE30I	PC	2.0	SA8	LBMXR0150G30	1	\$



Executive Order: A-008-0498

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 5 of 5

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
TOYOTA	SUPRA 2.0	PC	2.0	SA8	LBMXR0150G30	1	\$

