

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP IN	IFOR	MATION					
MODE YEAF	- 1 1	EST GROUP		VEHIC	LE CLASS(E	S)	·	FUEL C	ATEGORY		FUEL TYPE		
2020	LB	MXV02.0M48	4) 		PC				SINGLE FUEL HICLE		GASOLINE		
	USEFUL	LIFE (miles)		VEH	ICLE EMISS	ION C	ATE	GORY	INTERIM / IN	TE	RMEDIATE IN-USE STD		
EXH	/ORVR	EVAP		and the second se	FTP		SF	TP	FTP		SFTP		
. 15	0000	150000)	LEV3	ULEV125	LEV	3 CC	MPOSITE	*	1	PM		
SPE	CIAL FE		HAUS		ISSION CONTROL			OBD S	TATUS	family confident	ENGINE DISPLACEMENT (L)		
1	1 WU-TWC, TWC, WR-HO2S, HO2S, DFI, TC, CAC						-	FULL	*	Martin S.			
*	* *						Р	ARTIAL	ALL MODELS	and the second	2.0		
*		*						TIAL WITH FINES	*	the fighting a			
		E	VAPO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	(INFORMATIO	N			
EVA	P / ORV	R FAMILY	EVA	PORATIVE	E STD CATE	GORY			SSION STD E CLASS	SPECIAL FEATURES			
I	BMXR01	30F3X	L	EV 3 OPTI	3 OPTION2 WITH FEL			PC			*		
I	BMXR01	30F45	LI	EV 3 OPTI	ON2 WITH FEL			I	2C	*			
				1	EMISSION CI	REDIT	INFO	RMATION					
						REDIT FOR NON-PZEV ZERO-EVAP			REDIT FOR DO	R	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N	N			
				NMOG	AND FLEET	T AVE	RAGE	E INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO		HO/NMHC RATIO	NMOG+NO PC+LDT ((g								
*	* ·	1.10		*	0	.065			0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-008-0502 dated July 12, 2019.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of September 2019.

4711

Allen Lyons, Chief

Emissions Certification and Compliance Division



FUEL TYPE

BAYERISCHE MOTOREN WERKE AG Executive Order: A-008-0502-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

							2 - L					
				S+NOx mi)		O mi)		Ox mi)	HC (mg		PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*		*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10		0.065	0.125	0.5	2.1	*	*	*	4	0.000	0.003
50°F @4K		OLINE- R3 E10	0.043	0.250	0.4	2.1	*	*	*	16		
							NN	IOG+NC	x (g/mi)	CO (g/mi)		
	FUEL TYP				Ε		CE	RT	STD	CEF	RT	STD
HWFET @ 50K				*				1.1	*		ingen (M. Stark An official and A	
HWFET @	DL		GASO	LINE-TIE	R3 E10		0.0	34	0.125	-Califier		
20°F @ 50K		COLD (CO E10 RE	EGULAR G	ASOLINE	(TIER3)	the sec	a de la composición d		0.	7	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			51	IF LA	IAUSI	LIMISSIO	1 STAND	ANDOR	AND CERTIF	ICAT			3		
			A SUMP	22	NEC.	US06	in the second	1. J.	SC	03	3	81	COM	POSITE	
	FUEL TYI	PE	地理に		G+NOx /mi)	c CO (g/mi)		PM g/mi)	NMOG+NO> (g/mi)		CO g/mi)		OG+NOx g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	4	CERT		*	*			*		*				
6			STD	*		*		1.9130	*		*	11,256,62,3		A starting	
					*	*		2	*		*	0.075		0.6	*
@ UL	DUL GASOLINI				*	*		6	*		*	0.083		4.2	*
			BIN				国 山市	(all the second	设有规则部分			0.120		- Willia	Applements Applem
		WH	OLE VE	HICLE	EVAP	ORATIVE E	EMISSION	N STAN	DARDS AND	CER	RTIFIC	ATIO	N LEVELS		
						WHOLE	VEHICLE	EVAPO	ORATIVE TE	STIN	G	1		÷.,	
	ORATIVE	F	UEL TY	PE	3DH	IS (g/test) (@ UL		2DHS (g/te	st) @	UL	1	RL	(g/mi) @	UL
					CERT	STD	FEL	CER	RT STD		FEL	<u> </u>	CERT		STD
LBMXF	R0130F3X		ASOLIN IER3 E		0.252	0.300	0.300	0.10	65 0.30	0	0.30	00	0.01		0.05
LBMX	R0130F45		ASOLIN IER3 E		0.198	0.300	0.275	0.20	04 0.30	0	0.27	75	0.01	1	0.05

ORVR / FU	EL ONLY / CA	NISTER	BLEED	EVAPORATIVE						ELS		
EVAPORATIVE FAMILY	ORVR (g/	gallon) @	DUL	FUEL TYPE	FUEL O 3DHS RI (g/test)	G TEST		IG TEST () @ UL	ED BLEED C TEST (g/t			
	FUEL TYPE	CERT	STD	and an ender	CERT	STD * *	CERT	\$TD * *	CERT	STD		
LBMXR0130F45	GASOLINE- TIER3 E10	0.04	0.20	GASOLINE- TIER3 E10	*		*		0.020	0.020		
LBMXR0130F3X	GASOLINE- TIER3 E10	0.13	0.20	GASOLINE- TIER3 E10	×α		*		0.003	0.020		
	EFFECTIVE	LEAK D	IAMET	ER STANDAR	D AND CE	RTIFICA	TION LEV	EL (INCH	HES)			
EVAPORATIVE	FAMILY	LEA	K FAMIL	Y	CERT STD				STD	D		
LBMXR0130)F45	LBMXR0	130F45	-001	0.01			0.02				
LBMXR0130	F3X	LBMXRO	130F3X	-001	0.01				0.02			
8500#ALVW; MD	/· modium_dut		vehicle;							neulum-		

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
BMW	M235I XDRIVE	(1) PC 5 . ++	2.0	SA8	LBMXR0130F3X	1	P
BMW	X2 M35I	PC	2.0	SA8	LBMXR0130F45	1	P
MINI	JCW COUNTRYMAN ALL4	PC	2.0	1 SA8	LBMXR0130F45	1	P
MINI	MINI JOHN COOPER WORKS CLUBMAN ALL4	PC	2.0	SA8	LBMXR0130F45	1	та пр 111,172 г.,