

BAYERISCHE MOTOREN WERKE AG

Executive Order: A-008-0506 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION															
MODE		EST GROUP		VEHIC	LE CLASS(E	ES)		FUEL CATEGORY			TEGORY	FUEL TYPE			
2020	LB	MXV01.5H60	5H60 PC					PLUG-IN HYBRID ELECTRIC VEHICLE				GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION							CAT	ATEGORY INTERIM / INTERMEDIATE IN-L					MEDIATE IN-USE STD		
EXH	/ORVR	EVAP		FTP			SFTP F			FTP		SFTP			
15	0000	150000		LEV3	ULEV125	LEV	3	COMPOS	SITE	1000	PM		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD STATUS			ATUS	E	NGINE DISPLACEMENT (L)		
1	WU-TW	C, TWC, WR-HC)2S,	HO2S, D	FI, TC, C	AC		FULL	L	Γ	*	SAD-CHAR			
*	*							PARTI	IAL *			1.5			
*			* PARTIAL WITH FINES ALL MOI						ALL MODELS						
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION															
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS				SPECIAL FEATURES			
L	BMXR01	40G3H	LEV	V 3 OPTI	ON2 WITH	ON2 WITH FEL PC				*					
					EMISSION C	REDI	ΓIN	NFORMA	TION						
CDOUD							NMOG CREDIT FOR NON-PZEV ZERO- EVAP			N	NMOG CREDIT FOR DOR		OPTIONAL EXH. STD FOR WORK TRUCKS		
	* И						и и			N	N				
NMOG AND FLEET AVERAGE INFORMATION															
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	0.00	O/NMHC ATIO	NMOG+NOX FLI PC+LDT (0-375 (g/mi)			50 LVW) LI		NMOG+NOX FLEET ST LDT (3751 LVW-8500 GVWR) + MDPV (g/mi					
*	*	1.10		*		0.065					0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BAYERISCHE MOTOREN WERKE AG

Executive Order: A-008-0506

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have five (5) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of one hundred and twenty-five dollars (\$125) per vehicle for the third through fifth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to California Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 674

Allen Lyons, Chief

Emissions Certification and Compliance Division

day of September 2019.



BAYERISCHE MOTOREN WERKE AG

Executive Order: A-008-0506 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS.

	_				_						DS AND					ELS	
- Chicago da de	538	EXH									LEVELS (
	FUE	L TY	m ac O 10	onoxi djustm RVR [de; No ent fa [g HC/	Ox: oxid ctor; 20 gallon o	es of nit HS/3DI dispense	trogen; H HS [g HC ed]: on-bo	CHO: /test]: oard re	formalo 2/3 day fueling	hydrocark dehyde; Pl vs diurnal- vapor rec st procedu	M: particu -hot-soak; overy; g:	late r RL [gram	natter; F g HC/mi ; mg: mi	RAF: re i]: runr illigran	eactivi ning lo n; mi:	ty ss;
	Ž.			NMOG+NOx (g/mi)			CO (g/mi)		NOx (g/mi)		HCH (mg/r				PM (g/mi)		
				CERT STD		STD	CERT STD)	CERT STD		CERT		STD	CERT		STD
FTP@5	ЭK	*		*		*	*	*		*	*	*		*	,	* /	
FTP@L	11	OLIN R3 E	1	0.02	6 0	.125	0.8	2.3	1	*	*	*		4	0.002 0.		0.003
50°F @4	1161	OLIN R3 E		0.043	3 0	.250	0.9	2.:	1	*	*	*		16			
19 25 74					EII	EL TYP	_			N	MOG+NC	x (g/mi)			co (g/mi)	
										CI	CERT STD			CERT			STD
HWFE	@ 50K					*					* *						
HWFET @ UL GAS				SOLIN	E-TIE	R3 E10	3 E10 0.018			0.125							
20°F @ 50K COLD CO E10 REGULAR GA						ASOLIN	E (TIER	(3)					1.4		1	LO.0	
Т			SI	FTP E	XHAL			STANDA	ARDS	AND C	ERTIFIC	ATION LE	VEL				
16.5				US06						SC03				COMPOSITE			
	FUEL T	/PE	esperature and		OG+N (g/mi)		CO (g/mi)	P (mg			G+NOx /mi)	CO (g/mi)	NMOG+NOx (g/mi)			CO g/mi)	PM (mg/mi)
@ 4K	*		CERT	CERT		*		*		*		*					
			STD		*		*				*	*		A STATE OF			STO Live
			CERT		*	*		*		*		*	0.027		:	1.4	*
@ UL	GASOLINE TIER3 E1		STD		*		*		5		*	*	C	0.083		4.2	*
			BIN	Y									_	.120	4.7		
		WH	OLE VI	EHICL	E EV						OS AND C		OITA	N LEVE	LS		
	ORATIVE		UEL TY					HOLE VEHICLE EVAF /test) @ UL			2DHS (g/test) @ UL			RL (g/mi) @		ni) @	UL
FA	MILY	I SEL IMPE		-			STD			RT STD				CEI	EDT		STD
LBMXR	.0140G3H		ASOLII		0.2	_	. 300	0.300	0.2		0.300	0.30		0.01 0.05			
	RVR / FU				STER	BLEE	EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CEF	RTIFICA	TION	LEVE	LS
		T					T				NLY EVA						
	ORATIVE		ORVR	(g/gal	lon) @	on) @ UL FUEL TYPE				BDHS RIG TEST (g/test) @ UL		2DHS RIG (g/test) @		TEST BLE		EED CANISTER ST (g/test) @ 4K	
		FU	EL TYP	EC	ERT	STD	1		_	RT	STD	CERT		STD	CEI		STD
LBMXR	.0140G3H		SOLINE ER3 E		0.02	0.20		*		*	*	*		*	*		*



BAYERISCHE MOTOREN WERKE AG

Executive Order: A-008-0506

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
LBMXR0140G3H	LBMXR0140G3H-001	0.01	0.02						

not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	MINI	COOPER SE COUNTRYMAN ALL4	PC	1.5	SA6	LBMXR0140G3H	1	\$

ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION

MODEL		UDDS AER	UDDS EAER	US06 AER	HIGHW	ZEV		
NUMBER	PHEV TYPE	(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE	
1	*	23.80	26.07	*	23.12	23.43	0.00	