

Executive Order: A-009-1478-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP II	VFOR	MATION					
MODE	TEST COOLID VEUICI				LE CLASS(ES)			FUEL CATEGORY			FUEL TYPE		
2020	LC	RXV01.85P0		Sala Sala	PC DE				SINGLE FUEL HICLE	-	GASOLINE		
	USEFUL	LIFE (miles)		VEH	IICLE EMISS	ION C	ATE	GORY	INTERIM / IN	ITE	RMEDIATE IN-USE S	TD	
EXH	/ORVR	EVAF			FTP S			FTP FTP			SFTP		
150000 150000			0	LEV3	3 LEV160 LEV 3 COM			MPOSITE	POSITE *		*		
SPE	CIAL FE	ATURES & EX	CHAU		ON CONTRO	L		OBD S	TATUS		ENGINE DISPLACEMENT		
1	D	FI, TC, CAC	, TW	C, HO2S,	WR-HO2S			FULL	SOME MODELS				
* *							P	ARTIAL	* 1.8				
*			4	*				TIAL WITH	SOME MODELS	LS			
		Е	VAP	ORATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	INFORMATIO	N			
EVA	P / ORV	R FAMILY	EV	APORATIVE	STD CATE	GORY			SSION STD E CLASS		SPECIAL FEATURE	s	
I	LCRXR0100PK0 LEV					2			PC		*		
				-	EMISSION C	REDIT	INFO	RMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON- ZERO-EVAP						ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
	N N							N					
				NMOG	AND FLEET	AVE	RAGE	INFORMA	TION				
				NMOG+NO PC+LDT ('50 LVW) LDT		OG+NOX FLEET STD DT (3751 LVW-8500 /WR) + MDPV (g/mi)		NMOG+NOX FLEET ST MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		* 0.065				0.074			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-009-1478-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the listed vehicles that are equipped with optional Akrapovic exhaust system has been determined to have one deficiency. The aforementioned vehicles are approved subject to the manufacturer paying a fine of twenty five dollars (\$25) per vehicle for the Akrapovic exhaust monitor deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-009-1478 dated July 25, 2019.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 1214 day of June 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division



Executive Order: A-009-1478-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

= 77		EVU	LICTE	MICCI	ONE	CANDA	DDS AL	ID CEPT	CIEICA	TION	EVELS	(FTP, HW	FET	50°F 20°	F)		
		EARP	CI me ac	14: me onoxic justm	ethane le; NO ent fac a HC/c	x: oxide otor; 2D	G: non-(es of nite HS/3DH	CH4 orga rogen; Ho IS [g HC/ d]: on-bo	nic ga CHO: t (test]: i	s; HC: formald 2/3 day fueling	hydrocar lehyde; P 's diurnal- vapor red	bon; NMH M: particu +hot-soak covery; g:	C: no late n ; RL [on-CH4 H0 natter; RA g HC/mi]: ; mg: millig	C; CO: ca F: reactiv running lo gram; mi:	ity oss;	
	FUEL T		FUEL TYPE		000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: suppl												
					g/mi)		(g/mi)			/mi)		mg/m	The I	(g/r	ni)	
				CERT		STD	CERT	STE)	CERT	STD	CER	Т	STD	CERT	STD	
FTP@50	ok .	*		*		*	*	*		*	*	*		*	*	*	
FTP@U	L LEV	OLIN 73 E1 PREM	CC - 11 - 22	.077	6 0	.160	0.99	4.2	2	*	*	*		4 *		0.01	
50°F @4	ıĸ	*		*		*	*	*		*	*	* *		*			
				FUEL TYPE						NMOG+NOx		Ox (g/mi)	c (g/mi)		CO (g/mi)		
					FUE	LIYP	=			CI	ERT	STD		CERT		STD	
HWFE1	@ 50K					*					*	*					
HWFE	T@UL		(ASOI	INE-	LEV3 E	10 PR	EM		0.0	0093	0.160					
20°F @ 50K		GAS	ASOLINE-COLD CO H				IIGH OCTANE						1.75		10.0		
201	<u>@ 3011</u>								ARDS	AND C	ERTIFIC	ATION L	VEL	S			
	170		3,	., _	AIIAO		JS06	01711127			SC03				POSITE		
	FUEL T			MOG+NOx (g/mi)				M /mi)	NMOG+NOx (g/mi)		CO NA (g/mi)		OG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)		
		* CER			*		*				*	*					
@ 4K	*				*	-	*	-		-	*	*				+	
			CERT		*	_	*	+ ,	Ar .	<u> </u>	*	*	0	.0688	1.11	*	
@ UL	GASOLINE- STO		STD		*		* *		*	*		*	* 0		4.2	*	
@ OL	TIER3	IER3 E10				-		+						0.100		1	
14110		BIN	HICI	F EV	APORA	TIVE E	MISSION	STA	NDARE	S AND	CERTIFIC	ATIO	N LEVEL	S			
		1	IOLL VI	2,1101							IVE TES						
	PORATIVE FUEL TYPE								2DHS (g/test) @ UL				RL (g/mi) @ UL				
FAMILY					CER	T S	STD	FEL	CE	RT	STD	FE	L	CER	Г	STD	
LCRXR0100PK0		0	EASOLI LEV3 E	10			.50	100,000		175	0.65		*		0.001		
(ORVR / F	UEL	ONLY /	CANI	STER	BLEED	EVAP	ORATIV	EEMI	SSION	STANDA	ARDS ANI	CE	RTIFICAT	ION LEV	ELS	
										FUEL ONLY EVAP & CANISTE							
and the second second	ORATIV	E	ORVR	(g/gal	g/gallon) @ UL			FUEL TYPE		OHS RIG TEST (g/test) @ UL		(g/te	2DHS RIG (g/test) @		UL TEST (g/t		
		FI	JEL TY	PEC	ERT	STD			CI	ERT	STD	CERT	-	STD	CERT	STD	
LCRX	R0100PK		ASOLIN EV3 E1		0.025 0.20			*		*	*	*		*	*	*	



Executive Order: A-009-1478-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

III/ II/ AIR RESOU	RCES BOARD		Page 4 of 4	
EFFECTIVE	LEAK DIAMETER STAN	DARD AND CERTIFICATION L	EVEL (INCHES)	
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD	

to not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT; certification; STD: standard; FEL: family emission limit; GVWR; gross vehicle weight rating; LVW; loaded vehicle weight; ALVW; adjusted LVW; LEV; low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer: DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine: HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
ALFA ROMEO	4C	PC	1.8	AM6	LCRXR0100PK0	1	F
ALFA ROMEO	4C (AKRAPOVIC EXHAUST)	PC	1.8	AM6	LCRXR0100PK0	1	\$