

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MOD YEA		EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE		
202	0 L	FMXT02.02JU			LDT2		DEDICATED SINGLE FUEL VEHICLE				GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION								ATEGORY INTERIM / INTERMEDIATE IN-USE					
EXH/ORVR EVAP FTP							SF	TP	FTP		SFTP		
1	150000 150000 LEV3 ULEV70 LE						3 C	3 COMPOSITE PM			PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							,	OBD S	BD STATUS		ENGINE DISPLACEMENT (L)		
1	TWC, H	02S, WR-HO2S	, CAC	, TC, DE	I, EGR, E	GRC		FULL	ALL MODELS				
*	*							ARTIAL	*		2.0		
*					ann 1975 - 108 Ianns	PAF	RTIAL WITH * FINES *						
		E	APO	RATIVE &	REFUELING	(EVA	AP/OR	VR) FAMIL	INFORMATION	1			
EV	AP / OR	VR FAMILY	EVA	PORATIVE	E STD CATE	GOR	(	, EVAP EMISSION STD SPECIAL FE			SPECIAL FEATURES		
	LFMXR0	135NDF	LE	V 3 OPTI	ION2 WITH	FEL		LD	*				
				E	EMISSION CI	REDI	T INFO	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON- ZERO-EVAP										OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N N					
				NMOG	AND FLEET	AVE	RAG	E INFORMA	ΓΙΟΝ				
NMOG RAF	G CH4 RAF	FTP NMOG/NMHO RATIO		HO/NMHC RATIO NMOG+NOX FL PC+LDT (0-375 (g/mi)				V) LDT	+NOX FLEET S (3751 LVW-8500 R) + MDPV (g/m		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.065	1		*				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this  $\underline{\mathcal{SRS}}$  day of September 2019.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

FORD MOTOR COMPANY Executive Order: A-010-2202 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/i		CO (g/mi)			NOx (g/mi)		HO 'mi)			
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K	к *		*	*	*	*	*	*	*	*	*	*	
FTP@UL	P@UL GASOLINE- TIER3 E10		0.0264	0.070	1.15	1.7	*	*	*	4	0.0009	0.003	
50°F @4K	K GASOLINE- TIER3 E10		0.0482	0.140	0.17	2.1	*	*	0.8	16			
	er v						N	NMOG+NOx (g/mi)			CO (g/mi)		
		FUEL TYPE						RT	STD	CER	RT	STD	
HWFET @ 50K		ок *						* *					
HWFET @ UL		UL GASOLINE-TIER3 E10						125	0.070	0.070			
20°F @ 50K		COLD (	CO E10 RE	GULAR G	ASOLINE	(TIER3)	- Anna anna anna anna anna anna anna ann	e here i s		0.7	1	12.5	

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			5.56 5.3		US06					SC03		COMPOSITE			
	FUEL TYPE		Reference N	NMOG+NOx (g/mi)		CO Pr (g/mi) (mg/				)G+NOx g/mi)	CO (g/mi)	NMOG+N (g/mi)		CO (g/mi)	PM (mg/mi)
@ 4K	*		ERT	*	*					*	*	CENTRAL CONTRACTOR		利息的的 1993年1993年 1993年1993年	
0			STD	*		*		*		*	*				
		CERT		*		* 0.7		7		*	*	0.0292		1.01	*
@ UL	GASOLINI TIER3 E		STD	*		*	6	;		*	*	0.083		4.2	*
			BIN	$\left  \left  \left  \right  + \left  \left  \left  E \right  \right  \right  \right $								0.080			
		WHO	LE VEHI	CLE EV	APORA	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEV	ELS		
					W	HOLE \	/EHICLE	EVAPO	RAT	IVE TEST	ING				
		FUEL TYPE		: 3	3DHS (g/		/test) @ UL		2DHS (g/test) @ UL			RL		. (g/mi) @ UL	
				CEF	RT S	STD	FEL	CERT		STD	FEL	CI	CERT		STD
LFMXR0135NDF			SOLINE- ER3 E10	10 15	68 0	400	0.400	0.148	0.1481 0.400		0.400	0.	000	0.05	
(	ORVR / FU	EL ON	NLY / CA	NISTER	BLEED	EVAP	ORATIVE	EMISS	SION	STANDA	RDS AND	CERTIFIC	ATIO	N LEVE	ELS
								FUI	EL O	NLY EVA	& CANIS	TER BLE	ED		
	EVAPORATIVE FAMILY		ORVR (g/gallon) @ UL					OHS RIG TEST g/test) @ UL		27 - 272	t) @ UL	A ANTA ANTA A A A A A A A A A A A A A A		CANISTER /test) @_4K	
		FUE	L TYPE	CERT	STD	1		CER	RT	STD	CERT	STD	CE	ERT	STD
LFMXR0135NDF		535423559352 54	OLINE- R3 E10	0.006	0.20		OLINE- R3 E10	*		*	*	*	0.	014	0.020

CALI AIR RESC	FORNIA DURCES BOARD		FORD MOTOR COMPANY	Executive Order: A-010-2202 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4								
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE FAMILY	LEAK FAMILY		CERT	Г	STD							
LFMXR0135NDF	LFMXR0135NDF-0	01	*		0.02							
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: su ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxid heated/oxygen sensor; WR-H RDQS: reductant quality sen EGRC: EGR cooler; AIR/AIR fuel injection; DFI/IFI: direct/i full/partial/partial with fines or prefix 2: parallel; (2) suffix: se device (ex. DPF-SCRC: SCR ethanol ("15%"gasoline) fuel; -automatic transmission; CV: automated manual transmiss	0#LVW; LDT3: LDT 600 duty vehicle; MDV4: ME ': heavy-duty vehicle; E0 vehicle weight rating; L' per ULEV; ZEV: zero-er AC: HC adsorbing cata : selective catalytic redu zer; DPF: diesel particu 102S or AFS: wide rang sor; NH3S: ammonia se E: secondary air injection direct fuel injection; TC h-board diagnostic; DOF eries; a hyphen (-) betwee coated DPF); CNG/LN E10: "10%" ethanol ("90 continuously variable tr ion; AMS: automated m V: plug-in hybrid electric	01-850 0V 850 CS: en VW: lo nission lyst; V action- late fil e/linea nsor; I n (bel /SC: tr C: direc een aft G: con 0%"ga ansmi anual- vehic	0#GVWR,3751-5750 01-10000#GVWR; MI hission control system aded vehicle weight; n vehicle; TZEV: trans VU: warm-up catalyst urea/ammonia; NH30 ter (active); GPF: PM ar/heated air-fuel ratio EGR: exhaust gas rea t driven)/(electric driv urbo/super charger; O ct ozone reducing; HO ter treatment ECS inco npressed/liquefied na soline) fuel; A: autom ssion; SCV: selectable selectable transmissi	#ALVW; LDT4: DV5: MDV 1000 n; CERT: certific ALVW: adjusted sitional ZEV; TW ; NAC: NOx ads DC: ammonia ox filter for spark-io o sensor; NOXS circulation; HP/L en); PAIR: pulse CAC: charge air CT: hydrocarbon licates multiple f tural gas; LPG: atic (with lockup le continuously on; OT: other tra	cidation catalyst; CTOX/PTOX: gnited engine; HO2S/O2S: : NOx sensor; PMS: PM sensor; P EGR: High/Low Pressure EGR; ed AIR; SFI/MFI: sequential/multiport cooler; FFH: fuel fired heater; F/P/\$: n trap; BCAN: bleed carbon canister; functionalities of the after treatment liquefied petroleum gas; E85: "85%" p); M: manual transmission; SA: semi							

	2020 MODEL YEAR: VEHICLE MODELS INFORMATION												
MAKE MODEL VEH CLASS ENGINE (L) TRANS TYPE EVAPORATIVE EXH FAMILY ECS													
FORD	EDGE AWD	LDT2	2.0	A8	LFMXR0135NDF	1	F						
FORD	EDGE AWD	LDT2	2.0	SA8	LFMXR0135NDF	1	F						
FORD	EDGE FWD	LDT2	2.0	A8	LFMXR0135NDF	1	F						
LINCOLN	NAUTILUS AWD	LDT2	2.0	SA8	LFMXR0135NDF	1	F						
LINCOLN	NAUTILUS FWD	LDT2	2.0	SA8	LFMXR0135NDF	1	F						