

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| | | | | TEST GR | OUP IN | FORMA | TION | | | | |
|--|------------|--|--------------------|------------------------------|---|-------------------------|--------|---|--|--|--|
| MODE | | EST GROUP | VEHIC | LE CLASS(ES) | | | FUEL C | ATEGORY | FUEL TYPE | | |
| 2020 | LI | MXT03.03DZ | LDT3, LDT4 | | | | | SINGLE FUEL HICLE | DIESEL | | |
| - | USEFU | L LIFE (miles) | VEH | VEHICLE EMISSION CATEGOR | | | | INTERIM / INT | RMEDIATE IN-USE STD | | |
| EXH | /ORVR | EVAP | FTP | | | SFTP | | FTP | SFTP | | |
| 15 | 0000 | * | LEV3 | LEV160 LEV 3 COMPOS | | OSITE | * | PM | | | |
| SPE | | EATURES & EXI SYS | AUST EMISSIC | | OL | | OBD ST | TATUS | ENGINE DISPLACEMENT (L) | | |
| 1 | TC,DFI | , CAC, EGR, EGR | -C,OC,DPF,SC | RC, NOXS, F | DQS | FULL | | * | 3.0 | | |
| * | | | * | | 1 | PARTIAL | | * | | | |
| * | | | * | | | PARTIAL WITH ALL MODELS | | | | | |
| | | EV | APORATIVE & | REFUELIN | G (EVA | P/ORVR | FAMILY | INFORMATION | | | |
| EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR | | | | | | | | SSION STD E CLASS | SPECIAL FEATURES | | |
| | * | | | t 🔹 series de la composition | | | 1 | · International States | * | | |
| | | | E | EMISSION | CREDIT | INFORM | ATION | | | | |
| | EDIT FO | OX FLEET AVE. OR EXTENDED RRANTY | | EDIT FOR | | PZEV NMOG CREDIT FOR | | | OPTIONAL EXH. STD FOR WORK TRUCKS | | |
| | | N | | N | | N | | | N | | |
| | | | NMOG | AND FLEE | T AVE | RAGE IN | FORMA | TION | | | |
| NMOG RAF | CH4 RAF | FTP NMOG/NMHC RATIO | HCHO/NMHC RATIO | PC+LDT | NMOG+NOX FLEE PC+LDT (0-3750 L (g/mi) | | LDT | +NOX FLEET ST (3751 LVW-8500 R) + MDPV (g/mi) | D NMOG+NOX FLEET STE MDV (10,001-14,000 GVWR) (g/mi) | | |
| * | * | * | * | | 0.065 | | | 0.074 | * | | |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.) CALIFORNIA AIR RESOURCES BOARD

FORD MOTOR COMPANY

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) . (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II system of the listed vehicle models have been determined to have eleven (11) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of four hundred twenty five dollars (\$425) per vehicle for the third through the eleventh deficiencies for vehicles in the listed test group that are produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the California Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 1914 day of February 2020.

Allen Eyons, Chief Emissions Certification and Compliance Division

(a) Training the result of the Arcourt Eventstative Particle Engine Displacement, Emession Control Britanov, P Sensarity 112:10. If an arrow the U.S. Science of Send Controlation Devide, and Abbravisoung 1AV strateshie masses of the end arrow the U.S. Science in GrWyR later in this Exclusive Original Revolution in regurserveds. The Co. Section 1981; 2 angles the following that to 13 CCP Section 1995; 3(f) (3) in 18 CCP.



FUEL TYPE

FORD MOTOR COMPANY

Executive Order: A-010-2210 New Passenger Cars, Light-Duty Trucks and **Medium-Duty Vehicles**

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

| | | | - | | | | | | | | | | | | | | |
|-----------------------|-----------|-------------|-----------------|---|--------------|--------------|---------------|------------|--------------------|-------------------------------|----------------|------------------------|---------------|---------------|-----------|------------------------------|-------|
| | | | | | C+NC /mi) |)x | | CO /mi) | | | Ox mi) | | HCH (mg/r | | -7-1 | PN (g/n | |
| | | | | CERT | S | TD | CERT | STD |) C | ERT | STD | CER | т | STD | CER | r | STD |
| P@50K | ĸ | * | | * | | * | * | * | | * | * | * | | * | * | | * |
| TP@UL DIESEL-H | | EL-E | PA (| 0.144 | 0. | 160 | 0.2 | 4.2 | | * | * | * * | | 4 | 0.00 | 0 | 0.003 |
| °F @4K | ĸ | * | | * | | * | * | * | | * | * | * | | * | | | |
| | | | | FUEL TYPE | | | | | | NMHC+NOx (g/mi | | |) | | CO (g/mi) | | |
| | | FUELITPE | | | | | | | | CERT ST | | STD | CER | | r std | | STD |
| HWFET @ 50K | | | | * | | | | | | * | | * | | | | | |
| WFET | @ UL | | | DIESEL-EPA | | | | | | 0.044 0.1 | | | 60 | | | | |
| 20°F @ |) 50K | | | * | | | | | | | | | | * | | * | |
| | | | SF | TP EX | HAUS | ST EM | ISSION S | TANDA | RDS A | ND CE | ERTIFIC | ATION L | EVEL | .s | | | - |
| | | | | | | ι | JS06 | | | SC03 | | | (| | OMPOSITE | | |
| F | FUEL TY | EL TYPE | | - Contraction of the second | | CO (g/mi) | PM (mg/mi) | | NMHC+NOx (g/mi) | | CO N (g/mi) | | SACING INC. | |) ni) | PM (mg/mi) | |
| @4K * | | CERT | | | * | | * | | | 4 | | * | Dec antige (| | | | 2 |
| | | | STD | D * | | - | * | | | * | | * | a state | ALCONTRACT OF | | | |
| | | | | | * | | * | 0 | | 1 | | * | 0.127 | | 0.127 0. | | * |
| | IESEL-EPA | | PA STD * BIN | | | * | * 6 | | * | | * | 0.083 | | 4.2 | | * | |
| | | | | | | | | | 1997 22.8985 | | | | 0.180 | | | | |
| | | WH | OLE VE | HICLE | EVA | PORA | TIVE EM | ISSION | STAN | DARD | S AND C | ERTIFIC | ATIO | N LEVEL | .S | | |
| | | | | | | Wł | HOLE VE | HICLE | EVAPC | RATI | /E TEST | ING | | | | | |
| EVAPORATIVE FAMILY | | | | PE 3DHS (g/ | | /test) @ UL | | | 2DHS (g/test) | | @ UL | | RL (g/mi) @ l | | UL | | |
| | | | | | CERT | ERT STD | | FEL | CER | RT STD | | FE | FEL | | CERT | | STD |
| * | | | * | * | | * | * | * | | * | * | | * | | * | | |
| OF | RVR / FU | EL C | DNLY/ | CANIS | TER E | BLEED | EVAPO | RATIVE | EMISS | SION S | TANDA | RDS ANI | D CE | RTIFICAT | ION LI | EVE | LS |
| | | | | | | | | | | | | | | R BLEED | | | |
| EVAPORATIVE FAMILY | | ORVR (g/gal | | g/gallo | | | FUEL | | | DHS RIG TEST (g/test) @ UL | | 2DHS RIG (g/test) @ | | | | ED CANISTER (g/test) @ 4K | |
| | | | | ECE | RT | STD | 1 | | CER | | | CERT | | STD CE | | | |
| * | | | * | * * | | * | * | | | * | * | | * | * | | * | |
| | | EFF | ECTIV | E LEA | KDL | AMET | ER STA | NDAR | D AND |) CER | TIFICA | TION LE | EVEL | . (INCHE | S) | | |
| EVAPORATIVE FAMILY | | | | | LEAK FAMILY | | | | CERT | | | | STD | | | | |
| | * | | | * | | | | | * | | | | | * | | | |
| | | | | | | FAMI | | | DANL | CERT | | | | STD | | | |

CALIFORNIA

FORD MOTOR COMPANY

not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant guality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

| MAKE | MODEL | VEH CLASS | ENGINE (L) | TRANS TYPE | EVAPORATIVE FAMILY | EXH ECS | OBC |
|------|----------------------------------|-----------|------------|------------|--|------------|-----|
| FORD | F150 2WD | LDT3 | 3.0 | SA10 | * | 1 | \$ |
| FORD | F150 2WD | LDT4 | 3.0 | SA10 | * | 1 | \$ |
| FORD | F150 2WD BASE PAYLOAD LT TIRE | LDT3 | 3.0 | SA10 | * | 1 | \$ |
| FORD | F150 2WD BASE PAYLOAD LT TIRE | LDT4 | 3.0 | SA10 | - 161/191 * | 1 | \$ |
| FORD | F150 4WD BASE PAYLOAD LT TIRE | LDT3 | 3.0 | SA10 | + | 1 | \$ |
| FORD | F150 4WD BASE PAYLOAD LT TIRE | LDT4 | 3.0 | SA10 | + forcive | 1 | \$ |
| FORD | F150 PICKUP 4WD | LDT3 | 3.0 | SA10 | 1 1 CE 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | 1 | \$ |
| FORD | F150 PICKUP 4WD | LDT4 | 3.0 | SA10 | * | 1 | \$ |
| FORD | F150 PICKUP 4WD XL/XLT | LDT3 | 3.0 | SA10 | 100 · mo | 1 | \$ |

SWITTET RUITAGER AND STUDIES STREET

| い中国 | finng) JA | 20HS (gAosi) @ UL | | | JUID GROUP SHOL | | | HAAA TURA | F. AMORTONYE |
|----------|--|-------------------|----------------------|-----------|--------------------|--------|----------|--------------|--------------------------|
| \$ID | (358) | PEL | | CER! | 199 | Ura | 1983.) | | |
| | | 4 | | 14 | | × | | - 12 | |
| 6.25% | L. MORACINE | 480 QMA 204 | AC[4]AT3 | HONZBINE | THE F. D. P. C. P. | SAVE O | | MARTIN AND | |
| | (BL/ED) | istemas a - | AND XING | FUEL O | | | | | |
| | 035.13 11831 | | | | | | | | |
| | | | a second a second as | | | | | | 1 JANS/1 |
| The star | 1930 J | CRED 1 | | CERT_ | | - Ant | 2 | States (1997 | |
| | and the second s | and the second of | · _ mail and the | - | 1 | | 1 1 1 | | |
| | (22)(2)(4) | TANAT NOU | PARTICIA | DO AND GE | MACHAT | 123131 | BANC MAL | したが日本の | the second second second |
| | | | | | | | | | |