

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO		FOR	MATION						
MODE		EST GROUP		VEHICLE CLASS(ES) FUEL CATEGORY FUEL TY					FUEL TYPE					
2020) LF	MXD06.761B			MDV4				SINGLE FUEL HICLE		DIESEL			
USEFUL LIFE (miles) VEHICLE E						ION C	ATE	GORY	INTERIM / IN	TERN	ERMEDIATE IN-USE STD			
	I/ORVR	EVAP			FTP		SF	TP	FTP	SFTP				
15	50000	*		LEV3	ULEV200	US0	6, SC	EV (FULL CO3, FTP CYCLE)	*	*				
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS OBD STATUS						IGINE DISPLACEMENT (L)								
1	1 TC, DFI, CAC, EGR, EGRC, OC, DPF, SCRC, NOXS(2), RDQS							FULL	*					
*	* *						P	PARTIAL *			6.7			
*	* *							TIAL WITH	ALL MODELS					
		E	VAPC	RATIVE &	REFUELING	i (EVA	P/OR	VR) FAMIL	INFORMATION	1				
EVA	AP / ORV	R FAMILY	EVA	PORATIVE	E STD CATE	GORY	r		SSION STD E CLASS	SI	SPECIAL FEATURES			
	*				*				*		*			
					EMISSION C	REDI		ORMATION						
					REDIT FOR NON-PZEV ZERO-EVAP			NMOG C	NMOG CREDIT FOR DOR		OPTIONAL EXH. STD FOR WORK TRUCKS			
	N N				N				N					
				NMOG	AND FLEE	T AVE	RAG	E INFORMA	TION					
NMOG RAF	MOG CH4 NMOG/NMHC HCHO/NMHC DT (3751 I V/W-				.VW-8	500 G				MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)				
*	*	*		*	C	0.074			*		*			
See the Attachment for Vehicle Medels, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-														

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have six (6) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of one hundred and seventy five dollars (\$175) per vehicle for the third through sixth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this day of November 2019.

Allen Eyons, Chief Emissions Certification and Compliance Division



FORD MOTOR COMPANY Executive Order: A-010-2226 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

			NMHC+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL	DIES	SEL-EPA	0.146	0.200	0.2	4.2	*	*	*	6	0.001	0.008	
50°F @4K		*	*	*	*	*	*	*	*	*			
				-	N	NMHC+NOx (g/mi)			CO (g/mi)				
			FUEL TYPE				CE	RT	STD	CER	т	STD	
HWFET @	D 50K			*			,	+	*				
HWFET	@ UL		E	IESEL-EI	PA		0.1	L14	0.200				
20°F @ 50K				*						*		*	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

		0.									
		1.000		US06		SC0	3	COMPOSITE			
	FUEL TYPE		NMHC+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMHC+NOx (g/mi)	CO (g/mi)	NMHC+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	
@ 4K	*	CERT	*	*		*	*				
Ŭ		STD	*	*		*	*				
		CERT	*	*	*	*	*	0.189	0.0	2	
@ UL	DIESEL-EPA	STD	*	*	*	*	*	0.800	22.0	10	
		BIN			and applied the second			0.800			

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

WHOLE VEHICLE EVAPORATIVE TESTING

			VVF	IULE V								
EVAPORATIVE FAMILY	FUEL TYPE	3	3DHS (g/test) @			@ UL 2DHS (g/test) @ UL			UL		L (g/mi) @ UL	
		CER	TS	TD	FEL	CERT	STD	FEL	CE	RT	STD	
*	*	*	*		*	*	*	*	*	r	*	
ORVR / FUI	ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS										ELS	
FUEL ONLY EVAP & CANISTER BLEED												
EVAPORATIVE	ORVR (g/g			3DHS RIG TEST		2DHS RIG TEST		BLEED CANISTER				
FAMILY				FUE	L TYPE	(g/test) @ UL		(g/test) @ UL		TEST (g/test) @ 4K		
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD	
*	*	*	*		*	*	*	*	*	*	*	

 EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)

 EVAPORATIVE FAMILY
 LEAK FAMILY

 *
 *

FORD MOTOR COMPANY Executive Order: A-010-2226 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4 *: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LWV; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,0-3750#LWV; LDT2: S00#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: medium- duty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LWV: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU! warm-up catalyst; NAC: NOX adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); OFF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOX sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AlR/AIRE: secondary air injection; IC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/s5: full/partial/partial with fines on-board diagnostic; DOR: direct ozen reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: paralle; (2) suffix: series; a hyphen (-) between after treatment tecSC indicates multiple functionalities of the after treatment devi			
LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751- 8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: medium- duty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR; gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/S: prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DFF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%" gasoline) fuel; A: automatic (with lockup); M: manual transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Av	CALIFORNIA AIR RESOURCES BOARD		New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles
	LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 600 8500#ALVW; MDV: medium-duty vehicle; MDV4: ME duty passenger vehicle; HDV: heavy-duty vehicle; EC emission limit; GVWR: gross vehicle weight rating; L' ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-er ADSTWC: adsorbing TWC; HAC: HC adsorbing cata SCRC/SCR-N or SCRC-NH3: selective catalytic redu continuous/periodic trap oxidizer; DPF: diesel particu heated/oxygen sensor; WR-HO2S or AFS: wide rang RDQS: reductant quality sensor; NH3S: ammonia se EGRC: EGR cooler; AIR/AIRE: secondary air injection fuel injection; DFI/IFI: direct/indirect fuel injection; TC full/partial/partial with fines on-board diagnostic; DOF prefix 2: parallel; (2) suffix: series; a hyphen (-) betwee device (ex. DPF-SCRC: SCR coated DPF); CNG/LN ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90 -automatic transmission; CV: continuously variable tr automated manual transmission; AMS: automated m EAER: equivalent AER; PHEV: plug-in hybrid electric	01-8500#GVWR,3751-5750 02 8501-10000#GVWR; MI CS: emission control system VW: loaded vehicle weight; nission vehicle; TZEV: trans- lyst; WU: warm-up catalyst iction-urea/ammonia; NH30 late filter (active); GPF: PM re/linear/heated air-fuel rationsor; EGR: exhaust gas rea- n (belt driven)/(electric driver)/(electric driver)/ (electric driver)/(electric driver)/(electric driver)/ compressed/liquefied na 0%"gasoline) fuel; A: automansmission; SCV: selectable anual-selectable transmission; SCV: selectable anual-selectable transmission; SCV: Flever (and the selectable transmission; SCV: Se	 #ALVW; LDT4: LDT 6001-8500#GVWR,5751- DV5: MDV 10001-14000#GVWR; MDPV: medium- n; CERT: certification; STD: standard; FEL: family ALVW: adjusted LVW; LEV: low emission vehicle; sitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ; NAC: NOx adsorption catalyst; SCR-U or DC: ammonia oxidation catalyst; CTOX/PTOX: I filter for spark-ignited engine; HO2S/O2S: b sensor; NOXS: NOx sensor; PMS: PM sensor; circulation; HP/LP EGR: High/Low Pressure EGR; en); PAIR: pulsed AIR; SFI/MFI: sequential/multiport CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: CT: hydrocarbon trap; BCAN: bleed carbon canister; dicates multiple functionalities of the after treatment tural gas; LPG: liquefied petroleum gas; E85: "85%" natic (with lockup); M: manual transmission; SA: semile continuously variable transmission; AM: ion; OT: other transmission; AER: all-electric range;

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	F250 2WD BED DELETE DIESEL	MDV4	6.7	SA10	* `	1	\$
FORD	F250 4WD BED DELETE DIESEL	MDV4	6.7	SA10	*	1	\$
FORD	F250 PICKUP 2WD DIESEL	MDV4	6.7	SA10	*	1	\$
FORD	F250 PICKUP 4WD DIESEL	MDV4	6.7	SA10	*	1	\$
FORD	F350 2WD BED DELETE DIESEL	MDV4	6.7	SA10	* ,	1	\$
FORD	F350 2WD DIESEL	MDV4	6.7	SA10	*	1	\$
FORD	F350 4WD BED DELETE DIESEL	MDV4	6.7	SA10	*	1	\$
FORD	F350 4WD DIESEL	MDV4	6.7	SA10	*	1	\$