

TOYOTA MOTOR CORPORATION

Executive Order: A-014-1032

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	ORM	ATION					
MODE		ST GROUP		VEHICL	E CLASS(E		FUEL CATEGORY			FUEL TYPE			
2020	LT	XV01.8P33			PC		HYBRID ELECTRIC VEHICLE				GASOLINE		
	USEFUL	LIFE (miles)		VEH	ICLE EMISS	ION CA	ATEG	ATEGORY INTERIM / INTERMEDIATE IN-US					
EXH	/ORVR	EVAP	FTP SF			SFT	FTP FTP			SFTP			
15	0000	150000		LEV3	LEV3 SULEV30 LEV 3 CC)MPOSITE *			PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD STATUS			ENGINE DISPLACEMENT (L)		
1	TWC (2), WR-H02S	S, EGR,	EGRC, SFI		FULL ALL MODELS							
*	* *							RTIAL	1.8				
* *								TAL WITH	*				
		Е	VAPO	RATIVE &	REFUELING	(EVA	PIORV	R) FAMILY	INFORMATIO	N			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY EVAP EMISSION STD VEHICLE CLASS SPECIAL									PECIAL FEATURES				
1	LTYXR01	30J72		LEV 3 OPTION2				PC			HCT		
				E	MISSION C	REDIT	INFO	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NOT ZERO-EVAP							ON-PZEV NMOG CREDIT FOR DOR			R	OPTIONAL EXH. STD FOR WORK TRUCKS		
	N N								И				
				NMOG	AND FLEE	TAVE	RAGE	INFORMA	TION				
NMOG RAF	NMOG/NMHC				(0-3750		.VW) LDT (3751 LVW-8500 MDV (10,0			NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*	* 0.065 0.074 *					*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



TOYOTA MOTOR CORPORATION

Executive Order: A-014-1032

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

Vehicles certified under this Executive Order shall not be introduced into commerce before January 2, 2019.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of December 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



GASOLINE-

LEV3 E10

0.001 0.20

LTYXR0130J72

TOYOTA MOTOR CORPORATION

Executive Order: A-014-1032 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

	EXHA	AUST E	MISS	SION S	TANDA	RDS AN	ID CERT	IFICA	TION L	EVELS (FTP, HWI	ET,	50°F, 20	0°F)		
FUE	L TYI	m a C	onox djustr RVR	ide; NO nent fac [g HC/g	x: oxide ctor; 2D gallon d	es of nitr HS/3DH lispensed	ogen; H(S [g HC/ d]: on-bo	CHO: f test]: 2 ard re	formalde 2/3 days fueling	ehyde; Pl s diurnal+ vapor rec	M: particul hot-soak; overy; g: c	ate n RL [g	natter; R g HC/mi ; mg: mi	RAF: re:]: runni Iligram	activi	ty ss:
				NMOG+NOx (g/mi)		CO (g/mi)		T	NOx (g/mi)		The second second				PM (g/mi)	
			CER	т :	STD	CERT	STE	5 (CERT	STD	CERT	T	STD	CEF	_	STD
оĸ	*		*		*	*	*		*	*	*		* *			*
			0.01	92 0	.030	0.15	1.0		*	*	•		4 0.0002		02	0.003
\$K	*		*		*	*	*		*	*	*		*		3 ₁₄ (
				FUF	I TYP	F			-		x (g/mi)			CO (g	/mi)	
						-			CE	RT	STD		CER	T		STD
HWFET @ 50K					*					*	*					9 11 7 1
T @ UL			G.	SOLIN	E-TIE	Ŗ3 E10			0.0	065	0.030					
20°F @ 50K COLD			CO E10 REGULAR GASOL			ASOLINE	(TIER	(TIER3)					8 10.0			
		S	FTP	EXHAU	IST EM	ISSION	STANDA	ARDS	AND C	ERTIFIC	ATION LE	VEL	S			
															SITE	,
FUEL T	TYPE		N	MOG+N (g/mi)	Ox	CO (g/mi)	4				CO (g/mi)			1301		PM (mg/mi)
*		CERT		*		*				*	*					
	S			*		*				*	*					
				*		*	0.	4		*	* 0.01		.0179	0	24	*
(m 1 II I		STD		*		*		5	* *		(0.083 4.2		. 2	*	
		BIN														
	WH	IOLE V	EHIC	LE EV						X 50000000 20		ATIO	N LEVE	LS		
00 4 TU /					W	HOLE V	EHICLE	EVAP	ORATI	VE TEST	ING		_			
MILY	F	UEL T	YPE	3	DHS (g	/test) @	UL		2DH	S (g/test)	@ UL		F	KL (g/m	11) @	UL
				CER	RT :	STD	FEL	CE	RT	STD	FEL	•	CEI	RT		STD
1 T.TVXD0130.T72 1			The state of the s	10 13081 0 300 1		*	0.1	0.1170 0.300		* 0.		0.05				
DRVR / F	UEL	ONLY	CAN	IISTER	BLEE	EVAPO	DRATIVE	EMIS	SSION	STANDA	RDS AND	CE	RTIFICA	TION	LEVE	LS
														D		
ORATIV MILY	E	ORVR	(g/g	allon) @	g UL	FUEL		3DHS RIG TEST (g/test) @ UL								
		FUEL TYPE						CE	CERT STD		CERT S				STD	
	FUEL T # GASOLI TIER3 ORATIVE ORATI	FUEL TYPE SAMILY FUEL TYPE * GASOLINE— TIER3 E10 WH ORATIVE AMILY ORATIVE AMILY	FUEL TYPE FUEL TYPE GASOLINE- TIER3 E10 GUL GOUL	FUEL TYPE CH4: r monox adjustr ORVR 1000 r 10000 r 10000 r 1000 r 1000 r 1000 r 1000 r 1000 r 1000 r 10000	FUEL TYPE CH4: methane monoxide; NC adjustment fac ORVR [g HC/g 1000 miles; F:	FUEL TYPE FUEL TYPE FUEL TYPE CH4: methane; NMO monoxide; NOx: oxid adjustment factor; 2D ORVR [g HC/gallon of 1000 miles; F: degree of 1000 mi	FUEL TYPE	FUEL TYPE	FUEL TYPE	CH4: methane; NMOG: non-CH4 organic gas; HC: monoxide; NOx: oxides of nitrogen; HCH0: formald adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarb monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; Ph adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+ORVR [g HC/gallon dispensed]: on-board refueling vapor recipion of miles; F: degrees Fahrenheit; FTP: federal test procedured in the procedure of the proce	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMH monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particular adjustment factor; 2DHX/3DHS [g HC/Hcst]: 2/3 days diurnal-hot-socul adjustment factor; 2DHX/3DHS [g Hc/Hcst]: 2/10 days diurnal-hot-socul adjustment factor; 2DHX/3DHS [g Hc/Hcst]: 2/10 d	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: not monoxide; NOx: oxides of nitrogen; HCH0: formaldehyde; PM: particulate adjustment factor; 2DHS/3DHS [g HC/test]; 2d ays diunal+hot-soak; PM: particulate adjustment factor; 2DHS/3DHS [g HC/test]; 2d ays diunal+hot-soak; PM: particulate adjustment factor; 2DHS/3DHS [g HC/test]; 2d ays diunal+hot-soak; PM: particulate adjustment factor; 2DHS/3DHS [g HC/test]; 2d ays diunal+hot-soak; PM: particulate adjustment factor; 2DHS/3DHS [g/mi]; 2DHS/3DHS/3DHS/3DHS/3DHS/3DHS/3DHS/3DHS/3	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 monoxide; NOx oxides of nitrogen; HCH0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g HCH0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g HCH0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g HCH0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g HCH0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g HcH0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g HcH0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde; PM: particulate matter; Eye adjustment factor; 2DHS/30HS (g Hch0: formaldehyde	FUEL TYPE	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon, NMHC: non-CH4 HC; CO: car monoxide; NOx oxides of nitrogen; HCH0: formaldehyde; PM: particulate matter; RAF: reached; adjustment factor; 2DHS/3DHS [g HCHest]: 27d days diumal+not-sox; RE [g HC/mi]: running to ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g gram; mg; milligram; mi: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP NMOG+NOX



TOYOTA MOTOR CORPORATION

Executive Order: A-014-1032

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIV	E LEAK DIAMETER STAND	ARD AND CERTIFICATION	LEVEL (INCHES)
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD
LTYXR0130J72	LTYXR0130J72-001	*	0.02

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst, CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR	: VEHICLE MODELS IN	NFORMATION	

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
TOYOTA	COROLLA HYBRID	PC	1.8	CV1	LTYXR0130J72	1	F