

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	UP IN	FORM	IATION	a.				
MODE YEAR	- 1 16	ST GROUP	VEHICLE CLASS(ES)					FUEL CATEGORY			FUEL TYPE		
2020	LT	YXV02.0N4B	02.0N4B PC						SINGLE FUEL HICLE		GASOLINE		
l	JSEFUL	LIFE (miles)		VEHICLE EMISSION CATEGO				ORY	INTERIM / INT	FERM	RMEDIATE IN-USE STD		
EXH/ORVR EVAP				FTP S			SFT	FTP FTP			SFTP		
150000 150000				LEV3	ULEV50 LEV 3 C		3 CO	COMPOSITE NMOG+NOX AN		D PM	рм рм		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS OBD STATUS								EN	ENGINE DISPLACEMENT (L)				
1 TWC(2), WR-HO2S(2), DFI, SFI, EGR, EGRC FULL AI							ALL MODELS						
*			*				P	PARTIAL * 2.0					
* * PARTIAL WITH * FINES													
		E	VAPO	RATIVE &	REFUELING	(EVA	P/OR	R) FAMIL	INFORMATION	1			
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY EVAP EMISSION STD VEHICLE CLASS SPECIAL FEATURES							ECIAL FEATURES					
LTYXR0130P72 L					LEV 3 OPTION2			PC			HCT		
				I	MISSION C	REDIT	INFO	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS			
		N			N			N N					
				NMOG	AND FLEE	T AVE	RAGE	INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO	Contraction of the local division of the loc	HO/NMHC RATIO	DC-1 DL (0-3750)						MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		0.019	(	0.065			0.074		*		
0 + -	A 11 1	11-11-1					<b>F</b>	D:			tral Systems Dhase		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

## BE IT FURTHER RESOLVED:

Vehicles certified under this Executive Order shall not be introduced into commerce before January 2, 2019.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of December 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

CALIFORNIA AIR RESOURCES BOARD							TOYOTA MOTOR CORPORATION			Executive Order: A-014-1034 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4									
				14				A٦	TAC	HME	ENT	9 							
	EX	HAU	ST A	ND E	VAP	ORAT	IVE	EMIS	SION S	TAN	DAR	DS AND	CERTIF	ICA	TION	LEVE	LS		
		EX	HAU	ST EM	ssio	N STA	NDAF	RDS AN	ID CERT	IFICA	TION	LEVELS (	FTP, HWF	ET,	50°F, 20	D°F)			
	F	UEL -	adj OF		CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon nonoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity idjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; DRVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP										ty ss;				
	10				NMOG	+NOx			со		I	NOx	H	існо	)	РМ			
					(g/	mi)		()	g/mi)		(g/mi)		(mg/mi)		ii)	)		(g/mi)	
	-				ERT	ST	D	CERT	ST		CERT	STD	CERT		STD	CER	т	STD	
FTP@50		*			*	*		*	*		*	*	*		*	*	_	*	
FTP@U		GASOL FIER3		100	0192	0.0	50	0.21	1.7		*	*	*		4	0.00	01	0.003	
50°F @4	ιĸ	*			*	*		*	*		*	*	*		* .	$\gamma_{\pm}^{12}\phi_{\pm}\gamma_{\pm}^{3}\phi_{\pm}$			
1						FUEL	TYPE					MOG+NC				CO (g			
1.044											ERT	ERT STD		CERT			STD		
HWFET	6 @ 5	0K				,		•				*	*		and a second				
HWFE	т@เ	JL			GASO	LINE-	TIER	3 E10			0.	0116	0.050	1	展開				
20°F (	@ 50k	ĸ	COL	D CO E	10 R	EGULA	R GA	SOLINE	C (TIER	.3)				5	1.2	1		L0.0	
				SFT	PEX	HAUST	EMI	SSION	STAND	ARDS	AND	CERTIFIC	ATION LE	VEL	S				
			1 (2015) - (2015)				NMOG+NOx (		S06				SC03				OMPOS		
	FUE	LTYF	°E		CO PM (g/mi) (mg/mi)					) NMOG+NOx (g/mi)		CON (g/mi)		NMOG+NOx (g/mi)		O mi)	PM (mg/mi)		
@ 4K		*	C	CERT		*		*				*	*						
				STD		*	4	*				*	*			-			
	<b>C N C</b>	ASOLINE-		CERT		*	_	*	0.	. 3		*	*	0	.0251	0.	42	*	
@ UL				TIER3 E10		STD		*		*		5		*	*	C	.083	4	. 2
				BIN			1.18	4. J			1.50				0.050	144			
			WHO	LEVE	ICLE	EVAP							ERTIFICA	TIO	N LEVE	LS			
EVAP		TIVE			-		WH	IOLE V	EHICLE	EVAP	ORA	TIVE TEST	ING			RL (g/m	i) @	111.	
	MILY		FU	IEL TYP	PE	3Dł	IS (g/	/test) @	) UL		2DH	IS (g/test)	@ UL			(g/iii	1) @		
						CERT STD		TD	FEL	CE	RT STD		FEL		. CER			STD	
LTYXR0130P72		)P72	2 GASOLINE- TIER3 E10		10	0.1996 0.300		300	0 *		ł	0.300	*	*		0.005		0.05	
(	ORVR	R / FUE	EL O	NLY/C	ANIST	ER B	EED	EVAPO	ORATIV	EEMI	SSION	STANDA	RDS AND	CEF	RTIFICA	TION	EVE	LS	
			0		/dallo	n) @ I	H					ONLY EVA	P & CAN					MISTER	
EVAP FA			5	it in (g	'R (g/gallon) @ UL		FUE	FUEL TYPE			) @ UL		IS RIG TEST (test) @ UL		BLEED CANISTE TEST (g/test) @ 4				
4.000-123				L TYPE	CE	RT	STD	-			ERT	STD	CERT				CERT S		
LTYXR0130P72			OLINE- R3 E10		03 0	.20	GASOLINE- LEV3 E10			*	*	*		*	0.01	21	0.020		

	CI			NIA	
	CF	4 L I I		NIA	
1	AIR	RESO	URCES	BOARD	

Executive Order: A-014-1034 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

EFFECTIV	E LEAK DIAMETER ST	ANDARD AND CERTIFICATION	LEVEL (INCHES)			
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD			
LTYXR0130P72	LTYXR0130P72-001	*	0.02			
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: su ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxid heated/oxygen sensor; WR-H RDQS: reductant quality sen secondary air injection (belt of direct/indirect fuel injection; T fines on-board diagnostic; D( suffix: series; CNG/LNG: con E10: "10%" ethanol ("90%"ga continuously variable transm automated manual-selectable	0#LVW; LDT3: LDT 6001-85 duty vehicle; MDV4: MDV 85 ': heavy-duty vehicle; ECS: e vehicle weight rating; LVW: per ULEV; ZEV: zero-emissi fAC: HC adsorbing catalyst; : selective catalytic reduction izer; DPF: diesel particulate f02S or AFS: wide range/lin sor; NH3S: ammonia sensor driven)/(electric driven); PAIF 'C/SC: turbo/super charger; DR: direct ozone reducing; H npressed/liquefied natural ga asoline) fuel; A: automatic (w ission; SCV: selectable conti e transmission; OT: other tra	00#GVWR,3751-5750#ALVW; LDT4 501-10000#GVWR; MDV5: MDV 100 mission control system; CERT: certif oaded vehicle weight; ALVW: adjuste on vehicle; TZEV: transitional ZEV; T WU: warm-up catalyst; NAC: NOX ad n-urea/ammonia; NH3OC: ammonia of filter (active); GPF: PM filter for spark ear/heated air-fuel ratio sensor; NOX EGR: exhaust gas recirculation; EG :: pulsed AIR; SFI/MFI: sequential/mu CAC: charge air cooler; FFH: fuel fire CT: hydrocarbon trap; BCAN: bleed s; LPG: liquefied petroleum gas; E85 th lockup); M: manual transmission; nuously variable transmission; AM: a	01-14000#GVWR; MDPV: medium- ication; STD: standard; FEL: family ed LVW; LEV: low emission vehicle; WC/OC: 3-way/oxidizing catalyst; Isorption catalyst; SCR-U or oxidation catalyst; CTOX/PTOX: -ignited engine; HO2S/O2S: S: NOx sensor; PMS: PM sensor; RC: EGR cooler; AIR/AIRE: Iltiport fuel injection; DFI/IFI: d heater; F/P/\$: full/partial/partial with carbon canister; prefix 2: parallel; (2) i; "85%" ethanol ("15%"gasoline) fuel; SA: semi-automatic transmission; CV: utomated manual transmission; AMS: AER: equivalent AER; PHEV: plug-in			

5	2020 MODEL	YEAR: VE	HICLE M	ODELS INF	ORMATION		
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
TOYOTA	COROLLA	PC	2.0	SCV10	LTYXR0130P72	1	F
TOYOTA	COROLLA	PC	2.0	М6	LTYXR0130P72	1	F
TOYOTA	COROLLA XSE	PC	2.0	SCV10	LTYXR0130P72	1	F