

TOYOTA MOTOR CORPORATION

Executive Order: A-014-1048

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				-	TEST GRO	UP IN	IFOR	MATION					
MODE	1 1 1	ST GROUP	VEHICL	E CLASS(ES)			FUEL C	ATEGORY		FUEL TYPE			
2020) LT	YXV01.8P34			PC			HYBRID ELECTRIC VEHICLE			GASOLINE		
	USEFUL	LIFE (miles)		VEH	ICLE EMISS	CLE EMISSION CATEGORY				NTE	RMEDIATE IN-USE STD		
EXI	H/ORVR	EVAP		FTP SFTP			ГР	FTP		SFTP			
1.	50000	150000	LEV3	SULEV30	ULEV30 LEV 3 COMPO			*		PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD STATUS			ENGINE DISPLACEMENT (L)		
1	1 SFI, EGR, EGRC, WR-HO2S, TWC(2), HO2S							FULL	ALL MODELS				
*						Р	ARTIAL	*		1.8			
*							TIAL WITH FINES	*	100				
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
LTYXR0130J72 LEV 3 OPTION2								PC			HCT		
				E	EMISSION C	REDI	ΓINFO	RMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON- ZERO-EVAP							NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
	N N							N N					
				NMOG	AND FLEE	ΓAVE	RAGI	E INFORMA	TION				
NMOG RAF	NMOG/NMHC					0-375		V) LDT	IMOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		0.005	C	.065			0.074	*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



TOYOTA MOTOR CORPORATION

Executive Order: A-014-1048

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Allen Lyons, Chief

Emissions Certification and Compliance Division



FAMILY

LTYXR0130J72

FUEL TYPE

GASOLINE-

LEV3 E10

CERT

0.001

STD

0.20

TOYOTA MOTOR CORPORATION

Executive Order: A-014-1048

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

TEST (g/test) @ 4K

CERT

STD

*

(g/test) @ UL

STD

CERT

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

												CERTI				3			
		EXH/										FTP, HWI							
	FUE	FUEL TYPE		monoxide adjustme DRVR Id	e; NOx: ont factor HC/gallo	xide ; 2DI on di	s of nit 4S/3DH spense	rogen; H0 IS [g HC/ d]: on-bo	CHO: 'test]: ard re	formald 2/3 day fueling	lehyde; Pl 's diurnal+ vapor rec	oon; NMH M: particul hot-soak; overy; g: (ire; SFTP	ate r RL [gram	natter; R. g HC/mi] ; mg: mil	AF: reacti : running ligram; mi	vity loss;			
	No.					CONTRACTOR O		IOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		1	HCHO (mg/mi)		PM (g/mi)	
				CERT	STE	, +	CERT)	CERT	STD	CERT		STD.	CERT	STD			
TP@50)K			*	*		*	*		*	*	*		*	*	*			
FTP@U	GAS	GASOLINE- LEV3 E10		0.0177	0.03	30	0.14	1.0		*	*	*		4	4 0.0004				
50°F @4	1K	*		*	*		*	*		*	*	*		*		16 m. v			
				FUEL TYPE						NMOG+NOx (g/					CO (g/mi)				
								CI	ERT	STD		CER	T	STD					
HWFET @ 50K					*				*	*	*								
HWFE	T @ UL			GAS	OLINE-	LEV:	3 E10			0.	0084	0.030			The second of the second				
20°F @ 50K COLD CO E10 REGULAR GASOL						SOLIN	E (TIER	3)	2.5				0.72	2	10.0				
				SFTP EX	HAUST	EMI	SSION	STANDA	ARDS	AND C	ERTIFIC	ATION LE	VEL	.S					
viole is to		UEL TYPE		U			JS06				SC03				OMPOSITE				
	FUEL T			NMOG+NOx (g/mi)		CO (g/mi)	PM) (mg/mi)			G+NOx _J /mi)	CO (g/mi)		OG+NO> (g/mi)	CO (g/mi	PM (mg/m				
@ 4K	*	* C		* CE		Т	*		*				*	* .					
)	*		*				*	*							
	an		CER	Т	*	_	*	0.	. 4		*	*	0	.0147	0.14	*			
@ UL		LEV3 E10 BI			*		*		5		*	*	1	0.083	4.2	*			
														0.030					
		WH	OLE	VEHICL	EEVAP							ERTIFIC	ATIO	N LEVE	LS				
EVAPORATIVE FUEL		-UEL	TYPE	3DH	HOLE VEHICLE EVAF			2DHS (g/test) @ UL				RL (g/mi) @ UL		@ UL					
FA	AMILY	ILY				STD FEL		CE	CERT S		FEL	L CER		RT	STD				
LTYXR0130J72		7 1	GASOL LEV3				300			.170 0.300		*	0.00		00	0 0.05			
(ORVR / F				TER BL	EED	EVAP	ORATIVI	EEMI	SSION	STANDA	RDS AND	CE	RTIFICA	TION LE'	/ELS			
		T							F	UEL O	NLY EVA	P & CAN	STE	R BLEE					
	ORATIV	₹ (g/gall	on) @ U	L	FUE	. TVDE			HS RIG TEST 2DHS RI			G TEST BLEED CANISTER							

(g/test) @ UL

STD

CERT

FUEL TYPE



TOYOTA MOTOR CORPORATION

Executive Order: A-014-1048

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
LTYXR0130J72	LTYXR0130J72-001	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
TOYOTA	PRIUS	PC	1.8	CV1	LTYXR0130J72	1	F
TOYOTA	PRIUS ECO	PC	1.8	CV1	LTYXR0130J72	1	F