

Executive Order: A-014-1062

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	FORMA	TION			
MODE		EST GROUP	VEHIC	VEHICLE CLASS(ES)  FUEL CATEGORY  DEDICATED SINGLE FUEL  VEHICLE			FUEL C	ATEGORY	FUEL TYPE	
2020	L	TYXV02.0K6B							GASOLINE	
	USEFU	L LIFE (miles)	VEH	ICLE EMIS	SION C	ATEGOR	RY	INTERIM / INT	ERMEDIATE IN-USE STD	
EXH	ORVR	EVAP		FTP		SFTP		FTP	SFTP	
15	0000	150000	LEV3	ULEV125	LEV	3 COMP	OSITE	10 1 × 10 × 10 × 10 × 10 × 10 × 10 × 10	PM	
SPE	CIAL FI	EATURES & EXI	AUST EMISSIC	ON CONTRO	OL	17	OBD ST	TATUS	ENGINE DISPLACEMENT	
1		SFI, WR-HO	2S, TWC(2),	HO2S	14,00	FU	LL	ALL MODELS	Control Change	
*	*					PAR	TIAL	*	2:0	
*	*						L WITH	*		
		EV	APORATIVE &	REFUELING	G (EVA	P/ORVR)	FAMILY	INFORMATION		
EVA	P / ORV	/R FAMILY	EVAPORATIVE	STD CATE	GORY	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES	
I	TYXR0	130P72	LEV 3	OPTION2			P	С	HCT	
				EMISSION C	REDIT	INFORM	IATION			
COEDU ENDEYTENDED					EDIT FOR NON-PZEV NN			REDIT FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS	
N N					711	N N				
			NMOG	AND FLEE	T AVE	RAGE IN	FORMAT	TION		
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO	NMOG+NOX FLEET PC+LDT (0-3750 LV (g/mi)			LDT (	+NOX FLEET STI (3751 LVW-8500 R) + MDPV (g/mi)	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)	
*	*	1.10	0.016		0.065			0.074	*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-014-1062

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

STEET WEST TO SEE

### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Allen Lyons, Chief

OF THE PROPERTY OF THE PROPERT

Emissions Certification and Compliance Division

day of October 2019.

Executive Order: A-014-1062

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

## **ATTACHMENT**

## **EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS**

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

## **FUEL TYPE**

130.04		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	* 10 mm		*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10	0.0489	0.125	0.40	2.1	*	*	*	4	0.0002	0.003
50°F @4K	A STATE OF THE REAL PROPERTY.	*	*	*	*	*	*	* e	*		教教科的

		NMOG+N	Ox (g/mi)	CO (g/mi)		
William Sale	FUEL TYPE	CERT	STD	CERT	STD	
HWFET @ 50K		*	*		SANTER STRAFF	
HWFET @ UL	GASOLINE-TIER3 E10	0.0247	0.125	Action because the said Square	a to the file of the control of the control of	
20°F @ 50K	COLD CO E10 REGULAR GASOLINE (TIER3)	THE PARTY		1.27	10.0	

### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

-			US06			SC03		COMPOSITE		
1	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD * *		*	*		429.00			
		CERT	*	*	1.6	*	*	0.0430	0.72	*
@ UL	GASOLINE- TIER3 E10	STD	*	*	6	*	*	0.083	4.2	*
		BIN				<b>张生成加美</b>		0.080	A 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	

### WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

	FUEL TYPE		WHOLE						
EVAPORATIVE FAMILY		3DHS	S (g/test) (	@ UL	2D	HS (g/test) @	RL (g/ml) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
LTYXR0130P72	GASOLINE- TIER3 E10	0.1996	0.300	*	*	0.300	*	0.005	0.05

### ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K				
	<b>FUEL TYPE</b>	CERT	STD		CERT	STD	CERT	STD	CERT	STD			
LTYXR0130P72	GASOLINE- TIER3 E10	0.003	0.20	GASOLINE- LEV3 E10	*	*	*	*	0.0121	0.020			



Executive Order: A-014-1062

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

112 COLUM

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
LTYXR0130P72	LTYXR0130P72-001	Control of San Branch Marie Control of the Bridge of the B	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission: CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER: PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits. Y = credits, S = credits for some/select models

## 2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
TOYOTA	C-HR	PC	2.0	SCV7	LTYXR0130P72	1	F

SAN LERT EXCEPTIONS TO SANTY TOURIST

GUITE CANTELLINE FED EVALUES FOR THE EMISSION STATEGISTS AND CRITE TO TOWN EVEL OF

11 to leave

SURE ON PROPERTY ENDINE

A SHE STORY OF SHEET OF SHEET AND STORY OF SHEET

SOURCE AND AND REPORT AND AND AND ADDRESS OF THE PROPERTY OF T

STEEL STATE