

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP II	NFOR	MATION						
MOD		TEST GROUP		VEHIC	LE CLASS(E	S)		FUEL CATEGORY			FUEL TYPE			
202	021 MTYXV01.8P33 PC							HYBRID ELECTRIC VEHICLE			GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION								GORY	INTERIM / IN	RM	RMEDIATE IN-USE STD			
EX	H/ORVR	R EVA		FTP S			FTP FTP			SFTP				
150000 150000 LEV3 SULEV30						LEV	3 C	OMPOSITE	*		PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	STATUS		ENGINE DISPLACEMENT			
1		SFI, EGR, EGR	,WR-H	025, TWC (2),H02S			FULL	LL ALL MODELS					
*			*			F	ARTIAL *				1.8			
*					PAR	RTIAL WITH *								
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EV	AP / OR	VR FAMILY	EVA	PORATIVE	E STD CATE	GORY	RY EVAP EMISSION STD VEHICLE CLASS				SPECIAL FEATURES			
	MTYXR0	130J72		LEV 3	OPTION2			PC			HCT			
				1	EMISSION CI	REDIT	INFO	ORMATION						
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV NMOG CREDIT FOR DOR			R	OPTIONAL EXH. STD FOR WORK TRUCKS			
N N									N					
				NMOG	AND FLEET	AVE	RAG	E INFORMA	ΓΙΟΝ					
NMOG RAF						0-375				0				
*	*	1.10		0.013	0	.058		0.065				*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-014-1068 dated March 25, 2020.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 16th day of June 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

GASOLINE-

LEV3 E10

MTYXR0130J72

0.001 0.20

*

TOYOTA MOTOR CORPORATION

ATT	ACI	-IMF	=NT
		REARF	

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

					MOG+N (g/mi)			CO (g/mi)			lOx /mi)		HCH mg/n			PM (g/mi)		
				CEF	RT	STD	CER	T ST	D	CERT	STD	CER	r	STD	CE	RT	STD	
FTP@5	ок	*		*		*	*	*		*	*	*		*		*	*	
FTP@l	FTP@UL GASOLINE- TIER3 E10		Second	0.01	.92 0	.030	0.15	5 1.	0	*	*	*		4 0.00		002	0.003	
50°F @4K		*	*			*	*	*		*	*	*	*					
					EU		F			N	MOG+NC	Dx (g/mi)				(g/mi)	1	
					FU	FUEL TYPE				CE	CERT			CEF	RT		STD	
HWFE	T @ 50	ĸ				*					*	*						
HWFE	T @ UL	-		G	ASOLIN	E-TIE	R3 E10	1		0.0	0.0065 0.030							
20°F	@ 50K	0	COLD	CO E1	0 REGU	LAR G	ASOLIN	E (TIEF	R3)					0.88			10.0	
				SFTP	EXHAL	JST EN	IISSION	STAND	ARDS	AND C	ERTIFIC	ATION LE	VEL	S				
							US06	JS06			SC03		C		OMPOSITE			
	FUEL	FUEL TYPE		PE N		G+NOx CO			М	1	G+NOx	со	NMOG+NOx (g/mi)			CO	PM	
					(g/mi)		(g/mi) (mg/n		ı/mi)	(g/mi)		(g/mi)			(g/mi)	(mg/mi)	
@ 4K	*		CEF	RT	*		*			*		*						
6			ST	D	*		*				*	*						
		GASOLINE- TIER3 E10 BI		रा *		* *		0	. 4		*	*	0	.0179	0.24		*	
@ UL				D	*		*	* 6			*	*	0.077		4.2		*	
													0.03					
		W	HOLE	VEHIC	LE EV	APOR	ATIVE E	MISSION	STA	NDARD	S AND C	ERTIFICA	TIO	N LEVE	LS			
						N	HOLE \	/EHICLE	EVAP	ORATI	VE TEST	ING						
	ORATI			3	3DHS (g/test) @ UL					S (g/test)	@ UL		RL (g/i		g/mi) @ UL			
					CER	RT	STD	FEL	CE	RT	STD	FEL		CERT		STD		
MTYXR0130J72			GASOI LEV3	E10		0.1308 0		*	* 0.1		0.300	* *		0.00		0 0.05		
(ORVR /	FUEL	ONLY	/ CAN	ISTER	BLEE	D EVAP	ORATIVI				RDS AND				LEVI	ELS	
											Course of the local division of the local di	P & CANI						
	ORATI	VE	ORV	R (g/g	ganoni, e o			1	HS RIG TEST g/test) @ UL		2DHS RIG (g/test) @					ED CANISTER (g/test) @ 4K		
F/	AMILY	-	UEL T	VDE	CERT	STD		FUEL TYPE		RT STD		CERT	1	STD	CERT		STD	
			UEL I		VERI	310			+		910		+					

CALI AIR RESO	FORNIA urces board	TOYOTA MOTOR CORPORATION		Executive Order: A-014-1068-1 New Passenger Cars, Light-Duty Trucks an Medium-Duty Vehicle Page 4 of 4				
EFFECTIV	E LEAK DIAMETER	STA	NDARD AND CER	TIFICATION L	EVEL (INCHES)			
EVAPORATIVE FAMILY	LEAK FAMILY		CERT	г	STD			
MTYXR0130J72	MTYXR0130J72-00	01	*		0.02			
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium-o duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxidi heated/oxygen sensor; WR-H RDQS: reductant quality sens EGRC: EGR cooler; AIR/AIRI fuel injection; DFI/IFI: direct/in full/partial/partial with fines or prefix 2: parallel; (2) suffix: se	0#LVW; LDT3: LDT 600 duty vehicle; MDV4: MD : heavy-duty vehicle; EC vehicle weight rating; LV per ULEV; ZEV: zero-em AC: HC adsorbing cata : selective catalytic redu zer; DPF: diesel particu IO2S or AFS: wide rang sor; NH3S: ammonia se E: secondary air injectio ndirect fuel injection; TC board diagnostic; DOF ries; a hyphen (-) betwee	1-850 V 850 CS: em /W: lo lyst; W lotion- late fil e/linea nsor; I n (belf c/SC: tr R: direction en aft	0#GVWR,3751-5750 1-10000#GVWR; ME nission control system aded vehicle weight; vehicle; TZEV: trans VU: warm-up catalyst; urea/ammonia; NH30 ter (active); GPF: PM ar/heated air-fuel ratio EGR: exhaust gas rea t driven)/(electric drive urbo/super charger; C ct ozone reducing; H0 ter treatment ECS ind	#ALVW; LDT4: 0V5: MDV 1000 n; CERT: certific: ALVW: adjusted itional ZEV; TW ; NAC: NOx ads 0C: ammonia ox d filter for spark-io o sensor; NOXS circulation; HP/L en); PAIR: pulse CAC: charge air CT: hydrocarbon licates multiple f	kidation catalyst; CTOX/PTOX:			

device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2021 MODEL YEAR: VEHICLE MODELS INFORMATION												
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD					
TOYOTA	COROLLA HYBRID	PC	1.8	CV1	MTYXR0130J72	1	F					
TOYOTA	PRIUS	PC	1.8	CV1	MTYXR0130J72	1	F					
TOYOTA	PRIUS AWD	PC	1.8	CV1	MTYXR0130J72	1	F					
TOYOTA	PRIUS ECO	PC	1.8	CV1	MTYXR0130J72	1	F					