

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP INFO	RMATION				
MODE		TEST GROUP VEHIC			LE CLASS(ES)	FUEL	CATEGORY	FUEL TYPE		
2020	LN	SXTO3.5N7B			LDT2		1 P	SINGLE FUEL CHICLE	GASOLINE		
USEFUL LIFE (miles) VEHICLE E						SION CAT	EGORY	ERMEDIATE IN-USE STD			
EXH/ORVR EVAP				FTP SI			FTP.	FTP	SFTP		
15	0000	15000	0	LEV3	ULEV125	LEV 3	COMPOSITE	×	i in the table in the		
SPE	CIAL FE	ATURES & E				DL	OBD S		ENGINE DISPLACEMENT		
1	2	TWC, 2HO2S	2WR-	-HO2S, DE	I, TWC		FULL				
*			*				PARTIAL ALL MODELS 3.5				
*			*	*							
		E	VAPO	RATIVE &	REFUELING	G (EVAP/O	RVR) FAMIL	Y INFORMATION	1		
EVA	P / ORV	R FAMILY	EVA	PORATIVE	STD CATE	GORY		ISSION STD E CLASS	SPECIAL FEATURES		
I	NSXR01	20PBC		L	EV 2		L	DT2	*		
				E	EMISSION C	REDIT IN	ORMATION				
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						NMOG C	REDIT FOR DOI	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N	N		
		5.		NMOG	AND FLEE	TAVERAG	GE INFORMA	TION			
NMOG RAF	RAF NMOG/NMHC RATIO PC+LDT (0-3					W) LDT	+NOX FLEET S (3751 LVW-8500 R) + MDPV (g/m				
*	*	1.10		*		0.065		0.074	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



NISSAN MOTOR COMPANY, LTD.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of May 2019.

(netti) 又是自由

C norman

th

Allen Lyons, Chief Emissions Compliance, Automotive Regulations and Science Division

and the state of the second of the second second and the second second second second second second second second



NISSAN MOTOR COMPANY, LTD. Executive Order: A-015-0844 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon
monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity
adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss;
ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K:
1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			A contract of the	G+NOx mi)	CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)		M mi)		
		· · · · · · · · · · · · · · · · · · ·	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD		
FTP@50K	< *		*	*	*	*	*	*	*	*	*	*		
FTP@UL		OLINE- 73 E10	0.032	0.125	0.4	2.1	*	*	*	4	*	0.01		
50°F @4K		*	*	*	*	*	*	*	*	*	建洲和常	潮潮潮		
					_		NN	NMOG+NOx (g/mi)			CO (g/mi)			
				FUEL TYP	'E		CE	RT	STD	CER	Г., <u>Т</u>	STD		
HWFET @	IWFET @ 50K *					*		*						
HWFET @ UL			GASO	LINE-LEV	'3 E10		0.0	13	0.125		關於			
20°F @ 50K		COLD	CO E10 RI	EGULAR G	ASOLINE	(TIER3)				1.2	en all'a	12.5		
			SFTP EXH	AUSTEM	ISSION ST	TANDAR	OS AND CE	RTIFICA	TION LE	VELS		1997 ^{- 43}		
A State	US06							SC03 COMPC						
- 1997					NIMOC	INOW	00	NMOCINO	00	DA				

	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*		主要的	
		CERT	*	*	*	*	*	0.030	0.7	*
@ UL	GASOLINE- LEV3 E10	STD	*	*	*	*	*	0.083	4.2	*
		BIN	Mathin Tampin	AN AN AN	And the state			0.110		A REAL

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WH	IOLE \							
EVAPORATIVE FAMILY	FUEL TYPE	3	DHS (g/	/test) (DUL	2DH	F	RL (g/mi) @ UL			
		CER	T S	TD	FEL	CERT	STD	FEL	CE	RT	STD
LNSXR0120PBC	GASOLINE - CA PHASE 2	0 4	6 0	. 65	*	0.44	0.85	*	0.0	000	0.05
ORVR / FU	EL ONLY / CAN	NISTER	BLEED	EVAP	ORATIVE	EMISSION		RDS AND O	CERTIFICA	TION LE	/ELS
	а.			FUEL ONLY EVAP & CANISTER BLEED							
EVAPORATIVE FAMILY	ORVR (g/g	allon) @	DL 0	FUEL TYPE		3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANIST TEST (g/test) @	
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD
LNSXR0120PBC	GASOLINE - TIER 2 UNLEADED	0.13	0.20		*	*	*	*	*	*	*

AA	ALIFORN R RESOURCES BO		SSAN MOTOR OMPANY, LTD		Executive Order: A-015-0844 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4				
E	FFECTIVE LEAK DIA	METER STAN	DARD AND	CERTIFICATIO	N LEVEL (INCHES)			
EVAPORATIVE I	AMILY LEAK	FAMILY		CERT	S.				
- Partie and a straight for the straight	Address of the second second second	*		11.11.11.11.11.11.11.11.11.11.11.11.11.					
emission limit; GVV ULEV: ultra LEV; S ADSTWC: adsorbin SCRC/SCR-N or SC continuous/periodic heated/oxygen sens RDQS: reductant q secondary air inject direct/indirect fuel ir fines on-board diag suffix: series; CNG/ E10: "10%" ethanol continuously variab automated manual-	icle; HDV: heavy-duty vi /R: gross vehicle weight ULEV: super ULEV; ZEV g TWC; HAC: HC adsor CRC-NH3: selective cata trap oxidizer; DPF: dies sor; WR-HO2S or AFS: vi Jality sensor; NH3S: am ion (belt driven)/(electric nostic; DOR: direct ozor LNG: compressed/liqued ("90%"gasoline) fuel; A: e transmission; SCV: se selectable transmission; de; NMOG + NOx Fleet	rating; LVW: loa /: zero-emission bing catalyst; W alytic reduction-u sel particulate filte wide range/linear monia sensor; E driven); PAIR: p uper charger; CA the reducing; HCT fied natural gas; automatic (with electable continu ; OT: other transi Ave. Credit for E	aded vehicle we vehicle; TZEV U: warm-up cat trea/ammonia; er (active); GPF r/heated air-fue GR: exhaust g bulsed AIR; SFI C: charge air c T: hydrocarbon LPG: liquefied lockup); M: ma ously variable f mission; AER: xtended Warra	aight; ALVW: adju transitional ZEV; alyst; NAC: NOx NH3OC: ammonia PM filter for spa I ratio sensor; NC as recirculation; E /MFI: sequential/r ooler; FFH: fuel fit trap; BCAN: blee petroleum gas; E nual transmission; AM: all-electric range; nty: N = no credit	sted LVW; LEV: low e TWC/OC: 3-way/oxid adsorption catalyst; S a oxidation catalyst; C Irk-ignited engine; HO XS: NOx sensor; PM GRC: EGR cooler; AI multiport fuel injection; red heater; F/P/\$: full/ d carbon canister; pre 85: "85%" ethanol ("15 a; SA: semi-automatic automated manual tr EAER: equivalent AE s; Y = credits; S = crea	mission lizing ca CR-U or TOX/PT 2S/O2S S: PM se R/AIRE: partial/p fix 2: par fix 2: par 5%"gaso transmiss ansmiss R; PHE\	vehicle; talyst; OX: ensor; artial with rallel; (2) line) fuel; ssion; CV: ion; AMS:		
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD		
NISSAN	PATHFINDER 4WD PLATINUM	LDT2	3.5	CV1	LNSXR0120PBC	1	P		

AN S. Gam