

NISSAN MOTOR COMPANY, LTD.

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	FORMA	TION			
MODE	_	EST GROUP	VEHIC	LE CLASS(ES)			FUEL C	ATEGORY	FUEL TYPE	
2020	LN	ISXT05.6N9C		LDT4	1.1)12			SINGLE FUEL	GASOLINE	
1	USEFUL	LIFE (miles)	VEH	ICLE EMIS	SION C	ATEGO	RY	ERMEDIATE IN-USE STD		
EXH	/ORVR	EVAP		FTP		SFTP	FTP FTP		SFTP	
15	0000	150000	LEV3	ULEV125	LEV	LEV 3 COMPOSI		*	*	
SPE	CIAL FE	ATURES & EXI	HAUST EMISSIO	ON CONTRO	OL		OBD ST	TATUS	ENGINE DISPLACEMENT (L)	
1		2TWC (2) , 2HC	2S, 2WR-H02S	3, DFI		FL	FULL *			
*	*						RTIAL	ALL MODELS	5.6	
*			*				AL WITH	*		
		EV	APORATIVE &	REFUELING	G (EVA	P/ORVR	R) FAMILY	INFORMATION		
EVA	P / ORV	R FAMILY	EVAPORATIVE	E STD CATE	GORY	, E		SSION STD CLASS	SPECIAL FEATURES	
I	NSXR01	74PBA	L	EV 2 3			LD	T4	*	
				EMISSION C	REDIT	INFOR	MATION			
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ZEV NMOG CI		REDIT FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS	
		N		N		N			N	
			NMOG	AND FLEE	TAVE	RAGE IN	NFORMAT	ΓΙΟΝ		
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO	NMOG+NO PC+LDT		0 LVW) LDT (3		HOX FLEET STI 3751 LVW-8500 R) + MDPV (g/mi)	0 NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)	
*	*	1.10	*		0.065			0.074	*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



NISSAN MOTOR COMPANY, LTD.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby cancels and supersedes Executive Order A-015-0851 dated August 1, 2019.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of November 2019.

Allen Lyons, Chief missions Certification and Compliance Division



NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0851-1 New Passenger Cars, Light-Duty Trucks and **Medium-Duty Vehicles**

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

				G+NOx mi)		O mi)		Ox mi)		HCHO mg/mi)	Pl (g/r	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K		*	*	*	*	*	*	*	*	*	*	*
FTP@UL		OLINE- 3 E10	0.020	0.125	0.3	2.1	*	*	*	4	*	0.01
50°F @4K		OLINE- 3 E10	0.029	0.250	0.2	2.1	*	*	*	16	an Binn	
	1 page an				F		NN	IOG+NO	x (g/mi)	0	CO (g/mi)	
				FUEL TYP	E		CE	RT	STD	CERT		STD
HWFET @) 50K			*			*		*	distant.	a particular	
HWFET @	@ UL		GASC	LINE-LEV	73 E10		0.0	07	0.125	and the		
20°F @ 50K		COLD C	CO E10 REGULAR GASOLINE (TIER3)					Surger as	and the second second	0.9		12.5
			SFTP EXH	AUST EM	ISSION ST	TANDARD	S AND CE	RTIFICA	TION LE	VELS		
		1.00			US06			SC03		COMPOSITE		
F	UEL T	PE	NMOO	G+NOx	co	PM	NMOG	+NOx	co	NMOG+NOx	co	PM

	FUEL TYP	E	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/n		lOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	
@ 4K	*	CERT	*	*			*	*				
e		STD	*	*			*	*			1.1.1.1.1.1.1.1	
		CERT	*	*	* *		*	*	0.018	1.2	*	
(m)	GASOLINE LEV3 E10	I STO I	*	*	*		*	*	0.083	4.2	*	
		BIN							0.110	S. Start		
	٧	VHOLE VE	HICLE EVAPO	RATIVE E	MISSION S	STANDA	RDS AND	CERTIFIC	ATION LEVELS	5		
				WHOLE V	EHICLE E	VAPORA	TIVE TES	TING				
	ORATIVE	FUEL TY	PE 3DHS	6 (g/test) @	UL	20	HS (g/test) @ UL	RL	RL (g/mi) @ UL		
			CERT	STD	FEL	CERT	STD	FE	L CERT		STD	
LNSXR0174PBA		GASOLINE- LEV3 E10 0.49		0.90	*	*	1.15	* 0.000		0.05		
(ORVR / FUE	LONLY/	CANISTER BLE	ED EVAP	ORATIVE	EMISSIO	N STANDA	RDS AN	DCERTIFICATI	ON LEVE	LS	
						FUEL	ONLY EVA	P& CAN	ISTER BLEED			
FVAP	ORATIVE	ORVR (g/gallon) @ UL		3DHS PIG TEST 2DHS PIG TEST PI EED							

	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K	
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD
LNSXR0174PBA	GASOLINE- TIER3 E10	0.05	0.20	*	*	*	*	*	*	* .

AIR RESOURCES BOARD

NISSAN MOTOR COMPANY, LTD. Executive Order: A-015-0851-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

EFFECTIV	E LEAK DIAMETER STA	NDARD AND CERTIFICATION L	EVEL (INCHES)
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD
*	*	*	*
LDT<6000#GVWR,3751-5750 8500#ALVW; MDV: medium-o duty passenger vehicle; HDV: emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3: continuous/periodic trap oxidiz heated/oxygen sensor; WR-H RDQS: reductant quality sens EGRC: EGR cooler; AIR/AIRE fuel injection; DFI/IFI: direct/in full/partial/partial with fines on prefix 2: parallel; (2) suffix: se device (ex. DPF-SCRC: SCR ethanol ("15%"gasoline) fuel; -automatic transmission; CV: automated manual transmissi	0#LVW; LDT3: LDT 6001-850 heavy-duty vehicle; MDV4: MDV 850 heavy-duty vehicle; ECS: en vehicle weight rating; LVW: lo er ULEV; ZEV: zero-emission AC: HC adsorbing catalyst; W selective catalytic reduction- zer; DPF: diesel particulate fil 02S or AFS: wide range/linea or; NH3S: ammonia sensor; I direct fuel injection; TC/SC: t -board diagnostic; DOR: direct ries; a hyphen (-) between aff coated DPF); CNG/LNG: con E10: "10%" ethanol ("90%"ga continuously variable transmi on; AMS: automated manual- /: plug-in hybrid electric vehic	car; LDT: light-duty truck; LDT1: LDT- 10#GVWR,3751-5750#ALVW; LDT4: L 1-10000#GVWR; MDV5: MDV 10001 hission control system; CERT: certifica aded vehicle weight; ALVW: adjusted n vehicle; TZEV: transitional ZEV; TW /U: warm-up catalyst; NAC: NOx adso urea/ammonia; NH3OC: ammonia oxi ter (active); GPF: PM filter for spark-ig ar/heated air-fuel ratio sensor; NOXS: EGR: exhaust gas recirculation; HP/LF t driven)/(electric driven); PAIR: pulsed urbo/super charger; CAC: charge air of ct ozone reducing; HCT: hydrocarbon rer treatment ECS indicates multiple fun pressed/liquefied natural gas; LPG: li soline) fuel; A: automatic (with lockup) selectable transmission; OT: other tra de; NMOG + NOx Fleet Ave. Credit for	DT 6001-8500#GVWR,5751- -14000#GVWR; MDPV: medium- ation; STD: standard; FEL: family LVW; LEV: low emission vehicle; C/OC: 3-way/oxidizing catalyst; orption catalyst; SCR-U or dation catalyst; CTOX/PTOX: ynited engine; HO2S/O2S: NOx sensor; PMS: PM sensor; P EGR: High/Low Pressure EGR; d AIR; SFI/MFI: sequential/multipor cooler; FFH: fuel fired heater; F/P/\$ trap; BCAN: bleed carbon canister; unctionalities of the after treatment iquefied petroleum gas; E85: "85%"); M: manual transmission; SA: sen ariable transmission; AM: nsmission; AER: all-electric range;

:	2020 MODEL	YEAR: VE	HICLE M	ODELS INF	ORMATION		
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE	EXH ECS	OBD
INFINITI	QX80 2WD	LDT4	5.6	SA7	LNSXR0174PBA	1	P
NISSAN	ARMADA 2WD	LDT4	5.6	SA7	LNSXR0174PBA	1	P
NISSAN	ARMADA 4WD	LDT4	5.6	SA7	LNSXR0174PBA	1	P

2