

NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0856

New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

|  | •       |  |             | TEST GR                                      | OUP IN | FORMAT           | TION                          |   |                 |  |  |  |
|--|---------|--|-------------|--|--------|------------------|-------------------------------|---|-----------------|--|--|--|
| MODE                                   |         | EST GROUP                              | VEHIC       | VEHICLE CLASS(ES)                            |        |                  |                               | ATEGORY   |                 | FUEL TYPE  |  |  |
| 2020                                   | LN      | ISXD05.6W9A                            | MDV4        |  |        |                  | DEDICATED SINGLE FUEL VEHICLE |   |                 | GASOLINE   |  |  |
| - (                                    | USEFUL  | LIFE (miles)                           | VEH         | ICLE EMISS                                   | SION C | ATEGOR           | RY                            | INTERIM / INT                                     | ERMI            | EDIATE IN-USE STD  |  |  |
| EXH/ORVR EVAP                          |         |  |             | FTP SF                                       |        |                  | P FTP                         |   |                 | SFTP   |  |  |
| 150000 150000                          |         |  | LEV3        | SULEV170 LEV3 ULEV (CU USO6, SC03, TEST CYCL |        |                  | FTP                           | NMOG+NOX AND                                      | NMOG+NOX AND PM |  |  |  |
| SPE                                    | CIAL FE | EATURES & EXI                          | AUST EMISSI | ON CONTRO                                    | OL     |                  | OBD S                         | TATUS   | ENG             | GINE DISPLACEMENT  |  |  |
| 1                                      |         | 2TWC(2), 2HO                           | 2S, 2WR-HO2 | S, DFI                                       |        | FU               | FULL *                        |   |                 |  |  |  |
| *                                      |         | 2 10 10 10 10                          |             |  | PAR    | TIAL             | ALL MODELS                    |   | 5.6             |  |  |  |
|  | 15      |  | • 3003      |  |        | PARTIA<br>FIN    |                               | • •   |                 |  |  |  |
|  |         | EV                                     | APORATIVE & | REFUELING                                    | G (EVA | P/ORVR)          | FAMILY                        | INFORMATION                                       |                 |  |  |  |
| EVA                                    | P / ORV | R FAMILY                               | EVAPORATIV  |  |        | EV               | AP EMIS                       | SSION STD<br>E CLASS                              | SP              | ECIAL FEATURES   |  |  |
| I                                      | NSXF01  | 174PBB                                 | I           | LEV 2  |        |                  | MDV4                          |   |                 | *  |  |  |
|  |         |  |             | EMISSION C                                   | REDIT  | INFORM           | IATION                        |   |                 |  |  |  |
|  | EDIT FO | OX FLEET AVE.<br>OR EXTENDED<br>RRANTY |             | REDIT FOR I                                  |        | ZEV              | IMOG C                        | REDIT FOR DOR                                     |                 | OPTIONAL EXH. STD<br>FOR WORK TRUCKS                     |  |  |
|  |         | N                                      |             | N  |        |                  |                               | N   |                 | N  |  |  |
|  |         |  | NMOC        | AND FLEE                                     | TAVE   | RAGE IN          | FORMA                         | TION  |                 |  |  |  |
| NMOG CH4 NMOG/NMHC HCHO/NMHC LDT (3751 |         |  |             |  |        | 3500 GVW) MDV (8 |                               | OG+NOX FLEET STD<br>/ (8501-10000 GVWR)<br>(g/mi) |                 | NMOG+NOX FLEET STD<br>MDV (10,001-14,000<br>GVWR) (g/mi) |  |  |
| .*                                     | *       | 1.10                                   | *           |  | *      |                  | *                             |   |                 | *  |  |  |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0856

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

#### BE IT FURTHER RESOLVED:

The listed vehicle models are certified conditionally on the manufacturer providing evaporative emissions data with E10 certification gasoline as required by Part III.F.2 of the California Evaporative Emission Standards and Test Procedures for 2001 and Subsequent Model Motor Vehicles (Amended: September 2, 2015). This data must be submitted within 90 days from the date of this Conditional Executive Order as described in the manufacturer's request for Conditional Executive Order dated August 20, 2019.

Failure to provide the above data within the stipulated time, or failure of the data to be approved by the California Air Resources Board may be cause for the Executive Officer to rescind this conditional certification, in which case all vehicles covered under this conditional certification would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

OR VIOLET BRUCKS

Allen Lyons, Chief

**Emissions Certification and Compliance Division** 

day of September 2019.



UNLEADED

NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0856

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

# **ATTACHMENT**

|                    |          |              |                    |   |                                   |                                  | IIA                               | IIIVII                     | -141                           | Mark State  |                                       |                            | Sec. 1                         | 1 4                                    | A                              |  |  |
|--------------------|----------|--------------|--------------------|---|-----------------------------------|----------------------------------|-----------------------------------|----------------------------|--------------------------------|---|---------------------------------------|----------------------------|--------------------------------|--|--------------------------------|--|--|
| = 11               |          | -            |                    |   |                                   |                                  |                                   | -                          |                                | DS AND  |                                       |                            |                                |  | 3                              |  |  |
|                    | 500      | EXHA         |                    |   |                                   |                                  |                                   |                            |                                | LEVELS (  |                                       |                            |                                |  |                                |  |  |
|                    | FUE      | L TYP        | mor<br>adju<br>ORV | oxide; National indicates the contract of the | IOx: oxid<br>actor; 20<br>/gallon | es of nitr<br>HS/3DH<br>lispense | rogen; H<br>IS [g HC<br>d]: on-bo | CHO:<br>/test]:<br>pard re | formato<br>2/3 day<br>fueling  | hydrocari<br>dehyde; Pl<br>vs diurnal-<br>vapor rec<br>st procedu | M: particul<br>hot-soak<br>covery; g: | late m<br>; RL [g<br>gram; | natter; Rag HC/mi]<br>mg: mill | AF: reacti<br>: running l<br>igram; mi | vity<br>loss;                  |  |  |
|                    |          |              |                    | NMOG+   | all that the same                 | (                                | CO<br>g/mi)                       |                            |                                | lOx<br>J/mi)  |                                       | HCHC<br>mg/m               |                                |  | M<br>mi)                       |  |  |
|                    |          |              | CI                 | ERT   | STD                               | CERT                             | ST                                | D                          | CERT                           | STD   | CER                                   | т                          | STD                            | CERT                                   | STD                            |  |  |
| TP@50              | K        | *            |                    | *   | *                                 | *                                |                                   |                            | *                              | *   | N V                                   | 4                          | *                              | *                                      | *                              |  |  |
| FTP@U              |          | LINE<br>3 E1 | 1 0                | 060   | 0.170                             | 0.4                              | 4.                                | 2                          | *                              | *   |                                       | V                          | 6                              | 0.005                                  | 0.008                          |  |  |
| 50°F @4            | ıĸ       | *            | 100                | *   | *                                 | *                                | *                                 |                            | *                              |   |                                       |                            | *                              | S. F. You                              | A 101.10                       |  |  |
|                    | 5 0 1000 |              |                    |   | IEL TVD                           | -                                |                                   | 16 30 17                   | N                              | MOG+NC  | x (g/mi)                              |                            |                                | CO (g/mi                               | )                              |  |  |
| and the second     |          | W.           |                    | FUEL TYPE   |                                   |                                  |                                   |                            | CERT                           |   | STD                                   |                            | CERT                           |  | STD                            |  |  |
| HWFET @ 50K        |          | . 9 9        |                    |   |                                   |                                  |                                   |                            | •                              | *   |                                       |                            | 是於中華                           | -As records                            |                                |  |  |
| HWFET @ UL         |          | en 17/4   P  | GASOLINE-LEV3 E10  |   |                                   |                                  | 0                                 | 0.027                      |                                | 0.170   |                                       |                            |                                |  |                                |  |  |
| 20°F (             | @ 50K    | 1            |                    | est for   | *                                 |                                  | 0                                 |                            | 9                              | 2000年   |                                       |                            |                                |  | *                              |  |  |
|                    | 100      |              | SFT                | PEXHA   | UST EM                            | ISSION                           | STAND                             | ARDS                       | AND C                          | ERTIFIC   | ATION LI                              | VELS                       | S                              |  |                                |  |  |
|                    |          | US06         |                    |   |                                   |                                  | SC                                |                            |                                | SC03  |                                       |                            | co                             | COMPOSITE                              |                                |  |  |
|                    | FUEL TY  | L TYPE       |                    | NMOG+NOx<br>(g/mi)  |                                   | CO PN<br>(g/mi) (mg/             |                                   |                            |                                |   | CO Ni<br>(g/mi)                       |                            | G+NOx<br>g/mi)                 | CO<br>(g/mi)                           | PM<br>(mg/mi                   |  |  |
| @ 4K               | *        | * CERT       |                    |   |                                   |                                  |                                   |                            |                                |   |                                       |                            | 3.10                           |  |                                |  |  |
|                    |          |              |                    | *   |                                   | *                                |                                   | 945                        |                                | *   | *                                     |                            |                                |  |                                |  |  |
|                    |          | CE           |                    | *   |                                   | *                                |                                   | *                          | *                              |   | *                                     | 0.046                      |                                | 5.9                                    | 6                              |  |  |
| @ UL               | GASOLII  | 1 8 1 11 1   |                    | *   |                                   | *                                |                                   | *                          |                                | *   | *                                     | 0.450                      |                                | 12.0                                   | 10                             |  |  |
|                    |          |              |                    |   |                                   |                                  |                                   |                            |                                |   | operation of the                      |                            | . *                            | 177.03.00                              |                                |  |  |
|                    |          | WHO          | OLE VEH            | ICLE E  | VAPORA                            | TIVE E                           | MISSION                           | STA                        | NDAR                           | S AND C   | ERTIFIC                               | ATIO                       | I LEVEL                        | S                                      |                                |  |  |
|                    |          |              |                    |   | W                                 | HOLE V                           | EHICLE                            | EVAP                       | ORAT                           | IVE TEST  | ING                                   | FIN                        |                                |  |                                |  |  |
| EVAPORATIVE FAMILY |          | FUEL TYPE    |                    | E   | 3DHS (g/test) @ UL                |                                  |                                   |                            | 2DHS (g/test)                  |   | @ UL                                  |                            | RI                             | _ (g/mi) @                             | (g/mi) @ UL                    |  |  |
|                    |          |              |                    | CERT S  |                                   | STD                              | TD FEL                            |                            | CERT STD                       |   | FEL                                   |                            | CER                            | T                                      | STD                            |  |  |
| LNSXF0174PBB       |          | 1            | SOLINE<br>PHASE    | 1 0   | 44 1                              | .00                              | *                                 | 0.                         | 39                             | 1.25  |                                       | *                          |                                | 0.000 0.0                              |                                |  |  |
| 0                  | RVR / FL | IEL O        | NLY / C            | ANISTE  | R BLEE                            | EVAPO                            | DRATIV                            | E EMIS                     | SSION                          | STANDA  | RDS AND                               | CER                        | TIFICAT                        | TION LEV                               | ELS                            |  |  |
|                    |          |              |                    |   |                                   |                                  |                                   |                            | UEL ONLY EVAP & CANISTE        |   |                                       |                            |                                |  |                                |  |  |
|                    | ORATIVE  | ORVR (g/g    |                    | g/gallon) @ UL  |                                   | FUEL                             | FUEL TYPE                         |                            | 3DHS RIG TEST<br>(g/test) @ UL |   | 2DHS RIG T<br>(g/test) @              |                            |                                |  | ED CANISTER<br>T (g/test) @ 4K |  |  |
|                    |          | FUI          | EL TYPE            | CERT  | STD                               |                                  |                                   | CE                         | RT                             | STD   | CERT                                  |                            | STD                            | CERT                                   | STD                            |  |  |
| LNSXF0174PBB       |          | T            | OLINE -            | 0.08  | 0.20                              | *                                |                                   |                            | * *                            |   | *                                     |                            | *                              | *                                      | *                              |  |  |



NISSAN MOTOR COMPANY, LTD. Executive Order: A-015-0856

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

| EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES) |                        |      |     |  |  |  |  |  |
|---|------------------------|------|-----|--|--|--|--|--|
| EVAPORATIVE FAMILY  | LEAK FAMILY            | CERT | STD |  |  |  |  |  |
|   | PARTIE ATTO PORT AND A |      |     |  |  |  |  |  |

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3; LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection: DFI/IFI: direct/indirect fuel injection: TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic: DOR; direct ozone reducing; HCT; hydrocarbon trap; BCAN; bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2020 MODEL YEAR: VEHICLE MODELS INFORMATION

| MAKE   | MODEL                   | VEH CLASS | ENGINE (L) | TRANS TYPE | EVAPORATIVE FAMILY | ECS | OBD |
|--------|-------------------------|-----------|------------|------------|--------------------|-----|-----|
| NISSAN | NV2500 CARGO VAN        | MDV4      | 5.6        | SA7        | LNSXF0174PBB       | 10  | P   |
| NISSAN | NV3500 CARGO VAN        | MDV4      | 5.6        | SA7        | LNSXF0174PBB       | 1   | P   |
| NISSAN | NV3500 PASSENGER<br>VAN | MDV4      | 5.6        | SA7        | LNSXF0174PBB       | 1   | P   |