

Executive Order: A-021-0718

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	FORMA	TION					
MODE		EST GROUP	VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
2020	LO	CEXD06.78VV		MDV4				SINGLE FUEL HICLE	DIESEL			
	USEFU	L LIFE (miles)	VEH	IICLE EMIS	SION	ATEGO	RY	INTERIM / INT	ERMI	EDIATE IN-USE STD		
EXH/ORVR EVAP				FTP				FTP		SFTP		
150000 *			LEV3	ULEV200 LEV3 ULEV (FU US06, SC03, F TEST CYCLE)			, FTP	NMHC+NOX AND	PM	PM NMHC+NOX AND PM		
SPE	CIAL FI		HAUST EMISSISTEMS	ON CONTRO	DL		OBD S	TATUS	ENG	GINE DISPLACEMENT (L)		
1 T	C, CAC		EGRC, OC+DPF NOXS(2), PMS		30C,	FU	LL	*				
*			*			PAR	TIAL	*	6.7			
*			*				L WITH	ALL MODELS				
	-	E	APORATIVE &	REFUELING	G (EVA	P/ORVR) FAMILY	INFORMATION	_			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY						VEHICLE CLASS			SP	SPECIAL FEATURES		
	*			*				*	*			
				EMISSION C	REDIT	INFORM	MATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON-P							NMOG CI	REDIT FOR DOR		OPTIONAL EXH. STD FOR WORK TRUCKS		
N N							N			N		
			NMOG	AND FLEE	TAVE	RAGE IN	FORMA	TION				
MOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO	HCHO/NMHC RATIO	TOHO/NMHO DT /3754 VAL 95				3+NOX FLEET STD 3501-10000 GVWR) (g/ml)		NMOG+NOX FLEET ST MDV (10,001-14,000 GVWR) (g/ml)		
*	*	*	*	* *				*		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-021-0718

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles
Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the listed vehicle models has been determined to have ten deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of \$375 per vehicle for the third through tenth deficiencies for vehicles in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the California Air Resources Board (CARB) reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall also be subject to enhanced manufacturer in-use verification testing requirements as described in the CARB letter CLC-2019-079.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______day of November 2019.

Allen Lyons, Chief

Emissions Certification and Compliance Division



Executive Order: A-021-0718

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

							A	ITAC	ואורוי								
	EXHA	UST	AND	EVA	POF	VITAS	E EMIS	SION	STAI	NDAR	DS ANI	CERT	IFICATIO	N LEV	ELS		
		EXH	AUST	EMISS	ION S	TAND	ARDS A	ND CER	TIFIC	ATION	LEVELS	(FTP, HV	/FET, 50°F,	20°F)			
	FUE	L TY	r a	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP													
					MHC+NOx (g/mi)		CO (g/mi)			NOx (g/ml)			HCHO (mg/mi)		PM (g/mi)		
				CER	Г	STD	CERT	ST	D	CERT	STD	CER	T STD	CE	RT	STD	
FTP@5	ок	*		*		*	*	*		*	*	*	*	,		*	
FTP@l	JL DIES	EL-I	EPA	0.13	1 (0.200	0.27	4.	2	*	*	*	6	0.0	007	0.008	
50°F @	F @4K *		*		*	*	*		*	*	*	*	1		4- 3		
19.0				FUEL TYPE					NMHC+NOx (g/mi)				CO (g/mi)				
	UF				FU	EL IYE	E			CERT		STD	CE	RT	STD		
HWFET @ 50K *										*	*		Al-W				
HWFE	HWFET @ UL				DIESEL-EPA					0.	0154	0.200					
20°F	20°F @ 50K *								1			X 13	* *				
			S	FTP E	XHA	JST EN	ISSION	STAND	ARDS	AND C	ERTIFIC	ATION L	EVELS				
			3		US06					SC03 COMPOSITE							
	FUEL T	YPE		NMHC+NOx (g/mi)		CO (g/mi)		PM (mg/mi)		NMHC+NOx (g/mi)		NMHC+No (g/mi)		CO J/mi)	PM (mg/mi)		
@ 4K	*	, CE			*		*	*		*		*					
e			STD		*		*		II, I'a		*	*					
		(*		*		*		*	*	0.0755	0	.10	1.1	
@ UL	DIESEL-	ESEL-EPA STD BIN			*		*		*		*	*	0.800	2	2.0	10	
					0		1		File				*				
		WH	OLE V	EHIC	E EV	APORA	TIVE E	MISSION	N STA	NDARD	S AND	ERTIFIC	ATION LEV	ELS			
						W	HOLE V	EHICLE	EVAF	PORAT	VE TEST	ING					
EVAPORATIVE FUEL TYPE				YPE	PE 3DHS (g/test) @ UL					2DHS (g/test) @ UL				RL (g/mi) @ UL			
					CEF	CERT STD		FEL	FEL CE		STD	FEI	L CI	ERT		STD	
* *					*		*	*	,	k	*	*		*		*	
(DRVR / FI	JEL (ONLY /	CANI	STER	BLEE	EVAP	ORATIV	E EMI	SSION	STANDA	RDS AND	CERTIFIC	ATION	LEVE	LS	
													ISTER BLE				
EVAPORATIVE FAMILY		ORVR (g		(g/gal	g/gallon) @ UL		FUEL TYPE			DHS RIG TEST (g/test) @ UL			RIG TEST st) @ UL			CANISTER /test) @ 4K	
		FUEL 1		PE C	ERT STD		1		-	RT	STD	CERT		CEF		STD	
	*		*		*	*		*		*	*	*	*	*		*	
		EFF	ECTIV	E LE	AK D	IAME	ER ST	ANDAF	RD AN	ID CE	RTIFICA	TION LE	VEL (INC	IES)			
EVA	PORATIV	E FA	MILY		LEA	K FAM	LY			CER	T			STD			
						+								*			



Executive Order: A-021-0718

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC; SCR coated DPF); CNG/LNG; compressed/liquefied natural gas; LPG; liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits. Y = credits. S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	ECS	OBD
RAM	RAM 2500 4X2	MDV4	6.7	. A6	*	1	\$
RAM	RAM 2500 4X4	MDV4	6.7	A6	*	1	\$