

MAZDA MOTOR CORPORATION

Executive Order: A-016-0463 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
MOD	ı T	EST GROUP	HICLE CLAS	LE CLASS(ES)			FUEL C	ATEGORY	2	FUEL TYPE				
202	0 1.7	LTKXV01.5FFA PC						1		SINGLE FUEL HICLE	124	GASOLINE		
USEFUL LIFE (miles) VEHICLE E							ON C	ATEC	ORY	INTERIM / IN	MEDIATE IN-USE STD			
EX	H/ORVR	EVAP			FTP SF			TP	FTP		SFTP			
150000 150000				LE	V3 ULEV12	ULEV125 LEV 3 COMPC			MPOSITE	PM		PM		
SP	SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS		ENGINE DISPLACEMENT (L)		
1	7	WU-TWC, TWC,	WR	-HO2S,	HO2S, DFI				FULL	ALL MODELS				
*	* *							Р	ARTIAL	*		1.5		
*	* *							2 2 22.2	RTIAL WITH *					
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						ORY		EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
LTKXR0107GBK LEV					LEV 2				I	PC		*		
					EMISSIO	N CF	REDIT	INFO	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR ZERO-E							I NMOG CREDIT			REDIT FOR DO	OR DOR OPTIONAL EXH.			
N N								N				N		
NMOG AND FLEET AVERAGE INFORMATION														
NMO0 RAF	DAE RAE NMOG/NMHC RATIO PC+LDT				DT (V) LDT	NMOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*		0.065				0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



MAZDA MOTOR CORPORATION

Executive Order: A-016-0463

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

8 day of June 2019.

Allen Lyons, Chief

Emissions Compliance, Automotive Regulations and Science Division



GASOLINE-TIER3 E10

0.08

0.20

LTKXR0107GBK

MAZDA MOTOR CORPORATION

Executive Order: A-016-0463

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			Mark Company Company			-					FTP, HWI	- Surdings-			LS	nya na andarah dajan
		TYPE	CH4: mond adjust ORV	methan oxide; No stment fa R [g HC	e; NMO Ox: oxid octor; 2D /gallon o	G: non-Ces of nitred HS/3DH	CH4 orga ogen; H0 S [g HC/ d]: on-bo	nic gas CHO: fo test]: 2 ard ref	s; HC: ormal /3 da ueling	hydrocari dehyde; P ys diurnal- g vapor red	oon; NMH M: particul hot-soak; covery; g: g ure; SFTP	C: no ate n RL [g	n-CH4 I natter; F g HC/mi ; mg: mi	HC; CC AF: rea]: runni lligram;	activ	ity ss;
			N	NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		1	HCH((4)(4)(4)		P M (g/mi)	
				RT	STD	CERT	STE) (ERT	STD	CERT		STD	CERT		STD
TP@50	ĸ	*		k	*	*	*		*	*	*		*	* *		*
FTP@U	GASOLINE- LEV3 E10		0.0	079 (.125	0.3	2.1		*	*	*		4	0.001		0.003
50°F @4	K	*		*	*	*	*				*		*			
				FUEL TYPE					NMOG+NOx (g/mi)				CO (g			
									С	ERT	STD		CERT		STD	
HWFET	@ 50K				*					*	*					
HWFET @ UL			GASOLINE-LEV3 E10					0	.063	063 0.125						
20°F @ 50K COLD CO E			CO E	E10 REGULAR GASOLINE (TIER3)					in i		terminal and the engineering		0.5			10.0
			SFT	EXHA	JST EM	ISSION	STANDA	RDS	AND	CERTIFIC	ATION LE	VEL	s			
				US06					SC03				COMPOSITE			
	FUEL TYPE		(PE N		NMOG+NOx (g/mi)		CO PM (g/mi) (mg/mi		NMOG+NOx (g/mi)		CO (g/mi)	NMOG+NO (g/mi)			O mi)	PM (mg/mi
@ 4K	*	* CERT		*		*	*		*		*					
				*		*			*		*				14	
		CE		RT *		* 2			*		*	0.085		1	. 1	*
@ UL	GASOLIN LEV3 E	1.5			i	* *		*	0.083		4	4.2				
		BIN										0	.120	1.0		
		WHOL	E VEHI	ICLE EV						DS AND O	ERTIFICA	OITA	N LEVE	LS		
EVAPORATIVE FUEL		L TYPE	<u> </u>		(test) @ UL			2DHS (g/test) @ UL			R		RL (g/mi) @ UL			
			, ,		STD	D FEL		ERT ST		FEL	L CE		RT ST		STD	
T TO		OLINE-	1 0 38 1 0		.50	* *		0.65		*	0.0		0.05			
C	RVR / FU				BLEED	EVAPO	RATIVE	EMIS	SION	STANDA	RDS AND	CEF	RTIFICA	TION	EVE	LS
								FU	IEL C	NLY EVA	P & CANI	STEF	RBLEE	D		
EVAPORATIVE FAMILY		OR	VR (g/g	gallon) (@ UL	FUEL	FUEL TYPE			DHS RIG TEST (g/test) @ UL		2DHS RIG T (g/test) @				
		FUEL	TYPE	CERT	STD	10 00000000000000000000000000000000000		CE	RT	STD	CERT	T	STD	CER	тΙ	STD
		I. OLL						100,000		350.0.50	E == 0 0 1				•	



MAZDA MOTOR CORPORATION

Executive Order: A-016-0463

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
* 13 - 2 2 2 2 2										

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

	2020 MODEL	YEAR: VE	HICLE M	ODELS INF	ORMATION		
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MAZDA	MAZDA2	PC	1.5	SA6	LTKXR0107GBK	1	F
MAZDA	MAZDA2	PC	1.5	М6	LTKXR0107GBK	1	F