

MAZDA MOTOR CORPORATION

Executive Order: A-016-0465

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				-	TEST GRO	UP IN	IFOR	MATION					
MOD	ı T	EST GROUP	T	VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE			
202	2020 LTKXV02.5FFA PC						PC DEDICA				GASOLINE		
	USEFU	LIFE (miles)		VEH	VEHICLE EMISSION CATEGORY				INTERIM / IN	TER	RMEDIATE IN-USE STD		
EX	H/ORVR	EVAP		FTP S			ΓP FTP			SFTP			
1	50000	15000	LEV3	ULEV125 LEV 3 COM			MPOSITE	*		*			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD STATUS			ENGINE DISPLACEMENT (L)		
1 WU-TWC, TWC, WR-HO2S, HO2S, DFI, CAC, TC, EGR, EGRC								FULL	ALL MODELS				
*			*			P	ARTIAL	*		2.5			
* *								PARTIAL WITH *					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
	LTKXR0	L20GAK		L	EV 2		PC				*		
				E	EMISSION C	REDI	r INF	ORMATION	and the second s				
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON- ZERO-EVAP							N-PZEV NMOG CREDIT FOR DOR			R	OPTIONAL EXH. STD FOR WORK TRUCKS		
и									И	И			
NMOG AND FLEET AVERAGE INFORMATION													
NMO0 RAF						0-375					IMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0.065 0.07						*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



MAZDA MOTOR CORPORATION

Executive Order: A-016-0465

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BF IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

_ day of August 2019.

Allen Lyons, Chief

Emissions Certification and Compliance Division



GASOLINE-TIER3 E10

0.00

0.20

LTKXR0120GAK

MAZDA MOTOR CORPORATION

Executive Order: A-016-0465 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

								A ⁻	TTAC	НМІ	ENT							
	E	KHAU	ST	AND	EV	APOR	ATIVE	EMIS	SION S	TAN	IDAR	DS AND	CERTI	FICA	ATION	LEVE	LS	
		E	XHA	UST E	MIS	SION S	TANDA	RDS AI	ND CERT	TFICA	TION	LEVELS	(FTP, HWI	ET,	50°F, 2	0°F)		
		FUEL TYPE		m ac O	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP													
					NI	MOG+N (g/mi)	Ox	CO (g/mi)				NOx g/mi)		HCH(PN (g/n	
	64			-	CEF		STD	CERT		,	CERT	STD	CERT		STD			STD
FTP@5	0K	-	*		*		*	*	*		*	*	*		*	*		*
FTP@L	JL	GASOI LEV3		- 1	0.0	52 0	.125	0.3	2.1		*	*	*		4	*	* 0	
50°F @4	4K		ASOLINE- LEV3 E10		0.0	31 0	.250	0.3	2.1		*	*	*		16		o Alexandro de Saladorio de la Companya de la Comp La Companya de la Companya de	
						FUE	EL TYPI	Ξ			NMOG+NOx (g/mi)			_	CO (g/mi)			
								_		С	CERT S		MANUFACTURE OF THE TOTAL PROPERTY.		RT	range of the second		
HWFET @ 50K				*						* *				A CONTRACTOR OF THE CONTRACTOR			All productions of the second	
HWFE	HWFET @ UL				G	ASOLIN	IE-LEV	3 E10		0.032		0.125	0.125					
20°F	@ 5	0K	CO						E (TIER						0.	5		10.0
				S	FTP	EXHAU			STANDA	RDS	AND		ATION LE	VEL		24000		
	E11	UEL TYPE			NMOG+NOx			US06 CO PM			NMOG+NOx (g/mi)		СО	NMOG+NO			MPOSITE	
	FUELTYPE						(g/mi) (mg/mi		0.00	(g/mi)						mi)	PM (mg/mi)	
@ 4K		*		CERT		*		*				*	*					
0				STD		*		*				*	*	7 (1) W/2 (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)		V. Apr		
		CA COT TATE		SID				* *			*		*	0.065		2	. 0	*
@ UL										•		*	* (.083	4	. 2	*
	ВІ		BIN									0.120						
			WH	OLE V	EHIC	CLE EV							ERTIFICA	OITA	N LEVE	LS		
EVAP	EVAPORATIVE			IIEI T	VDE	3		HOLE VEHICLE EVAP			2DHS (g/test) @ UL			RL		RL (g/m	i) @	UL
FAMI		.Υ	FUEL TYPE			,,,		/test) @ UL						CE	CERT		STD	
LTKXR0120GAK		1		SOLINE- EV3 E10		0.29 0.50		FEL *			0.65 *		0.00					
	DRV	R / FUI	_	-	-	VISTER	BLEED	EVAP	ORATIVE	EMIS	SSION	STANDA	RDS AND	CEF	RTIFICA	TION L	EVE	LS
													P & CANI					
EVAP FA	OR/			ORVR	R (g/gallon) @ UL				FUEL TYPE			G TEST @ UL					BLEED CANISTER TEST (g/test) @ 4K	
			FUEL T		PE	CERT	ERT STD				RT	STD	CERT		STD	CER	Г	STD



MAZDA MOTOR CORPORATION

Executive Order: A-016-0465

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
*	*	*	*							

t: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SRC coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	
MAZDA	MAZDA6	PC	2.5	SA6	LTKXR0120GAK	1	F	