

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	FOR	ATION			-		
MODE		ST GROUP		VEHICL	E CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE		
202	D LP	RXV03.0PV6			PC		DEDICATED SINGLE FUEL VEHICLE				GASOLINE		
	USEFUL	LIFE (miles)		VEH	ICLE EMISS	ION C	ATEC	GORY	INTERIM / IN	TER	MEDIATE IN-USE STD		
EXH/ORVR EVAP				1000	FTP		SF	TP	FTP		SFTP		
150000 150000				LEV3	V3 ULEV70 LEV 3 C			OMPOSITE *			*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	OBD STATUS		ENGINE DISPLACEMEN (L)		
1 2TWC, 2WR-HO2S, 2HO2S, DFI, 2TC, 2CAC								FULL	*				
2 TWC, WR-HO2S, HO2S, DFI, TC, CAC								ARTIAL	ALL MODELS	2011	2.9, 3.0		
* *								TIAL WITH FINES	* '	1. (1. (1. (1. (1. (1. (1. (1. (1. (1. (			
		E١	APO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	Y INFORMATIC	N			
EV	AP / ORV	R FAMILY	EVA	PORATIVE	STD CATE	GORY	RY EVAP EMISSION STD VEHICLE CLASS				SPECIAL FEATURES		
	LPRXR01	90RP7	EV 3 OPTION2 WITH FEL				]	2C		*			
				E	EMISSION C	REDIT	INFO	ORMATION					
	REDIT FO	X FLEET AVE. REXTENDED RRANTY			EDIT FOR N ZERO-EVAP		ZEV	NMOG CREDIT FOR DO			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N		N N						
				NMOG	AND FLEE	T AVE	RAG	E INFORMA	TION				
NMOC RAF	CH4 RAF	FTP NMOG/NMHC RATIO		HO/NMHC RATIO	PC+LDL (0-37501			2017 To 10 The second sec			NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		0.01	C	0.065			0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this  $2^{NP}$  day of October 2019.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

DR. ING H.C.F. PORSCHE AKTIENGESELLSCHAFT

Executive Order: A-019-0270 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

# **ATTACHMENT**

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/i		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K *		* *		*	*	*	*	*	*	*	*	*
FTP@UL	TIER	LINE- 3 E10 REM	0.038	0.070	0.5	1.7	*	*	0	4	0.000	0.003
50°F @4K		*	*	*	*	*	*	*	*	*		行和關係以
							N	MOG+NOx	(g/mi)		CO (g/mi	)
				FUEL TYP	'E		CE	RT	STD	CEF	रा	STD
HWFET @	9 50K			*				*	*			情况的社会
HWFET (	@ UL		GASOLIN	E-TIER3	E10 PREM	4	0.0	012	0.070			N AND N I
20°F @	50K		GASOLIN	E-TIER3	E10 PREN	4				0.6		10.0
			SFTP EXH	AUST EN	ISSION S	TANDAR	DS AND C	ERTIFICA	TION LEVE	ELS		

## SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			US06							SC03		COMPOSITE				
	FUEL TYF	PE	NN	lOG+N (g/mi)		CO (g/mi)	PN (mg/	-		)G+NOx g/mi)	CO (g/mi)		OG+NO> (g/mi)	c C (g/i	-	PM (mg/mi)
@ 4K	*	CERT		*		*				*	*					
U		STD	*			*			*		*				湖道	
		CERT		*		*	1			*	*	(	0.024	0.	8	*
@ UL	GASOLINE TIER3 E1 PREM			*		*	6			*	*		0.083	4	2	*
		BIN	の作為			n sa an taon Ann an tao	ina ana ana ana ana ana ana ana ana ana						0.080			A grand of the state
		WHOLE VE	HIC	LE EVA	APORA	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFIC	ATIO	N LEVE	LS		
					WH	IOLE \	/EHICLE I	EVAP	ORAI	IVE TEST	ING					
		FUEL TY	ΈE	3	DHS (g/	/test) @	D UL		2DH	IS (g/test)	@ UL		R	L (g/m	)@	UL
				CER	TS	TD	FEL	CEI	RT	STD	FEL	-	CEF	RT		STD
LPRXR0190RP7		GASOLIN TIER3 H PREM	E10	0.21	L8 0.	300	0.300	0.2	13	0.300	0.30	0.300		01	0.05	
(	ORVR / FUE	LONLY /	CAN	ISTER	BLEED	EVAP	ORATIVE	EMIS	SSION	STANDA	RDS AND	CE	RTIFICA	TION L	EVE	LS
								FU	JEL C	NLY EVA	P & CAN	ISTE	R BLEE	D		
	ORATIVE	ORVR	(g/ga	'gallon) @ UL		FUE				IG TEST ) @ UL	2DHS (g/te		TEST			NISTER st) @ 4K
		FUEL TYP	ΡE	CERT	STD	1		CE	RT	STD	CERT	CERT		CER	RT STD	
LPRX	R0190RP7	GASOLINE TIER3 E1	-	0.03	0.20		OLINE- R3 E10		*	*	*		*	0.00	5	0.020

PREM

PREM

	JURCES BOARD	AKTI	DR. ING H.C.F. PORSCHE ENGESELLSCHAFT		Executive Order: A-019-0270 ssenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4
EFFECTI	VE LEAK DIAMETER	STA	NDARD AND CER	TIFICATION L	EVEL (INCHES)
EVAPORATIVE FAMILY	LEAK FAMILY		CERT	Г	STD
LPRXR0190RP7	LPRXR0190RP7-00	1	*		0.02
LDT<6000#GVWR,3751-578 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: su ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxid heated/oxygen sensor; WR-H RDQS: reductant quality sen EGRC: EGR cooler; AIR/AIR fuel injection; DFI/IFI: direct/i full/partial/partial with fines o prefix 2: parallel; (2) suffix: su device (ex. DPF-SCRC: SCF ethanol ("15%"gasoline) fuel -automatic transmission; CV automated manual transmission	60#LVW; LDT3: LDT 600 duty vehicle; MDV4: MDV ': heavy-duty vehicle; EC vehicle weight rating; LV per ULEV; ZEV: zero-em HAC: HC adsorbing cataly : selective catalytic reduc izer; DPF: diesel particula HO2S or AFS: wide range sor; NH3S: ammonia sen E: secondary air injection ndirect fuel injection; TC/ n-board diagnostic; DOR: eries; a hyphen (-) betwee coated DPF); CNG/LNG E10: "10%" ethanol ("90 continuously variable tra- ion; AMS: automated ma V: plug-in hybrid electric	1-850 V 850 S: em W: lo nissior yst; W ction-l ate filt e/linea nsor; I con 'SC: to 'SC: to 'S	0#GVWR,3751-5750 01-10000#GVWR; MI nission control system aded vehicle weight; n vehicle; TZEV: trans VU: warm-up catalyst urea/ammonia; NH30 ter (active); GPF: PM ar/heated air-fuel ratio EGR: exhaust gas rea t driven)/(electric driv urbo/super charger; 0 ct ozone reducing; H0 ter treatment ECS inco npressed/liquefied na soline) fuel; A: autom ssion; SCV: selectab selectable transmissi	#ALVW; LDT4: DV5: MDV 1000 n; CERT: certific ALVW: adjusted sitional ZEV; TV ; NAC: NOX ads DC: ammonia ox filter for spark-io sensor; NOXS circulation; HP/L en); PAIR: pulse CAC: charge air CT: hydrocarbor licates multiple f tural gas; LPG: natic (with lockup le continuously ion; OT: other tra-	cidation catalyst; CTOX/PTOX: gnited engine; HO2S/O2S: : NOx sensor; PMS: PM sensor; P EGR: High/Low Pressure EGR; ed AIR; SFI/MFI: sequential/multiport cooler; FFH: fuel fired heater; F/P/\$: n trap; BCAN: bleed carbon canister; functionalities of the after treatment liquefied petroleum gas; E85: "85%" p); M: manual transmission; SA: semi

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	0
PORSCHE	PANAMERA	PC	3.0	AMS8	LPRXR0190RP7	2	I
PORSCHE	PANAMERA 4	PC	3.0	AMS8	LPRXR0190RP7	2	I
PORSCHE	PANAMERA 4 EXECUTIVE	PC	3.0	AMS 8	LPRXR0190RP7	2	I
PORSCHE	PANAMERA 4 SPORT TURISMO	PC	3.0	AMS 8	LPRXR0190RP7	2	I
PORSCHE	PANAMERA 4S	PC	2.9	AMS8	LPRXR0190RP7	1	I
PORSCHE	PANAMERA 4S EXECUTIVE	PC	2.9	AMS8	LPRXR0190RP7	1	I
PORSCHE	PANAMERA 4S SPORT TURISMO	PC	2.9	AMS 8	LPRXR0190RP7	1	I