

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

			99.9 207.999 diken forgerangelander og gigterations	TEST GF		FORMAT	ION		2 . 2				
MODE	- I TI	TEST GROUP VEHICL			(ES)	FUEL CATEGORY				FUEL TYPE			
2020	LP	RXV04.0PH8		PC I			IN HYBRID IC VEHICLE		GASOLINE				
	USEFUL	LIFE (miles)	VEH	ICLE EMIS	CLE EMISSION CATEGORY INTERIM / IN				ITERI	TERMEDIATE IN-USE STD			
EXH/ORVR EVAP				FTP		SFTP				SFTP			
15	0000	150000	LEV3	ULEV125	LEV	3 COMPC	SITE	*		*			
SPE	CIAL FE		HAUST EMISSIO	ON CONTR	OL		OBD S	STATUS	EI	NGINE DISPLACEMENT (L)			
1 2TWC, 2HO2S(2), DFI, 2TC, 2CAC							FULL *						
*			*			PART	TIAL	ALL MODELS	4.0				
*		1	*			PARTIA		×					
		E\	APORATIVE &	REFUELIN	G (EVA	P/ORVR)	FAMIL	Y INFORMATIO	N				
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGO						EVAP EMISSION STD				SPECIAL FEATURES			
I	PRXR01	70RPH	LEV 3	OPTION2	ON2 PC			*					
				EMISSION	CREDIT	INFORM	ATION						
ALL	GR	E FOR TEST DUP EV	(FLEET IT FOR ARRANTY		G CREDIT FOR N-PZEV ZERO- . EVAP DOR			FOR	FOR OPTIONAL EXH. STD FOR WORK TRUCKS				
		*	N		N N				N				
			NMOG	AND FLE	ET AVE	RAGE IN	FORMA	TION					
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO	NMOG+N PC+LDT			NMOG+NOX FLEET ST LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		0	D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10	0.01		0.065			0.074		*			
See the	e Attach	ment for Vehic	le Models Eva	anorative F	amily	Engine D	isplace	ement Emissio	n Co	ntrol Systems Phase-			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2131 day of January 2020.

Allen Eyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

DR. ING H.C.F. PORSCHE AKTIENGESELLSCHAFT Executive Order: A-019-0277 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

					1.4 =	1.41											
				NI	/IOG+N (g/mi)	Ox		CO (g/mi)			NOx g/mi)		HCH mg/r			Pl (g/r	
			a sur la	CER	т	STD	CER	T ST	D	CERT	STD	CER	T	STD	CEF	Т	STD
FTP@5	ok	*		*		*	*	*	1	*	*	*		*	*		*
FTP@L	JL TIE	OLIN R3 E PREM	10	0.06	55 0	.125	0.5	2.	1	*	*	1		4 0.00		0	0.01
50°F @	4K	*		*	1.1	*	*	*	t costa	*	*	*		*	in a second		
				1.2	E U			and the second		1	MOG+N	Dx (g/mi)			CO (g	/mi)	
					FU	EL TYP	E			С	CERT STD			CER	RT		
HWFE	T @ 50K					*					*	*					
HWFE	T@UL		G	ASO	LINE-?	TIER3	E10 PI	REM		0	.034	0.125	194				
20°F	@ 50K	cc	DLD CO	E10) PREM	IUM GA	SOLIN	E (TIER	23)					0.8			10.0
			S	FTP	EXHAL	JST EM	ISSION	STAND	ARDS	AND	CERTIFIC		EVEL	S			
						, J	JS06				SC03		1	COMPOSITE			
	FUEL TYPE			NN	/IOG+N (g/mi)		CO (g/mi)		M J/mi))G+NOx g/mi)	Ox CO (g/mi)		NMOG+NOx (g/mi)		O mi)	PM (mg/mi)
@ 4K	. *		CERT		*		*				*	*					
			STD		*	·	*				*	*					
		GASOLINE- TIER3 E10 PREM			*		*		*		*	*	0.057		0	. 5	*
@ UL	TIER3				*		*		*		*	*		0.083	4	.2	*
													0.100				
		WH	IOLE VI	EHIC	LE EV	APORA	TIVE E	MISSION	STA	NDAR	DS AND	ERTIFIC	ATIO	N LEVE	LS		AND THE ALL CONTROL OF THE
						W	HOLE \	EHICLE	EVAP	ORAT	IVE TEST	ING					Por an a dation
	ORATIVE FUEL TYPE 3DHS (g/te			/test) (D UL		2DHS (g/test) @ UL RL (RL (g/m	mi) @ UL					
		15.			CER	T S	STD	FEL	CE	RT	STD	FEL	-	CEI	RT		STD
LPRXR0170RPH			GASOLII TIER3 I PREM	E10	0.1	98 0.	. 300	*	0.1	.133 0.300		*		0.00			0.05
C	DRVR / F	UEL	ONLY /	CAN	ISTER	BLEED	EVAP	ORATIVI	EEMI	SSION	STANDA	RDS AND	CE	RTIFICA	TION	EVE	ELS
										UEL ONLY EVAP & CANISTER BLEED							
	ORATIVE		ORVR (g/gallon) @ UL					DHS RIG TEST g/test) @ UL		2DHS RIG (g/test) @							
		FL	JEL TYP	E	CERT	STD			CE	RT	STD	CERT		STD	CER	Т	STD
LPRXF	80170RP		ASOLINI ER3 E: PREM		0.04	0.20		*		*	*	*		*	*		*

CALII AIR RESO	FORNIA URCES BOARD AKT	DR. ING H.C.F. PORSCHE TIENGESELLSCHAFT	Executive Order: A-019-0277 New Passenger Cars, Light-Duty Trucks ar Medium-Duty Vehicle Page 4 of 4				
EFFECTIV	E LEAK DIAMETER ST.	ANDARD AND CER	TIFICATION L	EVEL (INCHES)			
EVAPORATIVE FAMILY	LEAK FAMILY	CERI		STD			
LPRXR0170RPH	LPRXR0170RPH-001	*		0.02			

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits. S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	PORSCHE	PANAMERA TURBO S E-HYBRID	PC	4.0	AMS 8	LPRXR0170RPH	1	P
2	PORSCHE	PANAMERA TURBO S E-HYBRID EXECUTIVE	PC	4.0	AMS 8	LPRXR0170RPH	1	P
3	PORSCHE	PANAMERA TURBO S E-HYBRID SPORT TURISMO	PC	4.0	AMS 8	LPRXR0170RPH	1	Ρ

ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION

MODEL		UDDS AER	UDDS EAER	UDDS EAER US06 AER		HIGHWAY (MILES)			
NUMBER	PHEV TYPE	(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE		
1	*	18.2	18.2	*	20.8	20.8	0.00		
2	*	18.2	18.2	*	20.8	20.8	0.00		
3	*	18.2	18.2	*	20.8	20.8	0.00		