

HONDA MOTOR CO., LTD. Executive Order: A-023-0744

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MOD		EST GROUP		VEHICLE CLASS(ES)				FUEL C	ATEGORY		FUEL TYPE		
202	O LH	NXV03.5MBN			PC			SINGLE FUEL HICLE		GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION								ORY	INTERIM / IN	TERN	RMEDIATE IN-USE STD		
EX	H/ORVR	EVAP			FTP S			TP FTP			SFTP		
1	50000	150000)	LEV3	ULEV125 LEV 3 COMPOSIT			MPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	ENGINE DISPLACEMENT (L)			
1 2WU-TWC, TWC, 2WR-HO2S, 2HO2S, EGR, DFI								FULL	*				
*			*				Р	ARTIAL	RTIAL ALL MODELS				
*	d						TIAL WITH FINES	*					
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								EVAP EMISSION STD VEHICLE CLASS SPECIAL FEAT				
	LHNXR01	L	EV 2			P	rc ·	*					
				E	EMISSION C	REDIT	INFO	RMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON- ZERO-EVAP						ZEV	NMOG C	OPTIONAL EXH. STD FOR WORK TRUCKS				
	n n								N				
				NMOG	AND FLEET	ΓAVE	RAGE	INFORMA	TION				
NMOG RAF	NMOG/NMHC:				NMOG+NOX FLEET S PC+LDT (0-3750 LV (g/mi)			V) LDT	+NOX FLEET S (3751 LVW-8500 R) + MDPV (g/m				
*	* 1.10 0.05 0.065								0.074 *				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



HONDA MOTOR CO., LTD. Executive Order: A-023-0744

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _

_ day of May 2019.

Allen Lyons, Chief

Emissions Compliance, Automotive Regulations and Science Division



GASOLINE-TIER3 E10

0.01

0.20

LHNXR0151VFA

HONDA MOTOR CO., LTD.

Executive Order: A-023-0744

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

	EXHA	UST	T AND	EVA	POF	RATIVE	EMIS	SION	STAN	NDAF	RDS AN	D CE	RTI	FIC	ATION	LEV	ELS		
	FUE	FUEL TYPE			ethan de; No nent fa [g HC/	e; NMO Ox: oxid actor; 2D gallon o	G: non-0 es of nitr 0HS/3DH dispense	CH4 orga rogen; H IS [g HC d]: on-bo	anic ga CHO: /test]: pard re	as; HC forma 2/3 da efuelin	I LEVELS : hydroca :ldehyde; ays diurna g vapor re est proce	rbon; PM: pa l+hot-s ecover	NMH0 articula soak; y; g: g	C: no ate r RL [gram	on-CH4 h matter; R g HC/mi ; mg: mi	HC; C(AF: re]: runn ligram	activing lo	ity oss:	
				NMOG+NOx			co			NOx			нсно						
				(g/mi)		(g/mi) CERT STD		_	(g/mi)		. .	(mg/				(g/mi) CERT STD			
FTP@50K		*		*	<u> </u>	*	CERT *	*		CER1	STI	D CERT		+	STD CI		रा	STD *	
FTP@l	II GAS	SASOLINE-				. 125	0.1	2.:	1	*	*	\dashv	0		4		1	0.01	
50°F @	TEA2 EIO		*		*	*	*		*	*			+	*					
			<u>'</u>		EIII	EL TVD	-				NMOG+N	Ox (g	mi)	T		CO (g	g/mi)		
				(8)	FUEL TYPE			CERT			STD		CERT		STD				
HWFE	Г@ 50К					*					*		*						
HWFET @ UL				GA	SOLI	NE-LEV	3 E10			0	0.028		0.125						
20°F @ 50K COLD CO E10 REGU				LAR G	ASOLINE (TIER3)							0.9		10.0					
			S	FTP E	XHAL	JST EM	ISSION	STANDA	ARDS	AND	CERTIFI	CATIO	N LE	VEL	S	•			
		FUEL TYPE					JS06			SC03				COMPOSITE					
	FUEL T			NMOG+NOx (g/mi)		CO PM (g/mi) (mg/n			NMOG+NOx (g/mi)					IOG+NOx (g/mi) (O mi)	PM (mg/mi)		
@ 4K	*	* CEI		* *		*				*	*	WELL CONTROL							
					*		*				* *								
		GASOLINE- LEV3 E10		T *		*	*	r	*		*		0.050		0	. 4	*		
@ UL					*		*	,	•		*	*		0	.083	4	. 2	*	
				116										0	.100				
		WH	OLE V	EHICL	E EV						DS AND		FICA	TIO	N LEVE	_S			
EVA D	OD A TIVE								EVAP	ORA	TIVE TES	TING			D	l /a/m	🙈		
	ORATIVE MILY	FUEL TYPE		YPE	3DHS (g/test) @ UL					2DHS (g/test) @ UL				RL (g/mi) @ UL					
				CER	RT S	TD	FEL	CERT		STD		FEL		CERT		STD			
LHNXR0151VFA			GASOLINE- LEV3 E10 0.25 0			.50 * 0.		37	37 0.65 *			0.00		0.05					
C	RVR / FU	JEL (ONLY /	CANIS	STER	BLEED	EVAPO	RATIVE	EMIS	SSION	STAND	ARDS	AND	CEF	RTIFICA	TION	EVE	LS	
											UEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY		ORVR (g/gal			Ion) @) UL	FUEL TYPE		55000000000		IS RIG TEST /test) @ UL		2DHS RIG (g/test) @					CANISTER /test) @ 4K	
		FUEL TYPE		PE C	ERT	STD			CE	RT STD		CE	RT	STD		CERT STD			



HONDA MOTOR CO., LTD. Executive Order: A-023-0744

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
*	*	*	*							

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
ACURA	RLX	PC	3.5	SA10	LHNXR0151VFA	1	P