

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

YEAR PC   2020 LHNXV02.0BEB   USEFUL LIFE (miles) VEHICLE EMISSION CATEGORY   EXH/ORVR EVAP   150000 150000   LEV3 SULEV30   SPECIAL EEATURES & EXHAUST EMISSION CONTROL											
2020 LHNXV02.0BEB PC   USEFUL LIFE (miles) VEHICLE EMISSION CATEGORY   EXH/ORVR EVAP FTP   150000 150000 LEV3 SULEV30 LEV 3 COMPOSIT   SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS OB   1 TWC, WR-H02S, H02S, EGR, EGRC, SFI FULL   * * PARTIAL	VEHICLE GASOLINE   INTERIM / INTERMEDIATE IN-USE STD   FTP   SFTP   TE *										
EXH/ORVR EVAP FTP SFTP   150000 150000 LEV3 SULEV30 LEV 3 COMPOSIT   SPECIAL FEATURES & EXHAUST EMISSION CONTROL OB OB   1 TWC, WR-H02S, H02S, EGR, EGRC, SFI FULL   * * PARTIAL   * * PARTIAL	TE FTP SFTP * PM										
150000 150000 LEV3 SULEV30 LEV 3 COMPOSIT   SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS OB   1 TWC, WR-HO2S, HO2S, EGR, EGRC, SFI FULL   * * PARTIAL	TE * PM										
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS OB   1 TWC, WR-HO2S, HO2S, EGR, EGRC, SFI FULL   * * PARTIAL   * * PARTIAL											
SYSTEMS OB   1 TWC, WR-HO2S, HO2S, EGR, EGRC, SFI FULL   * * PARTIAL   * * PARTIAL											
* * PARTIAL	BD STATUS										
A PARTIAL W	*										
*     *	L ALL MODELS 2.0										
	ИТН *										
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION											
	EMISSION STD HICLE CLASS SPECIAL FEATURES										
LHNXR0121VSA LEV 3 OPTION2	PC *										
EMISSION CREDIT INFORMATI	ION										
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON-PZEV ZERO-EVAP	OG CREDIT FOR DOR OPTIONAL EXH. STD FOR WORK TRUCKS										
Y N	N N										
NMOG AND FLEET AVERAGE INFOR	RMATION										
NMOG CH4 NMOG/NMHC HCHO/NMHC PC+LDT (0-3750 LVW)	MOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi) NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)										
* * 1.10 0.05 0.065	(3)										

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this <u>20</u><sup>1</sup> day of September 2019.

Midrael J. Ros Allen Lyons, Chief Jan A Emissions Certification and Compliance Division



FUEL TYPE

HONDA MOTOR CO., LTD. Executive Order: A-023-0758 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

						*****							
				S+NOx mi)	CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		5	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL		OLINE- V3 E10	0.016	0.030	0.4	1.0	*	*	0	4	0.001	0.003	
50°F @4K		*	*	*	*	*	*	*	*	*		lag Salap os	
							N	NMOG+NOx (g/mi)			CO (g/mi)		
				FUEL TYP	E		CE	RT	STD	CER	T	STD	
HWFET @	@ 50K *				*			*		*			
HWFET @	WFET @ UL GASOLINE-LEV			3 E10		0.0	004	0.030			an a dar da sa		
20°F @	50K COLD CO E10 REGULAR GASOLINE (TIER3)								0.	5	10.0		

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC03	3	CON	IPOSITE	
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			Anna I
		STD	*	*		*	*			
		CERT	*	*	0	*	*	0.011	0.4	*
@ UL	GASOLINE- LEV3 E10	STD	*	*	6	*	*	0.083	3 4.2	*
		BIN						0.050		end de la

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WHOLE \	/EHICLE	EVAPORA	TIVE TESTI	NG					
EVAPORATIVE FAMILY	FUEL TYPE	3DH	S (g/test) @	DUL	2DI	HS (g/test) (	RL (g/mi) @ UL					
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD			
LHNXR0121VSA	GASOLINE- LEV3 E10	0.202	0.300	*	0.218	0.300	*	0.00	0.05			
ORVR / FUE	ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS											
	FUEL ONLY EVAP & CANISTER BLEED											

					FUELC	INLI EVA	- a CANIS	IER BLEE	U			
EVAPORATIVE FAMILY	ORVR (g/g	gallon) @	) UL	FUEL TYPE	3DHS R (g/test	IG TEST ) @ UL	2DHS R (g/test		BLEED C TEST (g/t			
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD		
LHNXR0121VSA	GASOLINE- TIER3 E10	0.01	0.20	GASOLINE- LEV3 E10	*	*	*	*	0.004	0.020		

CALI AIR RESC	LIFORNIA ESOURCES BOARD HONDA MOTOR CO., LTD.		Executive Order: A-023-0758 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4								
EFFECTI	/E LEAK DIAMETER	STA	NDARD AND CER	TIFICATION L	_EVEL (INCHES)						
EVAPORATIVE FAMILY	LEAK FAMILY		CERT	Г	STD						
LHNXR0121VSA	LHNXR0121VSA-B00		*	=	0.02						
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: su ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxid heated/oxygen sensor; WR-H RDQS: reductant quality sen: EGRC: EGR cooler; AIR/AIR fuel injection; DFI/IFI: direct/i full/partial/partial with fines or prefix 2: parallel; (2) suffix: se device (ex. DPF-SCRC: SCR ethanol ("15%"gasoline) fuel; -automatic transmission; CV: automated manual transmiss	LHNXR0121VSA     LHNXR0121VSA=B00     *     0.02       *: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751- 8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: medium- duty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR; gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TVC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOX sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$ full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DFF-SCRC: SCR coated DFF); CNG/LNG: compr										

# 2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
HONDA	ACCORD HYBRID	PC	2.0	CV1	LHNXR0121VSA	1	P