

HYUNDAI MOTOR COMPANY

Executive Order: A-254-0415 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODEL YEAR TEST GROUP				VEHICLE CLASS(ES)			FUEL C	ATEGORY		FUEL TYPE			
2020 LHYXV01.6BC5 PC									SINGLE FUEL HICLE		GASOLINE		
USEFUL LIFE (miles) VEHICLE						LE EMISSION CATEGORY INTERIM / IN					TERMEDIATE IN-USE STD		
EXHIORVR EVAP				FTP SF			TP	FTP		SFTP			
150000 150000				LEV3	3 ULEV70 LEV 3 COMP			OMPOSITE	PM		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD STATUS			ENGINE DISPLACEMENT (L)		
1	1 WU-TWC, TWC, WR-HO2S, HO2S, DFI, TC, CAC							FULL	*	7			
* *							F	ARTIAL	ALL MODELS	1.6			
*	* *							TIAL WITH	. *				
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR					GORY			SSION STD E CLASS	SF	SPECIAL FEATURES			
LHYXR0110BCE LEV 2					EV 2			F	PC		*		
				E	EMISSION CI	REDIT	INFO	ORMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NO ZERO-EVAP					ON-P	ZEV	- I NIMOG CREDIT EOR DOR I			PTIONAL EXH. STD OR WORK TRUCKS			
N N								n n					
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	NMOG/NMHC PC+LD1 (0-37)				0-375		W) LDT (3751 LVW-8500 MDV (10,00°			MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	* * 1.10 * 0.065						0.074 *						

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



HYUNDAI MOTOR COMPANY

Executive Order: A-254-0415

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 3011

Allen Lyons, Chief

Emissions Compliance, Automotive Regulations and Science Division



HYUNDAI MOTOR COMPANY Executive Order: A-254-0415 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

							A.	TTAC	HM	ENT	•								
	EXH	AUS	TAI	ND E	VAPOF	RATIV	EEMIS	SION	STAN	IDAF	RDS AND	CERTI	FICA	TION	LEVEL	S			
		EXI	HAUS	TEM	SSION S	STAND	ARDS A	ND CER	TIFIC	ATION	LEVELS	(FTP, HW	FET, 5	50°F, 20	°F)				
	FU	EL T	YPE	mon adjus ORV	oxide; N stment fa /R [g HC	Ox: oxio actor; 2[/gallon (les of nit DHS/3DH dispense	rogen; H IS [g HC d]: on-bo	CHO: :/test]: oard re	formal 2/3 da fueling	: hydrocan ldehyde; P lys diurnal- g vapor rec est proced	M: particu +hot-soak covery; g:	ılate m ; RL [g gram;	atter; R/ HC/mi] mg: mill	AF: react : running ligram; m	ivity loss;			
							NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)			PM (g/mi)		
				CE	RT	STD	CERT		<u> </u>	CERT		CER		STD	CERT	STD			
FTP@5	oK	*			* '	*	*	*	1	*	*	*	1	* *		*			
FTP@l	TP@UL GASOLINE- TIER3 E10		0.	046	0.070	0.6	1.	7	*	*.	*		4	0.001	0.003				
50°F @4K GASO				0.	040	0.140	0.3	1.	7	w	*	*		16					
					FL	JEL TYP	PΕ				NMOG+N				CO (g/m				
		-								CERT		STD		CERT		STD			
HWFE.	T @ 50k	1			*					<u> </u>	*								
HWFE	T@UL				GASOLI	NE-TIE	R3 E10	R3 E10		0	.027	0.070	70						
20°F	@ 50K		COLD	CO E	10 REGU	JLAR G	ASOLINI	(TIEF	R3)				- 1 - 1 - 1 - 1	0.6		10.0			
				SFT	PEXHA	UST EN	ISSION	STAND	ARDS	AND	CERTIFIC	ATION LE	EVELS						
\$		UEL TYPE					US06	S06			SC03				OMPOSITE				
	FUEL				NMOG+I (g/mi		CO (g/mi)	1	M /mi)		OG+NOx g/mi)	CO (g/mi)		G+NOx /mi)	CO (g/mi)	PM (mg/mi)			
@ 4K	*	*		* CERT		RT			*			*		*					
				STD		*		*			*	*							
	CER		CE		*		*		2	<u> </u>	*	*	0.059		0.7	*			
@ UL	2 0 5 55 55	TIERS EIG		מז	*		*	(6		*	*	0.	.083	4.2	*			
				IN									Annean and the same	070					
		W	HOLI	VEH	ICLE EV						DS AND C	-	ATION	LEVEL	.S				
		_				W	HOLE V	EHICLE	EVAP	ORAT	TIVE TEST	ING		DI	(m/mai) (20111			
	FAMILY FUE		AMILY FUEL TYPE			3DHS (g/test) @ UL				2DHS (g/test) @					RL (g/mi) @ U				
									STD	TD FEL C		ERT STD		FEL		CERT		STD	
LHYXR0110BCE		E	CA P	HASE 2			.50	*	0.29		0.65	*				0.05			
	DRVR / I	FUEL	ONL	YICA	NISTER	BLEE	EVAPO	DRATIVE			STANDA					ELS			
EVAPORATIVE FAMILY		,		/R (g/	'R (g/gallon) @ UL					DHS RIG TEST		2DHS RIG T		EST					
				1					FUEL TYPE		(g/test) @ UL		(g/test) @ l		UL TEST (g/t		est) @ 4K		
				TYPE	CERT	STD			CE	RT	STD	CERT	S	TD	CERT	STD			
LHYXF	E	ASOLINE - TIER 2 0. UNLEADED		0.06	0.20	*			*		*		* *		*				



HYUNDAI MOTOR COMPANY

Executive Order: A-254-0415

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
*	*	*	*						

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic: DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
HYUNDAI	VELOSTER	PC	1.6	м6	LHYXR0110BCE	1	P
HYUNDAI	VELOSTER	PC	1.6	AM7	LHYXR0110BCE	1	P