

Executive Order: A-254-0425 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	IFORI	MATION					
MODE		EST GROUP	VEHIC	CLE CLASS(ES)		FUEL C	ATEGORY		FUEL TYPE		
2020	LH	YXV02.0MG5		PC		I		SINGLE FUEL HICLE		GASOLINE		
à	USEFUL	LIFE (miles)	VE	HICLE EMIS	SION C	ATEC	ORY	INTERIM / IN	ER	MEDIATE IN-USE STD		
EXI	I/ORVR	EVAP		FTP		SF	ГР	FTP		SFTP		
1.	50000	150000	LEV	ULEV70	LEV	3 CO	MPOSITE	PM	- 11	PM		
SPE	CIAL FE		HAUST EMISSI	ON CONTRO	OL .		OBD S	TATUS	E	NGINE DISPLACEMENT (L)		
1	WU-TW	C, TWC, WR-H	102S, H02S, I	FI, TC, C	AC		FULL	*	W.			
*		-	*		N. O. S. C.	P	ARTIAL	ALL MODELS	2.0			
*			*		9 3 Ho	The state of	TIAL WITH FINES	*	desired fill spends			
		E	/APORATIVE 8	REFUELIN	G (EVA	P/OR	VR) FAMILY	INFORMATION				
EVA	AP / ORV	RFAMILY	EVAPORATIV	E STD CATE	EGORY			SSION STD E CLASS	S	SPECIAL FEATURES		
	LHYXR01	35MGG	LEV 3	OPTION2		PC				HCT		
				EMISSION (CREDIT	INFC	RMATION					
	REDIT FO	X FLEET AVE. OR EXTENDED RRANTY	NMOG CI	REDIT FOR I		ZEV	NMOG CI	REDIT FOR DOF	2	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N		N				N		N		
	7		NMO	G AND FLEE	T AVE	RAGE	INFORMA	TION		· ·		
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO	PC+LDT			/) LDT (+NOX FLEET S1 (3751 LVW-8500 R) + MDPV (g/mi		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	*		0.065			0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-254-0425 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

althoughter (Chr) \$ 550° noticed

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

DE TELFERON CLETTETO NON CONTROL STORME CONTROL NON PLETE OF 40% 新/性 14/2 1477

HONEY VAUNT : (SIN VO

Executed at El Monte, California on this 14

MOSTAMACHA TATATA ROMENIA

MERCAMPO SALEDANIANA TREFFERMA DERIM

ins directory of the time discrete, the constitue family Engine Displacement, teniavion Society Systems France

POFE BY WOLVEST

becaused with seniches in 1949 oner 36 years as 1974 in 1974 Indian in the Executive Corper are centred to the respondent teation because a anchorable to MOV portugate to 3 october 1965 and 1965 and 1965 and 1965

Allen Lyons, Chief

Emissions Compliance, Automotive Regulations and Science Division



Executive Order: A-254-0425

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS	AND CERTIFICATION LEVELS	(FTP, HWFET, 50°F, 20°	°F)
----------------------------	--------------------------	------------------------	-----

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

		NMOG+NOx (g/mi)				NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K		*	* =	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10	0.042	0.070	0.3	1.7	*	*	*	4	0.001	0.003
50°F @4K	GASOLINE- TIER3 E10	0.040	0.140	0.1	1.7	vii 1 ¥ 1-10	*	*	16		

	EUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)		
	FUEL TYPE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*				
HWFET @ UL	GASOLINE-TIER3 E10	0.016	0.070			
20°F @ 50K	COLD CO E10 REGULAR GASOLINE (TIER3)			0.7	10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06	- W	SC03	-	COMPOSITE		
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*			
-	(4)	CERT	*	*	2	*	*	0.040	0.8	*
@ UL	GASOLINE- TIER3 E10	STD	*	*	6	*	*	0.083	4.2	*
	•	BIN						0.070		4

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WHOLE \						
EVAPORATIVE FAMILY	FUEL TYPE	3DHS (g/test) @ UL			2DI	HS (g/test) @ UL		RL (g/n	ni) @ UL
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
LHYXR0135MGG	GASOLINE- LEV3 E10	0.226	0.300	*	0.224	0.300	*	0.01	0.05

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

				FUEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY	ORVR (g/g	gallon) @	UL	FUEL TYPE	3DHS R (g/test		2DHS R (g/test		BLEED C TEST (g/t			
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD		
LHYXR0135MGG	GASOLINE- TIER3 E10	0.03	0.20	GASOLINE- LEV3 E10	*	*	· *	*	0.003	0.020		



Executive Order: A-254-0425 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

EFFECTIV	/E LEAK DIAMETER STA	ANDARD AND CERTIFICATION	LEVEL (INCHES)
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD
LHYXR0135MGG	LHYXR0135MGG-TM1	0.00	0.02

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	ECS	OBD
WAIL	an year year as a second	Commission of Statement &	2.0	SA8	LHYXR0135MGG	1	P
HYUNDAI	SANTA FE AWD	PC		3 200	LHYXR0135MGG	1	P
HYUNDAI	SANTA FE FWD	PC	2.0	SA8	LHYXR0135MGG	ALTER STREET	- 10 c

AND LEVEL STANDORATE TEST OF

以前作的现代形式

A 4 6 - 19 19 19 19

THUR LAYED

EDEN EL MORENCHET AND APOLICE CHERTHER AND ACTOR EVIDER

M. An 拉翻起

AREA EVANCE AND SECRETARIOUS ARE DESCRIBED AND AREA OF AREA.

PURE ONLY BUAP & CANSTELL

T TAR