

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	UP IN	IFOR	MATION					
MOD YEA		EST GROUP		VEHICI	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE		
202	0 LH	YXV02.4LH5		ť.	PC		DEDICATED SINGLE FUEL VEHICLE			GASOLINE			
	USEFUL	LIFE (miles)		VEH	ICLE EMISS	ION C	ATE	GORY	INTERIM / IN	TER	FERMEDIATE IN-USE STD		
EXH/ORVR EVAP					FTP S			SFTP FTP			SFTP		
1	50000	150000		LEV3	ULEV70	LEV	LEV 3 COMPOSITE PM				PM		
SPECIAL FEATURES & EXHAUST E SYSTEMS								OBD S	TATUS	E	NGINE DISPLACEMENT (L)		
1 WU-TWC, TWC, WR-HO2S, HO2S,								FULL	SOME MODELS	COLUMN COLUMN			
* *							P	ARTIAL	SOME MODELS	A LANGE	2.4		
* *								ARTIAL WITH *					
		E١	/APO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	(INFORMATIO	4			
EV	AP / ORV	R FAMILY	PORATIVE					SSION STD E CLASS	s	PECIAL FEATURES			
	LHYXR0133LHG				LEV 3 OPTION2 PC					HCT			
				E	EMISSION C	REDIT	INFO	RMATION	-				
	REDIT FC	X FLEET AVE. R EXTENDED RANTY		EDIT FOR N ZERO-EVAP		ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS			
N N								N N					
				NMOG	AND FLEET	T AVE	RAG	E INFORMA	TION				
NMOC RAF	NMOG CH4 FTP RAF RAF NMOG/NMHC RATIO RATIO (g/n						_VW) LDT (3751 LVW-8500 MDV (10,0			NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*	0	0.065			0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### **BE IT FURTHER RESOLVED:**

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### **BE IT FURTHER RESOLVED:**

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_day of July 2019.

Allen Lyons, Chief Emissions Certification and Compliance Division



HYUNDAI MOTOR COMPANY Executive Order: A-254-0427 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

# ATTACHMENT

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon<br/>monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity<br/>adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss;<br/>ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K:<br/>1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)			CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		°M 'mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K	950K *		*	*	*	*	*	*	*	*	*	*	
FTP@UL	TP@UL GASOLINE- TIER3 E10		0.034	0.070	0.5	1.7	*	*	*	4	0.000	0.003	
50°F @4K	31374135071133	SOLINE- LR3 E10	0.028	0.140	0.2	1.7	*	*	*	16	and designed and the second se		
								NMOG+NOx (g/mi)			CO (g/mi)		
FUEL TYPE					CE	RT	STD	CER	T	STD			
HWFET @ 50K				*				*					
HWFET @ UL			GASO	LINE-TIE	R3 E10		0.0	)17	<b>0.070</b>				
20°F @ 50K		COLD (	CO E10 RI	EGULAR G	ASOLINE	(TIER3)	i Barto	t page and the second sec	1994. 1994. 1994.	1.5	5	10.0	

## SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			361	FEANA	JOIEN	133101	I STANDA	ANDS AN	DCERTIFIC		in the second				
						<b>JS06</b>			SC03		COMPOSITE				
	FUEL TYI	PE		NMOG+N (g/mi		CO (g/mi)	Pl (mg/		MOG+NOx (g/mi)	CO (g/mi)	NMOG+N (g/mi)		CO /mi)	PM (mg/mi)	
@ 4K	*	* CE		*		*	1		*	*					
Ŭ			STD	*		*			*	*					
		C	CERT	*		*	0		*	*	0.030	0	.9	*	
@ UL	GASOLIN TIER3 E		STD	*		*	6		*	*	0.083	4	.2	*	
			BIN								0.070				
		WHO	LE VEH	ICLE EV	APORA	TIVE E	MISSION	STANDA	RDS AND	CERTIFICA	TION LEV	ELS			
					W	HOLE	/EHICLE	EVAPOR	ATIVE TES	TING					
		FUEL TYPE		E :	BDHS (g	/test) (	@ UL	2	DHS (g/test	) @ UL		RL (g/n	1i) @	i) @ UL	
				CEI	रा	STD	FEL	CERT	STD	t) @ UL RL (g/mi) @ FEL CERT S	STD				
LHYXR0133LHG			SOLINE EV3 E10	102	48 0	.300	*	0.171	0.300	*	0	0.01			
(	ORVR / FUI	EL O	NLY / CA	NISTER	BLEE	DEVAP	ORATIVE	EMISSI	ON STANDA	RDS AND	CERTIFIC	ATION	LEVE	ELS	
								FUEL	ONLY EVA	P & CAN	STER BLE	ED			
ORVR / FU EVAPORATIVE FAMILY		0	ORVR (g/gal		on) @ UL		FUEL TYPE		3DHS RIG TEST (g/test) @ UL		RIG TEST () @ UL		BLEED CANISTE TEST (g/test) @ 4		
		FUE	L TYPE	CERT	STD			CERT	STD	CERT	STD	CEF	RT	STD	
LHYXI	R0133LHG		OLINE- R3 E10	0.00	0.20		OLINE- 73 E10	*	*	*	*	0.0	11	0.020	

CALI AIR RESC	FORNIA URCES BOARD	COMPANY			Executive Order: A-254-0427 Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4			
EFFECTI	/E LEAK DIAMETER	STA	NDARD AND CER	TIFICATION L	EVEL (INCHES)			
EVAPORATIVE FAMILY	LEAK FAMILY		CER	Г	STD			
LHYXR0133LHG	LHYXR0133LHG-T	L2	0.00	)	0.02			
8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: su ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxidi heated/oxygen sensor; WR-H RDQS: reductant quality sens secondary air injection (belt or direct/indirect fuel injection; T fines on-board diagnostic; DO suffix: series; CNG/LNG: com E10: "10%" ethanol ("90%"ga continuously variable transmi	duty vehicle; MDV4: ME : heavy-duty vehicle; EC vehicle weight rating; L' per ULEV; ZEV: zero-er AC: HC adsorbing cata : selective catalytic redu zer; DPF: diesel particu IO2S or AFS: wide rang sor; NH3S: ammonia se Iriven)/(electric driven); C/SC: turbo/super char DR: direct ozone reducin pressed/liquefied natur isoline) fuel; A: automat ssion; SCV: selectable a transmission; OT: othe	DV 850 CS: en VW: lc nission lyst; V uction- late fil ge/line pAIR: ger; C ng; HC al gas ic (with contin er trans	01-10000#GVWR; MI nission control system baded vehicle weight; n vehicle; TZEV: tran VU: warm-up catalyst urea/ammonia; NH3( lter (active); GPF: PN ar/heated air-fuel rati EGR: exhaust gas re pulsed AIR; SFI/MFI AC: charge air coolei CT: hydrocarbon trap; t; LPG: liquefied petro h lockup); M: manual uously variable trans smission; AER: all-eli	DV5: MDV 1000 n; CERT: certific ALVW: adjusted sitional ZEV; TW ; NAC: NOX ads DC: ammonia ox 1 filter for spark-i o sensor; NOXS circulation; EGR : sequential/mult r; FFH: fuel fired BCAN: bleed ca bleum gas; E85: transmission; S. mission; AM: au ectric range; EAI	tidation catalyst; CTOX/PTOX: gnited engine; HO2S/O2S: : NOx sensor; PMS: PM sensor; C: EGR cooler; AIR/AIRE: tiport fuel injection; DFI/IFI: heater; F/P/\$: full/partial/partial with arbon canister; prefix 2: parallel; (2) "85%" ethanol ("15%"gasoline) fuel; A: semi-automatic transmission; CV: tomated manual transmission; AMS: ER: equivalent AER; PHEV: plug-in			

	2020 MODEL	YEAR: VEI		ODELS INF	ORMATION		
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
HYUNDAI	TUCSON AWD	PC	2.4	SA6	LHYXR0133LHG	1	F
HYUNDAI	TUCSON AWD (W/SCC)	PC	2.4	SA6	LHYXR0133LHG	1	P
HYUNDAI	TUCSON FWD	PC	2.4	SA6	LHYXR0133LHG	1	F
HYUNDAI	TUCSON FWD (W/SCC)	PC	2.4	SA6	LHYXR0133LHG	1	P