

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

			· · · · · · · · · · · · · · · · · · ·	TEST GR	OUP IN	FOR	ATION					
MOD YEA	I TI	EST GROUP	VEHIC	CLE CLASS(	LE CLASS(ES) FUEL CATEGORY			ATEGORY	FUEL TYPE			
202	0 LK	MXV02.0D13	and ships of a	PC HYBRID ELECTRIC GA					GASOLINE			
į.	USEFUL	LIFE (miles)	VE	HICLE EMISS	SION C	ATEG	TEGORY INTERIM / INTERMEDIATE IN-USE S					
EX	H/ORVR	EVAP		FTP	1.000	SF	FTP TABLE FTP			SFTP		
1	50000	150000	LEV3	SULEV30	LEV	3 CO	3 COMPOSITE P			PM		
SP	ECIAL FE		HAUST EMISS		DL		OBD S	TATUS	a straighter a	ENGINE DISPLACEMENT (L)		
1	DFI, WI	R-HO2S, HO2S	, WU-TWC, TW	VC, EGR, E	GRC	12.5	FULL		Statistics in	an suffering to the service of		
*			*			P.	ARTIAL	ALL MODELS	100	2.0		
*		~~~	*	E	APPENDING IN DESTRICTION		TAL WITH *					
		E\	APORATIVE 8		G (EVA	P/OR	R) FAMIL	INFORMATIO	N			
EV	AP / ORV	R FAMILY	EVAPORATIV	E STD CATE	GORY		EVAP EMISSION STD VEHICLE CLASS SPECIAL FEATURE					
	LKMXR01	43D1E	. ]	LEV 2			P	DC D		*		
				EMISSION C	REDIT	INFC	RMATION			· · · · · · · · · · · · · · · · · · ·		
	REDIT FO	X FLEET AVE. OR EXTENDED RRANTY	REDIT FOR N ZERO-EVAF		ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS			
		N		N			N N					
			NMO	G AND FLEE	TAVE	RAGE	INFORMA	TION				
NMOG RAF	MOG CH4   MOG/MMHC   HCHO/NMHC   PC+LT					ET STD NMOG+NOX FLEET STI 0 LVW) LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)			0			
*	*	1.10	*		0.065			0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)

CALIFORNIA AIR RESOURCES BOARD

#### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this  $5t^{L}$  day of April 2019.

Michael A. I Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

reaction provides a reaction of the state of the second state of t	$[a(i)] \vec{T} [a_i^{(n)} + i$	ontal na 195 Novemb	7		
CTE INÉ D'HORTEC ENCORT NOTIVIER	905 901 T0390 0089	KALLEN AN NUT NEED V BRANT NAM		SVALLEN GROENEER VRAA	05 T1C 9/10
	l'		and the second	an same name of a little too, is a most strain	and a support of the support
<ul> <li>South and the set of the set of</li></ul>	HOLAMECTIP:	uku tu ku	a anna anna anna anna anna anna anna a		
MUM (16.965) (4,000 - )	<ul> <li>VARCS (KINTYLEET STU ) (MCSTATION WARKS)</li> <li>(MCSTATION WARKS)</li> </ul>	Francist to a start LVA	CHMMICH H CITAR	977) OHRENSSMA OTTER	ા તેટ્ર વે તેટ્ર વે તેટ્ર
and a second		124 4		61	

See the Avaluation for Mariede Modela, Evanpointing Family, Empire Ouplansing, Emission Outron, Svatikis, Phane In Reschires, CRU, Lucipatives, Eccolor, Standards and Cerufication Levels, Into Abb. Attaces, Accupitation menoreally, Articles (HTV) over 14, 500 polytes in RVMR, Takad in hits Executive Onder and Sacrina Torthe Process rights (FTV), CP Station 1961 2, authority to MOV pursuant to 15, CCR Section, 1963 (2012), or 15 CCR Record 1966 RAPED, et abolication



FUEL TYPE

UNLEADED

KIA MOTORS CORPORATION Executive Order: A-314-0326 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

# ATTACHMENT

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

1.11年代現代													
		NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)		
C SCHERE			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K	050K *		*	*	*	*	* ,	*	*	*	*	*	
FTP@UL		OLINE- R3 E10	0.015	0.030	0.4	1.0	*	*	*	4	0.000	0.003	
50°F @4K		OLINE- R3 E10	0.012	0.060	0.2	1.0	*	*	*	8			
She Quille			-	FUEL TYP	-		NN	OG+NO	x (g/mi)	CO (g/mi)			
				FUEL ITP	<b>C</b>		CE	RT	STD	CEF	RT	STD	
HWFET @ 50K				*		-	*	* *				a) son matanyous	
HWFET @ UL		L GASOLINE-TIER3 E10					0.0	0.006 0.030					
20°F @ 50K		COLD C	CO E10 RE	GULAR GA	SOLINE	(TIER3)	. 动力支持			0.1	5	10.0	

### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

		31	IFE		JOI EIN	133101	STANDA	ANDS AN		CERTIFIC.		VELS		2		
		1973-278 				JS06		-		SC03	-	С	OMPC	SITE		
	FUEL TY	PE			MOG+NOx (g/mi)		Pl (mg/		NMOG+NOx (g/mi)		CO (g/mi)	NMOG+NOx (g/mi)		CO g/mi)	PM (mg/mi)	
@ 4K	*	CERT		*		*			*		*					
-		STD	*		*		*		*	* .		18 37	ta de te			
		I SID I		*		* 1			*		*	0.012		0.3	*	
@ UL	GASOLIN TIER3 E			*		* 6		;		*	*	0.083		4.2	*	
		BIN	協議	1.5								0.030	24		e Thefe	
		WHOLE VE	HICL	E EV	APORA	TIVE E	MISSION	STAND	AR	DS AND C	ERTIFIC	TION LEVE	ELS			
×					W	HOLE \	/EHICLE	EVAPOR	RAT	IVE TEST	ING					
	ORATIVE	FUEL TYPE		3	DHS (g	(g/test) @ UL		2	2DHS (g/test)		@ UL		RL (g/mi) @		UL	
				CERT		STD	D FEL CE			STD FE		L CERT		STD		
LKMXR0143D1E		GASOLINI CA PHASI		0.3	0 0	.50	*	0.30		0.65	*	0.	0.02		0.05	
(	ORVR / FUI	EL ONLY / C	ANI	STER	BLEED	EVAP	ORATIVE	EMISSI	ON	STANDA	RDS AND	CERTIFIC	TION	LEVE	ELS	
	2							FUE	LO	NLY EVA	P & CANI	STER BLEE	D			
EVAPORATIVE FAMILY		ORVR (	g/gal	lon) @ UL		FUEL TYPE			3DHS RIG TEST (g/test) @ UL			RIG TEST st) @ UL			CANISTER g/test) @ 4K	
		FUEL TYP	EC	ERT	STD			CERT	r	STD	CERT	STD	CE	1	STD	
LKMXI	R0143D1E	GASOLINE TIER 2		0.02	0.20		*		а. "	*	*	*	+	,	*	

CALI AIR RESC	FORNIA DURCES BOARD	C	KIA MOTORS CORPORATION		Executive Order: A-314-0326 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4							
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE FAMILY	LEAK FAMILY		CER	ſ	STD							
*	*	1999 - 1999 1997 -	*		*							
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: su ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxidi heated/oxygen sensor; WR-H RDQS: reductant quality sens secondary air injection (belt d direct/indirect fuel injection; T fines on-board diagnostic; DC suffix: series; CNG/LNG: com E10: "10%" ethanol ("90%"ga continuously variable transmi automated manual-selectable	* * * * * * * * * * * * * * * * * * *											
2020	MODEL YEAR	: VE	HICLE MOD	ELS INFO	RMATION							

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
KIA	OPTIMA HYBRID	PC	2.0	AM6	LKMXR0143D1E	1	P