

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	UP IN	IFOR	MATION					
MODE YEAF		EST GROUP		VEHIC	LE CLASS(E	S)		FUEL CATEGORY			FUEL TYPE		
2020	2020 LKMXV02.0CE5 PC							DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION							CATEGORY INTERIM / INTERMED					EDIATE IN-USE STD	
EXH	I/ORVR	EVAP	-		FTP		SF	TP		-TP	SFTP		
15	0000	150000	(here) at	LEV3	ULEV70	LEV	з сс	MPOSITE		PM		PM	
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS		EN	GINE DISPLACEMENT (L)	
1	1 SFI, WR-HO2S, HO2S, WU-TWC, TWC, EGR, EGRC								ALL MO	DELS	a land		
*	* *							ARTIAL	*			2.0	
*	*							ARTIAL WITH * FINES *					
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVA	P / ORV	R FAMILY	EVA	PORATIVE	E STD CATE	GORY		EVAP EMISSION STD VEHICLE CLASS			SP	ECIAL FEATURES	
I	KMXR01	.30CEG		LEV 3	3 OPTION2 PC						HCT		
				I	EMISSION CI	REDIT	INFC	RMATION					
	EDIT FO	X FLEET AVE. DR EXTENDED RRANTY			REDIT FOR NON-PZEV ZERO-EVAP						OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N			N	
				NMOG	AND FLEET	AVE	RAGE	INFORMA	TION		-		
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	1 10 10 0000000	HCHO/NMHC RATIO NMOG+NOX FL PC+LDT (0-375 (g/mi)				V) LDT	+NOX FLE (3751 LVW R) + MDPV	-8500			
*	*	1.10		*	0	.065			0.074			*	
See th	o Attack	ment for Vehi		odels Ev	anorative Fa	milv	Engi	ne Displace	ement En	nission	Con	trol Systems Phase-	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this <u>477</u> day of June 2019.

Allen Lyons, Chief Emissions Compliance, Automotive Regulations and Science Division



FUEL TYPE

KIA MOTORS CORPORATION Executive Order: A-314-0333 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.												
24 				G+NOx mi)		O mi)		Ox mi)		HO /mi)		M mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K		*	*	*	*	*	*	*	*	*	*	*
FTP@UL		OLINE- R3 E10	0.033	0.070	0.3	1.7	*	*	*	4	0.000	0.003
50°F @4K		OLINE- R3 E10	0.024	0.140	0.1	1.7	*	*	*	16		
N. M. Martin	111. 38 F.						NN	NMOG+NOx (g/mi)			CO (g/mi)
的限制			FUEL TYPE						STD	CEF	т	STD
HWFET @) 50K					*		er alle and				
HWFET @	D UL		GASO	R3 E10	0.0	023	0.070			Filese and		
20°F @ 50K		COLD (CO E10 RI	EGULAR GA	ASOLINE	(TIER3)	in the second	Salasie -		0.4	1	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	1.11111	US06			SC03		COMPOSITE			
FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	
@ 4K *	CERT	*	*		*	*				
	STD	*	*	学性的学生	*	*				
	CERT	*	*	1	*	*	0.034	0.6	*	
GASOLINE- TIER3 E10	STD	*	*	6	*	*	0.083	4.2	*	
	BIN		- Alexandra da	- 法教育的保守	and the second second	和理论的对	0.070	Autoria		
	* GASOLINE-	A CERT * CERT STD CERT GASOLINE- TIER3 E10 STD	(g/mi) * CERT * STD * * GASOLINE- TIER3 E10 STD *	(g/mi) (g/mi) * CERT * STD * * GASOLINE- TIER3 E10 STD *	(g/mi) (g/mi) (mg/mi) * CERT * * STD * * * GASOLINE- TIER3 E10 STD * * 1	(g/mi) (g/mi) (mg/mi) (g/mi) * CERT * * * STD * * * * GASOLINE- TIER3 E10 STD * * 6 *	Kommunication (g/mi) (g/mi) (mg/mi) (g/mi) <th< td=""><td>K (g/mi) (g/mi) (mg/mi) (g/mi) (g/mi)</td><td>Matrix Matrix Matrix<</td></th<>	K (g/mi) (g/mi) (mg/mi) (g/mi)	Matrix Matrix<	

WHOLE VEHICLE EVAPORATIVE TESTING

			WINCLE							
EVAPORATIVE FAMILY	FUEL TYPE	3DHS (g/test		@ UL	2D	HS (g/test)	IS (g/test) @ UL			ni) @ UL
		CERT	STD	FEL	CERT	STD	FEL	CER	T	STD
LKMXR0130CEG	GASOLINE- LEV3 E10	0.256	0.300	*	0.194	0.300	*	0.0	3	0.05
ORVR / FUI	EL ONLY / CAN	STER BL	EED EVAF	ORATIV	E EMISSION	N STANDAF	RDS AND CEI	RTIFICA	ΓΙΟΝ Ι	LEVELS
				FUEL ONLY EVAP & CANISTER BLEED						
EVAPORATIVE	ORVR (g/gal	ion) @ UL			3DHS RIG TEST		2DHS RIG TEST		BLEED CANISTER	

EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE		IG TEST :) @ UL		IG TEST) @ UL	BLEED CANISTER TEST (g/test) @ 4K	
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD
LKMXR0130CEG	GASOLINE- TIER3 E10	0.01	0.20	GASOLINE- LEV3 E10	*	*	*	*	0.006	0.020

CALI AIR RESO	FORNIA DURCES BOARD	, C	KIA MOTORS CORPORATION	New Pa	Executive Order: A-314-0333 ssenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4
EFFECTIV	/E LEAK DIAMETER	STA	NDARD AND CER	TIFICATION L	EVEL (INCHES)
EVAPORATIVE FAMILY	LEAK FAMILY		CER		STD
LKMXR0130CEG	LKMXR0130CEG-B	D1	0.00		0.02
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxidi heated/oxygen sensor; WR-H RDQS: reductant quality sens secondary air injection (belt direct/indirect fuel injection; T fines on-board diagnostic; DC suffix: series; CNG/LNG: com E10: "10%" ethanol ("90%"ga continuously variable transmi	0#LVW; LDT3: LDT 600 duty vehicle; MDV4: ME ': heavy-duty vehicle; E0 vehicle weight rating; L' per ULEV; ZEV: zero-er lAC: HC adsorbing cata : selective catalytic redu izer; DPF: diesel particu tO2S or AFS: wide rang sor; NH3S: ammonia se driven)/(electric driven); 'C/SC: turbo/super char DR: direct ozone reducin ppressed/liquefied natur isoline) fuel; A: automat ission; SCV: selectable e transmission: OT: othe	D1-850 DV 850 CS: en VW: lo missio alyst; V uction- ilate fil ge/line ensor; PAIR: ger; C ng; HC ral gas ic (with contin er tran	00#GVWR,3751-5750 01-10000#GVWR; MI hission control systen baded vehicle weight; n vehicle; TZEV: tran VU: warm-up catalyst urea/ammonia; NH30 (ter (active); GPF: PM ar/heated air-fuel rativ EGR: exhaust gas re pulsed AIR; SFI/MFI AC: charge air cooler CT: hydrocarbon trap; ; LPG: liquefied petro h lockup); M: manual uously variable transi smission: AER: all-ele	J#ALVW; LD14: DV5: MDV 1000 n; CERT: certific ALVW: adjusted sitional ZEV; TV ; NAC: NOx ads DC: ammonia ox I filter for spark-io o sensor; NOXS circulation; EGR : sequential/mult ;; FFH: fuel fired BCAN: bleed ca bleum gas; E85: transmission; S mission; AM: au ectric range; EA	ignited engine; HO2S/O2S: :: NOX sensor; PMS: PM sensor; :C: EGR cooler; AIR/AIRE: tiport fuel injection; DFI/IFI: heater; F/P/\$: full/partial/partial with arbon canister; prefix 2: parallel; (2) "85%" ethanol ("15%"gasoline) fuel; A: semi-automatic transmission; CV: tomated manual transmission; AMS: ER: equivalent AER; PHEV: plug-in
2020	MODEL YEAR	: VE	EHICLE MOD	ELS INFO	RMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
KIA	FORTE	PC	2.0	CV1,M6	LKMXR0130CEG	1	F
KIA	FORTE 5	PC	2.0	CV1	LKMXR0130CEG	1	F
KIA	FORTE FE	PC	2.0	CV1	LKMXR0130CEG	1	F

.