(A)	CALIFORNIA AIR RESOURCES BOARD	
AA	CALL ONNIA	
- 117 - 1 1 7	AIR RESOURCES SOARD	

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

9-1 1					TEST GRO		IFOR	MATION							
MODE		EST GROUP		VEHICI	_E CLASS(E	S)		FUEL CATEGORY			FUEL TYPE				
2020) LI	MXV02.0DG5		PC DEDICATED SINGLE FUEL GASOL:						GASOLINE					
	USEFU	LIFE (miles)		VEH	ICLE EMISS	ION C	ATEGORY INTERIM / INTE				TERMEDIATE IN-USE STD				
EX	H/ORVR	EVAP		FTP SFTP FTP							SFTP				
1	50000	150000		LEV3	ULEV70	70 LEV 3 COMPOSITE PM					PM				
SPE	SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								TATUS	E	ENGINE DISPLACEMENT (L)				
1	DF	I, WR-HO2S,	IO2S,	WU-TWC,	TC, CAC			FULL	*	1					
*			*				P	ARTIAL	ALL MODELS	11	2.0				
*			*	PARTIAL WITH * FINES											
		E	APOF	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	(INFORMATION	1					
EVA	AP / OR	R FAMILY	EVAF	PORATIVE	STD CATE	GORY			SSION STD E CLASS	s	PECIAL FEATURES				
	LKMXR0	L40DGG		LEV 3	OPTION1			1	2C		нст				
				E	EMISSION C	REDIT		ORMATION							
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY											OPTIONAL EXH. STD FOR WORK TRUCKS				
		N			N			N N							
· · ·				NMOG	AND FLEET	Γ AVE	RAG	E INFORMA	TION						
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO	a serie serie se	O/NMHC RATIO	NMOG+NO PC+LDT ((g			press of sector and an an an an an and an							
*	*	1.10		*	0	.065			0.074		*				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this /6²⁴day of July 2019.

Allen Lyons, Chief Emissions Certification and Compliance Division



KIA MOTORS CORPORATION Executive Order: A-314-0338 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

		UEL TY	PE														
					OG+N((g/mi)	Эх		CO (g/mi)			NOx g/mi)		HCH mg/r			PN (g/m	
				CERT	. 5	STD	CER	r st	D	CERT	STD	CER	т	STD	CER	т	STD
FTP@5	ok	*		*		*	*	*		*	*	*		*	*		*
FTP@L		ASOLIN IER3 E		0.046	5 0.	.070	0.6	1.	7	*	*	*		4	0.00)1	0.003
50°F @4	1 1 2 1	ASOLIN IER3 E	August 1997	0.046	5 0.	.140	0.4	1.	7	*	*	*		16			
					EUE	L TYP	E			1	MOG+N	Ox (g/mi)			CO (g	/mi)	
					FUE	LITP	E			С	ERT	STD		CERT STD			
HWFE	Т @ 50	к				*					*	*					
HWFE	T @ U	L		GAS	OLINE	-TIEF	X3 E10			0	.021	0.070)				
20°F	@ 50K							E (TIEF			de sanse			0.6	;	1	.0.0
			S	FTP E	XHAU			STAND	ARDS	AND		ATION LI	EVEL				
					-		JS06				SC03				MPOS		
	FUEL	TYPE			OG+N((g/mi)	Dx	CO (g/mi)		M /mi))G+NOx g/mi)	CO (g/mi)		OG+NO: (g/mi)		O mi)	PM (mg/mi)
@ 4K		+	CERT		*		*				*	*					
@ 4K			STD		*		*				*	*					
		2	CERT		*		*	:	3		*	*	(0.048	048 0.9		*
@ UL		LINE- 3 E10	STD		*		*		6		*	*	0	0.083	.083 4.2		*
			BIN											0.070			
		WH	IOLE VI	EHICL	E EVA	PORA	TIVE E	MISSION	STAN	DAR	DS AND	CERTIFIC	ATIO	N LEVE	LS		
						W	HOLE V	EHICLE	EVAP	ORAT	IVE TES	FING					
			UEL T	/PE	30	OHS (g	/test) @) UL		2DH	IS (g/test) @ UL		R	L (g/m	i) @	UL
					CER	T S	STD	FEL	CE	RT	STD	FEL	_	CERT S		STD	
LKMXF	R0140E	DCC I	SASOLII LEV3 E		0.25	8 0.	350	*	0.2	87	0.350	*		0.02		0.05	
C	DRVR	FUEL	ONLY /	CANIS	STER I	BLEED	EVAP	ORATIVE	EEMIS	SION	STANDA		D CEI	RTIFICA	TION L	EVE	LS
									Fl	JEL O	NLY EVA	P & CAN	ISTE	R BLEE	כ		
		IVE	ORVR	(g/gall	lon) @	UL	FUE	FUEL TYPE		3DHS RIG TEST (g/test) @ UL		2DHS RIG T (g/test) @				D CANISTER (g/test) @ 4K	
81		FL	JEL TYP	PE C	ERT	STD	1			RT	STD	CERT		STD	CER	r	STD
LKMXF	R0140E		SOLINI		. 02	0.20		OLINE- 3 E10	0	. 0	0.0	0.0		0.0	*	* *	

CALI AIR RESO	CALIFORNIA AIR RESOURCES BOARD			CALIFORNIA CORPORATION			New Pas	Executive Order: A-314-0338 Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4			
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)											
EVAPORATIVE FAMILY	LEAK FAMILY		CERT		STD						
LKMXR0140DGG	LKMXR0140DGG-J	F1	0.02		0.02						
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: su ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxidi heated/oxygen sensor; WR-H RDQS: reductant quality sens secondary air injection (belt d direct/indirect fuel injection; T fines on-board diagnostic; Do suffix: series; CNG/LNG: com E10: "10%" ethanol ("90%"ga	0#LVW; LDT3: LDT 600 duty vehicle; MDV4: MI : heavy-duty vehicle; E0 vehicle weight rating; L per ULEV; ZEV: zero-en IAC: HC adsorbing cata : selective catalytic redu zer; DPF: diesel particu (O2S or AFS: wide rang sor; NH3S: ammonia se Iriven)/(electric driven); C/SC: turbo/super char DR: direct ozone reducin pressed/liquefied natur soline) fuel; A: automat ssion; SCV: selectable a transmission: OT: othe	01-850 DV 850 CS: en VW: lo missio alyst; V uction- ulate fil ge/line ensor; PAIR: rger; C ng; HC ral gas cic (wit contin	00#GVWR,3751-5750 01-10000#GVWR; MI nission control system baded vehicle weight; n vehicle; TZEV: tran VU: warm-up catalyst -urea/ammonia; NH30 lter (active); GPF: PM ar/heated air-fuel rativ EGR: exhaust gas re pulsed AIR; SFI/MFI AC: charge air cooler CT: hydrocarbon trap; ;; LPG: liquefied petro h lockup); M: manual uously variable trans smission: AER: all-ele	J#ALVW; LD14: DV5: MDV 1000 n; CERT: certific ALVW: adjusted sitional ZEV; TV ;; NAC: NOx ads DC: ammonia ox 1 filter for spark-i o sensor; NOXS circulation; EGR : sequential/mult r; FFH: fuel fired BCAN: bleed ca bleum gas; E85: transmission; S mission; AM: au ectric range; EA	ignited engine; HO2S/O2S: :: NOX sensor; PMS: PM sensor; C: EGR cooler; AIR/AIRE: tiport fuel injection; DFI/IFI: heater; F/P/\$: full/partial/partial with arbon canister; prefix 2: parallel; (2) "85%" ethanol ("15%"gasoline) fuel; A: semi-automatic transmission; CV: tomated manual transmission; AMS: ER: equivalent AER; PHEV: plug-in						
2020	MODEL YEAR	: VE	EHICLE MOD	ELS INFO	RMATION						

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
KIA	OPTIMA	PC	2.0	SA6	LKMXR0140DGG	1	P

.