

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR 2020	TE	ST GROUP											
2020			VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE				
	LKM	XV01.6AB6		PC				SINGLE FUEL HICLE		GASOLINE			
USE	EFUL	LIFE (miles)		VEH	VEHICLE EMISSION CATEGORY					TER	RMEDIATE IN-USE STD		
EXH/OF	RVR	EVAP			FTP		SF	SFTP FTP			SFTP		
15000	00	150000		LEV3	ULEV125	LEV	3 C	OMPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD STATUS			ENGINE DISPLACEMENT		
1 SFI, WR-HO2S, HO2S, WU-TWC, TWC, EGR, EGRC								FULL	ALL MODELS		1.6		
*	* *							PARTIAL	*				
*	*							TIAL WITH	*				
		َ E۱	APO	RATIVE &	REFUELING	(EVA	P/OF	RVR) FAMIL	INFORMATION	1			
EVAP /	ORVR	FAMILY	EVA	PORATIVE	STD CATE	GORY			SSION STD E CLASS	SPECIAL FEATURES			
LKM	XR011	OABG		LEV 3	3 OPTION2			F	DC .	-	HCT		
LKM	XR012	OABG		LEV 3	3 OPTION2			PC			HCT		
				E	EMISSION CI	REDIT		ORMATION					
CREDI	IT FOF	FLEET AVE. R EXTENDED RANTY			EDIT FOR N ZERO-EVAP	DIT FOR NON-PZEV RO-EVAP			REDIT FOR DOI	R OPTIONAL EXH. STD FOR WORK TRUCKS			
	1	N			N			N			N		
				NMOG	AND FLEET	<b>AVE</b>	RAG	E INFORMA	TION		S.		
	I NMOG/NMHC			IO/NMHC RATIO	C NMOG+NOX FLEET PC+LDT (0-3750 LV (g/mi)								
*	*	1.10		*		*			*		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of July 2019.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

LEV3 E10

## ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		~										
				DG+NOx CO g/mi) (g/mi)		-		Ox mi)		HCHO (mg/mi)		'M 'mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K		*	*	*	*	*	*	*	* *		*	*
FTP@UL		OLINE- R3 E10	0.062	0.125	0.2	2.1	*	*	*	4	· *	0.01
50°F @4K		OLINE- R3 E10	0.102	0.250	0.1	2.1	* .	. *	*	16		
i ja i	- 24		r	FUEL TYP			N	IOG+N	CO (g/mi	CO (g/mi)		
5				E	CE	RT	STD	CER	RT	STD		
HWFET @ 50K *			*				ł	*				
HWFET @ UL		GASOLINE-TIER3 E10				0.0	0.032 0.125			a second and a second sec	1. Ja - 1	
20°F @ 5	50K	COLD (	CO E10 RI	EGULAR G	ASOLINE	ASOLINE (TIER3)				0.3	0.3 10.0	

### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			51		AUAOOI	LINICOION	UTAND	ANDO		OLIVIII IO			0			
s						US06	0			SC03	0		COM	IPOSIT	Έ	
	FUEL TY	PE			OG+NOx (g/mi)	CO (g/mi)		PM g/mi)		DG+NOx g/mi)	CO (g/mi)		OG+NOx g/mi)	CO (g/m		PM ng/mi)
@ 4K	@ 4K *		CERT		*	*				* *		906 ( (			1941 - A. •	lan. Ar
0			STD		*	*		- 7- 18		*	*		agas na "nana" ja		2 * 2 *	
			CERT		*	*	* *		*		*	0	0.067			*
@ UL	@ UL GASOLIN TIER3 E	I SID		*		*		*		*	*	0	0.083			*
			BIN		1 						an a	(				<b>S</b> ar
		WH	OLE VE	HICL	E EVAPO	ORATIVE E	MISSION	N STAN	IDAR	DS AND C	ERTIFIC	CATIO	N LEVELS	i .		
						WHOLE \	/EHICLE	EVAP	ORA	<b>FIVE TEST</b>	ING					
	EVAPORATIVE FAMILY		FUEL TYPE		3DH	S (g/test) (	(g/test) @ UL			2DHS (g/test) @ UL			RL (g/mi) @ UL			
					CERT	STD	FEL	CEF	RT	STD	FE	FEL		CERT		D
LKMXF	LKMXR0110ABG		ASOLIN LEV3 E	10 230 1		0.300	*	0.2	0.255 0.		*		0.01	0.0		05
LKMXF	R0120ABG		ASOLIN		0.230	0.300	*	0.2	55	0.300	*		0.01		0.0	05

A	CALII Ir reso	FORN URCES B	<b>NIA</b> Oard				ſ	Executive Order: A-314-0340 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4					
ORVR / FUI	EL ONLY /	CANISTER	BLEED	EVAPO	RATIVE	EMISSION	STANDA	RDS A	ND CERTIF	CATION LEV	/ELS		
			FUEL ONLY EVAP & CANISTER BLEED										
EVAPORATIVE FAMILY	ORVR (	(g/gallon) @ UL		FUEL	TYPE		3DHS RIG TEST (g/test) @ UL		S RIG TES test) @ UL		CANISTER test) @ 4K		
	FUEL TYP	E CERT	STD			CERT	STD	CER	T STD	CERT	STD		
LKMXR0120ABG	GASOLINE TIER3 E1	1 0 01	0.20	GASOLINE- LEV3 E10		*	*	*	*	0.003	0.020		
LKMXR0110ABG	GASOLINE TIER3 E1	.0 0.01	0.20	GASOLINE- LEV3 E10		*	*	*	*	0.003	0.020		
E	EFFECTIV	E LEAK D	IAMETE	ER STA	NDAR	D AND CE	RTIFICA	TION L	EVEL (IN	CHES)			
EVAPORATIVE	FAMILY	LEA	K FAMIL	LY CERT			RT	Г			STD		
LKMXR0120	ABG	LHYXR0	120ABG-	-нс1 0.00			00				-		
LKMXR0110	ABG	LHYXR0	110ABG-	-HC1 0.00					0.02				
*: not applicable; # LDT<6000#GVWR 8500#ALVW; MDV duty passenger ve emission limit; GV ULEV: ultra LEV; S ADSTWC: adsorbi SCRC/SCR-N or S continuous/periodi heated/oxygen ser RDQS: reductant of secondary air inject direct/indirect fuel fines on-board diag suffix: series; CNG E10: "10%" ethano continuously varial automated manual hybrid electric vehi some/select mode	2,3751-5750 /: medium-o hicle; HDV: WR: gross v SULEV: sup ng TWC; HA SCRC-NH3: c trap oxidiz trap oxidiz trap oxidiz sor; WR-H4 quality sense transmis function; TO gnostic; DO GLNG: comp of ("90%"gas ble transmis l-selectable icle; NMOG	#LVW; LD luty vehicle heavy-duty vehicle weig er ULEV; Z AC: HC ads selective c cer; DPF: di O2S or AFS or; NH3S: a tiven)/(elect C/SC: turbo R: direct oz pressed/liqu soline) fuel; sion; SCV: transmission	T3: LDT 6 ; MDV4: I vehicle; pht rating; EV: zero- corbing ca atalytic re esel parti S: wide ra mmonia ric driven /super ch vone redu uefied nat A: autom selectab	5001-850 MDV 850 ECS: en LVW: lo -emission atalyst; V eduction- iculate fil nge/line: sensor; l ); PAIR: arger; C cing; HC tural gas hatic (with le contin ther trans	00#GVW 01-1000 nission ( paded ven n vehicle VU: war urea/an iter (acti ar/heate EGR: e) pulsed AC: cha C:	VR,3751-57 0#GVWR; I control syste ahicle weigh e; TZEV: tra m-up cataly monia; NH ve); GPF: F ad air-fuel ra khaust gas AIR; SFI/M arge air cool occarbon tra iquefied pet b); M: manu variable trar n; AER: all-	50#ALVW MDV5: MD em; CERT ht; ALVW: ansitional 2 fst; NAC: N 30C: amn PM filter for atio sensor recirculatio FI: sequen ler; FFH: fit p; BCAN: I troleum ga al transmis semission; electric rar	; LDT4: V 1000 : certific adjustec ZEV; TV IOx ads nonia ox spark-i ; NOXS on; EGR tial/mult uel fired bleed ca s; E85: ssion; S. AM: au nge; EAI	LDT 6001-8 1-14000#GV ation; STD: d LVW; LEV /C/OC: 3-wa orption cata gnited engir : NOx senso C: EGR coo iport fuel inj heater; F/P arbon canist "85%" ethar A: semi-auto tomated ma ER: equivale	500#GVWR; { WR; MDPV: standard; FEI low emissior ay/oxidizing ca lyst; SCR-U o lyst; CTOX/P le; HO2S/O2S or; PMS: PM s ler; AIR/AIRE ection; DFI/IF \$: full/partial/ ar; prefix 2: pa ol ("15%"gas- matic transmis- nual transmisent AER; PHE	5751- medium- L: family n vehicle; atalyst; TOX: S: Sensor; E: I: partial with arallel; (2) oline) fuel; ission; CV: sion; AMS:		

# 2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	
KIA	RIO	PC	1.6	CV1,M6	LKMXR0110ABG	1	F	
KIA	RIO	PC	1.6	CV1,M6	LKMXR0120ABG	1	F	