

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GROUI		MATION				
MODE		EST GROUP	VEHIC	VEHICLE CLASS(ES)			ATEGORY	FUEL TYPE		
2020	2020 LASXV05.2AM5			PC			SINGLE FUEL HICLE	GASOLINE		
	USEFUL	LIFE (miles)	VEH	ICLE EMISSIO	N CATE	GORY	INTERIM / IN	TERMEDIATE IN-USE STD		
EX	I/ORVR	EVAP		FTP	SF	TP	FTP	SFTP		
1!	150000 150000		CERTI LEV3 U	LEV OPTION IFYING TO LEV 2 SF1 JLEV NMOG+ STANDARD NOX						
SPE	ECIAL FE		HAUST EMISSI	ON CONTROL		OBD S	TATUS	ENGINE DISPLACEMENT (L)		
1	2WU-TWO		R-H02S, 2H02S FI, AIR	, 2TC, 2CAC,		FULL	*			
*			*		I	PARTIAL	ALL MODELS	5.2		
*			*	PARTIAL WITH *						
		E	VAPORATIVE &	REFUELING (E	VAP/OF	RVR) FAMIL	INFORMATIO	N		
EVA	AP / ORV	R FAMILY	EVAPORATIV	E STD CATEGO	RY		SSION STD E CLASS	SPECIAL FEATURES		
	LASXR01	60P1Y	L	EV 2		F	рс	*		
				EMISSION CRE	DIT INF	ORMATION				
					DIT FOR NON-PZEV RO-EVAP			R OPTIONAL EXH. STD FOR WORK TRUCKS		
NN							N	N		
			NMOG	AND FLEET A	VERAG	E INFORMA	TION			
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO	HCHO/NMHC RATIO	NMOG+NOX PC+LDT (0-3 (g/m	3750 LV					
*	*	1.04	*	0.1	25		0.125	*		
See th	e Attach	ment for Vehi	cle Models, Ev	aporative Fam	ily, Eng	ine Displace	ement, Emissio	n Control Systems, Phase-		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



ASTON MARTIN LAGONDA LIMITED Executive Order: A-098-0061 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____/3 __ day of April 2019.

lico

Allen Lvons, Chief Emissions Compliance, Automotive Regulations and Science Division



	trong v MCM + (7W/YC)		017 A.F	NT 4.9	104 AV
an an an ann an Anna an Anna an Anna		421.0			
eu in aneada color	Capital Instrument Childs (Child	副原则于 的复数手动力的空气动	A sought of	$d(1/2) q_{ij}^{\ell}(t_i, \dots, \tilde{A}_{\ell}^{\ell+1})$	1.8344 234 832
	scheine auf bind jate eine				
	nac e la regró aviturgal ar s Alexiencia d'Alexientes e se				

网络达莱 信托查查



UNLEADED

FUEL TYPE

ASTON MARTIN LAGONDA LIMITED Executive Order: A-098-0061 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

											· · · · · · · · · · · · · · · · · · ·	
			NMOG (g/I	i+NOx mi)		O mi)	N((g/i		HC (mg			PM /mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K		*	*	*	*	*	*	*	*	*	*	*
FTP@UL	T	DLINE - IER 2 LEADED	0.0598	0.125	1.08	2.1	*	*	*	11	*	0.01
50°F @4K	T	DLINE - IER 2 LEADED	0.079	0.250	0.84	2.1	*	*	*	16		
		FUEL TYPE						NMOG+NOx (g/mi)		CO (g/mi)		
								RT	STD	CER	T I	STD
HWFET @ 50K		*							*	i ingele Kanvasela		
HWFET (DUL		GASOLINE	- TIER 2	2 UNLEAD	ED	0.0	070	0.125			
20°F @	50K		GASOLINE	- TIER 2	2 UNLEAD	ED	interties.	Martin 1	entine seu	1.6	0	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

		"我们的"		US06			SC03			COMPOSITE		
	FUEL TYPI	E Contraction	NMHC+NOx (g/mi)	CO (g/mi)			IHC+NOx (g/mi)	CO (g/mi))G+NOx g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	GASOLINE TIER 2 UNLEADED	CERT	0.046	0.73			0.031	0.59				
Ŭ		STD	0.14	8.0			0.20	2.7		ie obsta	过去的时候	1. 建富达了
		CERT	*	*		t i	*	*	0.	.0455	*	*
@ UL	GASOLINE TIER 2 UNLEADED	STD	*	*		• .	*	*	0	.083	*	. *
		BIN						an a	0	.070		
	V	HOLE VE	EHICLE EVAPO	DRATIVE E	MISSION	STANDA	RDS AND O	CERTIFIC	ATIO	N LEVELS		
				WHOLE V	EHICLE	EVAPORA	TIVE TEST	TING				
EVAPORATIVE FAMILY				3DHS (g/test) @ UL			2DHS (g/test) @ UL			RL (g/mi) @ UL		
			CERT	STD	FEL	CERT	STD	FE	L	CERT		STD
LASXI	R0160P1Y	GASOLIN TIER		0.50	*	0.49	0.65	*		0.00		0.05

AA?	CALIF		NIA OARD	ASTON LAGONDA	Ν	Executive Order: A-098-0061 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4								
ORVR / FU	EL ONLY / CA	NISTER	BLEED	EVAPORATIVE	EMISSION	STANDA	RDS AND	CERTIFIC	ATION LEV	'ELS				
				i a distante e trade e	FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL		FUEL TYPE	3DHS RIG TEST (g/test) @ UL		and the second sec	IG TEST) @ UL	BLEED CANISTER TEST (g/test) @ 4K						
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD				
LASXR0160P1Y	GASOLINE - TIER 2 UNLEADED	0.01	0.20	**************************************			97.51 (* 1997) 1973 - * 1974 (* 1997) 1975 - 1975 (* 1997)		*	*				
	EFFECTIVE		DIAMET	ER STANDAR	D AND CE	RTIFICA	TION LEV	EL (INCH	HES)					
EVAPORATIVE	FAMILY	LEA	K FAMIL	Y	CE	RT			STD					
* *		*		r			*							
*: not applicable; # LDT<6000#GVWF 8500#ALVW; MD\ duty passenger ve	R,3751-5750#L /: medium-dut	.VW; LD vehicle	T3: LDT ; MDV4:	6001-8500#GVV MDV 8501-1000	VR,3751-57 0#GVWR; I	50#ALVW; MDV5: MD	LDT4: LD ⁻ V 10001-14	T 6001-850 4000#GVV	00#GVWR,5 VR; MDPV:	5751- medium-				

duty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
ASTON MARTIN	DB11 V12 AMR	PC	5.2	SA8	LASXR0160P1Y	1.1	P
ASTON MARTIN	DBS SUPERLEGGERA	PC	5.2	SA8	LASXR0160P1Y	1	P