

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	FOR	MATION					
MODE	T	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY	FUEL TYPE			
2020 LASXV04.0AES					PC DEDICATED SINGLE FUEL VEHICLE					GASOLINE			
USEFUL LIFE (miles)					ICLE EMISS	ION C	ATEC	GORY	INTERIM / INTERMEDIATE IN-USE ST				
EXH/ORVR EVAP					FTP SFTF			TP	FTP		SFTP		
150000 150000		0	CERTI LEV3 U	V2 ULEV OPTION CERTIFYING TO I CV3 ULEV NMOG+ NOX		LEV 2 SFTP STANDARD		*		*			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	ingittan and	ENGINE DISPLACEMENT (L)		
1 2WU-TWC, 2TWC, 2WR-H02S, 2H02S, DF 2CAC						2,		FULL	ALL MODELS	and a Colling of the			
*			*				ARTIAL	*		4.0			
*			*				TIAL WITH FINES	*					
		E	VAP	ORATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	(INFORMATIO	N			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GORY	,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
LASXR0160P1Y LEV 2							I	PC	*				
				E	EMISSION CR	REDIT	INFO	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ON-P	ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS		
N N					N				N		N		
				NMOG	AND FLEET	AVE	RAG	E INFORMA	TION				
NMOG RAF					0-375		V) LDT						
*	*	1.04		*	0	.125			0.125	*			
0	A.I. I		1.1	Manlala E.			Enni	na Dianta a		- 0	ontrol Systems Phase		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-098-0062 dated April 15, 2019.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_day of October 2019.

Allen Lyons, Chief Emissions Certification and Compliance Division

Æ	¥	A		A L Res	IFO	RN es boa	A		ASTON AGOND				E New Pass		tive Orde er Cars, Li Mo	ght-D	uty Tr -Duty	
	-							A	ГТАС	нм	ENT							
	E		and the second second	The second s									D CERT				ELS	
100-11-12	05722		EXH										(FTP, HV					
				monoxide; NOx: oxides adjustment factor; 2DHS ORVR [g HC/gallon disp			s of nitrogen; HCHO: fo HS/3DHS [g HC/test]: 2/ spensed]: on-board refu			formaldehyde; PM: particula 2/3 days diurnal+hot-soak; F				_ [g HC/mi]: running loss; m; mg: milligram; mi: mile; K:				
				NMOG+NOx (g/mi)			CO (g/mi)			NOx (g/mi)			HCH (mg/r			PM (g/mi)		
				- F	CERT	<u> </u>		CERT			CERT	STD			STD	CE		STD
FTP@5	ок		*		*	*		*	*		*	*	*	+	*		* *	
FTP@l			LINE ER 2 EADE	2	0.064	2 0.1	25	0.43	2.	1	*	*	*		11	*		0.01
50°F @	4K		LINE ER 2 EADE	2	0.072	4 0.2	50	0.12	2.	1	*	*	*		16			
- Fill						FUEL	TYPE		(A)				Ox (g/mi)			CO (		
加速時											CI	ERT	- Unitation application areas			T	STD	
HWFE						4						*	*		na pangangangan Nasir pangangangan Nasir pangangangangan	Side, G		验。期代1月6日 和书代代刊
HWFE	т @	UL		G	ASOLIN	E - TI	ER 2	UNLEA	DED	ť.	0.0	0153	0.12	5				
20°F	@ 5	0K		G	ASOLIN	E - TI	ER 2	UNLEA	DED		明峰海				0.2	7,	1	0.0
AN	-			-	SFTP E	XHAUSI			STAND	ARDS	AND C	ERTIFIC	ATION L	EVE				
	2					US06				<u>,</u> ,	SC03			COMPOSITE				
	FU					CO g/mi)			NMHC+NOx (g/mi)		1		MOG+NOx (g/mi)		CO /mi)	PM (mg/mi)		
GASOLINE TIER 2 @ 4K UNLEADED		TIER 2		C	0.19			0.029		0.7								
		ST		STD		0.14		8.0	74-16 		0	.20	2.7	2.7				
	<b>-</b>			CER	RT *			* *		*		*	*	* 0			*	*
@ UL		SOLINE - FIER 2 ST NLEADED		STE	D *			* *		*		* .	*	* (			*	*
				BIN	和原理社会和自然问题		議會議				1000			-	0.070	ない語		
			WH	OLE	VEHICL	E EVAP							CERTIFIC	ATIC	N LEVE	S		
EVAP			F	UELI	TYPE	3DH		OLE VE est) @		EVAP			/E TESTING (g/test) @ UL		_   R	L (g/n	1i) @	UL
Γ <i>Ρ</i>		. 1				CERT	ST	D	FEL	CE			FEL		CFRT			STD
LASXR	101 <i>6</i>	50P1Y		ASOLI TIEF JNLEA	2	0.39	0.1		*	0.4		0.65	*		0.00		0.05	

AN	CALIF			ASTÓN LAGOND	٢	Executive Order: A-098-0062-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4							
ORVR / FU	EL ONLY / CA	NISTER	BLEED	EVAPORATIVE	EMISSION	STANDA	RDS AND	CERTIFIC	ATION LEV	ELS			
				813 A 1898	FUEL C	NLY EVA		NISTER BLEED					
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE		IG TEST ) @ UL		IG TEST ) @ UL	TEST (g/t	ANISTER est) @ 4K			
	FUEL TYPE	E CERT STD		and an and a second	CERT	STD	CERT	STD	CERT	STD			
LASXR0160P1Y	UNLEADED		1	1997 - 1997 -		* *	αιμα 146 μ τους 14 μ τους		*	*			
	EFFECTIVE		DIAMET	ER STANDAR	D AND CE	RTIFICA	TION LEV	EL (INC	HES)				
EVAPORATIVE FAMILY		LEA	K FAMIL	Y	CE	RT	a barta la	STD					
*			* -		-	•			*	<b>STD</b> * .0-3750#LVW; LDT2:			
LDT<6000#GVWI 8500#ALVW; MD duty passenger ve emission limit; GV ULEV: ultra LEV; ADSTWC: adsorb SCRC/SCR-N or	R,3751-5750#L V: medium-dut ehicle; HDV: he WR: gross veh SULEV: super ing TWC; HAC SCRC-NH3: se SCRC-NH3: se	-VW; LD y vehicle avy-duty nicle weig ULEV; Z : HC ad elective c	T3: LDT ; MDV4: y vehicle; ght rating (EV: zero sorbing c atalytic r	6001-8500#GVV MDV 8501-1000 ECS: emission ; LVW: loaded v -emission vehic atalyst: WU: wa	WR,3751-57 00#GVWR; control syst rehicle weig le; TZEV: tr rm-up cataly mmonia; NH tive): GPF: I	MDV5: MD em; CERT ht; ALVW: ansitional 2 vst; NAC: N I3OC: amn PM filter fol	; LD14: LD V 10001-1 : certificatio adjusted LV ZEV; TWC/ NOx adsorp nonia oxida	4000#GVV on; STD: si /W; LEV: I OC: 3-way tion cataly tion cataly ted engine	VR; MDPV: andard; FEI ow emissior /oxidizing ca st; SCR-U o st; CTOX/P	medium- _: family n vehicle; atalyst; r			

<b>2020 MODEL</b>	. YEAR: VEHICLE MODELS INFORMATION	e.
		-

MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
DB11 V8	PC	4.0	SA8	LASXR0160P1Y	1	F
VANTAGE	PC	4.0	M7	LASXR0160P1Y	1	F
VANTAGE V8	PC	4.0	SA8	LASXR0160P1Y	1	F
VANIAGE VO		1.0	1			
	DB11 V8 VANTAGE VANTAGE V8	DB11 V8 PC VANTAGE PC VANTAGE V8 PC	DB11 V8PC4.0VANTAGEPC4.0VANTAGE V8PC4.0	DB11 V8PC4.0SA8VANTAGEPC4.0M7VANTAGE V8PC4.0SA8	MODELVEH CLASSENGINE (L)TRANS TYPEFAMILYDB11 V8PC4.0SA8LASXR0160P1YVANTAGEPC4.0M7LASXR0160P1YVANTAGE V8PC4.0SA8LASXR0160P1Y	MODELVEH CLASSENGINE (L)TRANS TYPEFAMILYECSDB11 V8PC4.0SA8LASXR0160P1Y1VANTAGEPC4.0M7LASXR0160P1Y1VANTAGE V8PC4.0SA8LASXR0160P1Y1

Z = 2 [2] 1.1 (2) 240 (2)