

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| TEST GROUP INFORMATION                                |   |                |      |                                     |            |        |   |                    |  |  |                           |  |  |
|---|---|----------------|------|-------------------------------------|------------|--------|---|--------------------|--|--|---------------------------|--|--|
| MOD<br>YEA  |   | EST GROUP      |      | VEHIC                               | LE CLASS(E | S)     |   | FUEL C             | ATEGORY  |  | FUEL TYPE                 |  |  |
| 202   | LJLXT03.0HTR LDT4   |                |      |                                     |            |        | 1   |                    | SINGLE FUEL<br>HICLE                                     |  | GASOLINE                  |  |  |
|   | USEFU   | L LIFE (miles) |      | VEH                                 | ICLE EMISS | ION C  | ATEC  | GORY               | INTERIM / IN   | TER                                    | MEDIATE IN-USE STD        |  |  |
| EX  | H/ORVR  | EVAP           |      |                                     | FTP        |        | SF  | ГР                 | FTP  |  | SFTP                      |  |  |
| 1   | 50000   | 150000         |      | LEV3                                | SULEV30    |        |   | SULEV<br>ALONE     | NMOG+NOX   |  | *                         |  |  |
| SPECIAL FEATURES & EXHAUST EMISSION CONTRO<br>SYSTEMS |   |                |      |                                     |            | L      |   | OBD S              | TATUS  | Contraction of the local data          | NGINE DISPLACEMENT<br>(L) |  |  |
| 1   | DF  | I, TWC, TC,    | CAC, | WR-H02S,                            | HO2S(2)    | 200    |   | FULL               | ALL MODELS   | State State                            |                           |  |  |
| *   |   |                | *    |                                     |            | 調子の調査  | P   | ARTIAL             | *  | Sector Sector                          | 3.0                       |  |  |
| *   | * *   |                |      |                                     |            |        |   | TIAL WITH<br>FINES | *  |  |                           |  |  |
|   |   | E              | APO  | RATIVE &                            | REFUELING  | (EVA   | P/OR  | VR) FAMIL          | (INFORMATIO  | N                                      |                           |  |  |
| EV  | AP / OR\  | R FAMILY       | EVA  | PORATIVE                            | E STD CATE | GORY   | EVAP EMISSION STD<br>VEHICLE CLASS                            |                    |  | S                                      | SPECIAL FEATURES          |  |  |
|   | LJLXR0  | 175P1Z         |      | LEV 3 OPTION2                       |            |        | LDT4  |                    |  | *                                      |                           |  |  |
|   |   |                |      | E                                   | EMISSION C | REDIT  | INFC  | RMATION            |  |  |                           |  |  |
|   | NMOG+NOX FLEET AVE.<br>CREDIT FOR EXTENDED<br>WARRANTY<br>XERO-EVAP |                |      |                                     |            |        | NMOG CREDITEOR DO   |                    |  | R OPTIONAL EXH. STD<br>FOR WORK TRUCKS |                           |  |  |
|   | N N   |                |      |                                     |            |        |   | -                  | N  |  | N                         |  |  |
|   | NMOG AND FLEET AVERAGE INFORMATION                                  |                |      |                                     |            |        |   |                    |  |  |                           |  |  |
| NMOO<br>RAF   | RAE RAE NMOG/NMHC RATIO PC+LDT (0                                   |                |      | X FLEET STD<br>0-3750 LVW)<br>g/mi) |            | /) LDT | NMOG+NOX FLEET ST<br>LDT (3751 LVW-8500<br>GVWR) + MDPV (g/mi |                    | NMOG+NOX FLEET STD<br>MDV (10,001-14,000<br>GVWR) (g/mi) |  |                           |  |  |
| *   | *   | 1.10           |      | 0.02                                | 0          | .065   |   |                    | 0.074  |  | *                         |  |  |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

#### BE IT FURTHER RESOLVED:

The listed vehicle models have been certified on the condition that the manufacturer provide all the on-board diagnostic data required by 13 CCR Section 1968.2(h)(1) by January 20, 2020. Failure to submit the required demonstration data by the specified date, or failure of the submitted demonstration data to show compliance with the test procedures, shall be cause for the Air Resources Board to revoke this Executive Order and vehicles sold under the revoked conditional certification shall be deemed uncertified.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-409-0070 dated August 28, 2019.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 1077 day of January 2020.

Allen Eyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

20°F @ 50K

0.94

12.5

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

|             |      |                  | NMOG+NOx<br>(g/mi) |          | CO<br>(g/mi) |     |      | NOx<br>(g/mi)   |       | HCHO<br>(mg/mi) |           | M<br>mi) |  |
|-------------|------|------------------|--------------------|----------|--------------|-----|------|-----------------|-------|-----------------|-----------|----------|--|
|             |      |                  | CERT               | STD      | CERT         | STD | CERT | STD             | CERT  | STD             | CERT      | STD      |  |
| FTP@50K     |      | *                | *                  | *        | *            | *   | *    | *               | *     | *               | *         | *        |  |
| FTP@UL      |      | OLINE-<br>73 E10 | 0.0237             | 0.030    | 0.91         | 1.0 | *    | *               | 0.00  | 4               | 0.001     | 0.003    |  |
| 50°F @4K    |      | OLINE-<br>73 E10 | 0.0275             | 0.060    | 0.62         | 1.0 | *    | *               | 0.0   | 8               |           |          |  |
|             |      |                  | FUEL TYPE          |          |              |     |      | NMOG+NOx (g/mi) |       |                 | CO (g/mi) |          |  |
|             |      |                  |                    | CE       | RT           | STD | CER  | RT              | STD   |                 |           |          |  |
| HWFET @ 50K |      |                  | *                  |          |              |     |      |                 | *     |                 |           |          |  |
| HWFET @     | @ UL |                  | GASO               | LINE-LEV | 3 E10        |     | 0.0  | 03              | 0.030 |                 |           |          |  |

# SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

GASOLINE-LEV3 E10

|      |                       |      |                    | US06         |               | SC03               | 3            | COMPOSITE          |              |  |
|------|-----------------------|------|--------------------|--------------|---------------|--------------------|--------------|--------------------|--------------|--|
|      | FUEL TYPE             |      | NMOG+NOx<br>(g/mi) | CO<br>(g/mi) | PM<br>(mg/mi) | NMOG+NOx<br>(g/mi) | CO<br>(g/mi) | NMOG+NOx<br>(g/mi) | CO<br>(g/mi) | PM<br>(mg/mi)  |
| @ 4K | *                     | CERT | *                  | *            |               | *                  | *            |                    |              |  |
|      |                       | STD  | *                  | *            |               | *                  | *            |                    |              |  |
|      |                       | CERT | 0.0187             | 0.69         | 3.3           | 0.0105             | 0.27         | *                  | *            | *  |
| @ UL | GASOLINE-<br>LEV3 E10 | STD  | 0.050              | 9.6          | 6             | 0.020              | 3.2          | *                  | *            | *  |
|      |                       | BIN  |                    |              |               |                    |              | *                  |              | and a second sec |

# WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

|                       |   |                      | WH        | IOLE \                          |                  |               |       |                |        |               |            |  |
|-----------------------|---|----------------------|-----------|---------------------------------|------------------|---------------|-------|----------------|--------|---------------|------------|--|
| EVAPORATIVE<br>FAMILY | FUEL TYPE   | 3                    | DHS (g    | /test) @                        | DUL              | 2Dł           | 1     | RL (g/mi) @ UL |        |               |            |  |
|                       |   | CER                  | CERT      |                                 | FEL              | CERT          | STD   | FEL            | CE     | RT            | STD        |  |
| LJLXR0175P1Z          | GASOLINE-<br>LEV3 E10   | 0.29                 | 0.298 0.5 |                                 | *                | *             | 0.500 | *              | 0.     | 00            | 0.05       |  |
| ORVR / FU             | ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS |                      |           |                                 |                  |               |       |                |        |               |            |  |
|                       |   |                      |           | FUEL ONLY EVAP & CANISTER BLEED |                  |               |       |                |        |               |            |  |
| EVAPORATIVE           | ORVR (g/g   | ORVR (g/gallon) @ UL |           |                                 |                  | 3DHS RIG TEST |       | 2DHS RIG TEST  |        | BLEED CANISTE |            |  |
| FAMILY                |   |                      |           | FUEL TYPE                       |                  | (g/test       | )@UL  | (g/test        | ) @ UL | TEST (g/      | test) @ 4K |  |
|                       | FUEL TYPE   | CERT                 | STD       |                                 |                  | CERT          | STD   | CERT           | STD    | CERT          | STD        |  |
| LJLXR0175P1Z          | GASOLINE -<br>TIER 2<br>UNLEADED  | 0.01                 | 0.20      |                                 | OLINE-<br>73 E10 | *             | *     | *              | *      | 0.010         | 0.020      |  |

| CALI<br>AIR RESC  | FORNIA<br>urces board  | JAGI  | JAR LAND ROVER<br>LIMITED  | Executive Order: A-409-0070-1<br>New Passenger Cars, Light-Duty Trucks and<br>Medium-Duty Vehicles<br>Page 4 of 4   |  |  |  |  |  |  |  |
|---|--|---|--|---|--|--|--|--|--|--|--|
| EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)   |  |   |  |   |  |  |  |  |  |  |  |
| EVAPORATIVE FAMILY  | EVAPORATIVE FAMILY LEAK FAMILY   |   | CERT   | Г   | STD  |  |  |  |  |  |  |
| LJLXR0175P1Z  | LJLXR0175P1Z-0   | 01  | *  |   | 0.02   |  |  |  |  |  |  |
| LDT<6000#GVWR,3751-575<br>8500#ALVW; MDV: medium-<br>duty passenger vehicle; HDV<br>emission limit; GVWR: gross<br>ULEV: ultra LEV; SULEV: su<br>ADSTWC: adsorbing TWC; H<br>SCRC/SCR-N or SCRC-NH3<br>continuous/periodic trap oxid<br>heated/oxygen sensor; WR-H<br>RDQS: reductant quality sen<br>EGRC: EGR cooler; AIR/AIR<br>fuel injection; DFI/IFI: direct/i<br>full/partial/partial with fines of<br>prefix 2: parallel; (2) suffix: set<br>device (ex. DPF-SCRC: SCF<br>ethanol ("15%"gasoline) fuel;<br>-automatic transmission; CV | 0#LVW; LDT3: LDT 600<br>duty vehicle; MDV4: MD<br>: heavy-duty vehicle; E0<br>vehicle weight rating; L'<br>per ULEV; ZEV: zero-en<br>IAC: HC adsorbing cata<br>: selective catalytic redu<br>izer; DPF: diesel particu<br>4028 or AFS: wide rang<br>sor; NH3S: ammonia se<br>E: secondary air injection<br>no-board diagnostic; DOF<br>eries; a hyphen (-) betwu<br>& coated DPF); CNG/LN<br>E10: "10%" ethanol ("9<br>continuously variable tu<br>ion; AMS: automated m<br>V: plug-in hybrid electric | 01-850<br>V 850<br>CS: en<br>VW: lo<br>nission<br>lyst; V<br>uction-<br>late fil<br>ge/linea<br>ensor; l<br>on (bel-<br>C/SC: t<br>R: direct<br>een aff<br>G: cor<br>0%"ga<br>ransmi<br>anual | 0#GVWR,3751-5750<br>11-10000#GVWR; ME<br>hission control system<br>aded vehicle weight;<br>h vehicle; TZEV: trans<br>VU: warm-up catalyst<br>urea/ammonia; NH30<br>ter (active); GPF: PM<br>ar/heated air-fuel ratio<br>EGR: exhaust gas reacher<br>t driven)/(electric driv<br>urbo/super charger; (<br>ct ozone reducing; H0<br>ter treatment ECS incompressed/liquefied na<br>isoline) fuel; A: autom<br>ission; SCV: selectab<br>-selectable transmiss | #ALVW; LDT4:<br>V5: MDV 1000<br>n; CERT: certific<br>ALVW: adjusted<br>itional ZEV; TW<br>; NAC: NOx ads<br>OC: ammonia ov<br>filter for spark-io<br>o sensor; NOXS<br>circulation; HP/L<br>en); PAIR: pulse<br>CAC: charge air<br>CT: hydrocarbor<br>licates multiple f<br>tural gas; LPG:<br>hatic (with lockup<br>le continuously<br>ion: OT: other tri- | (dation catalyst; CTOX/PTOX:<br>gnited engine; HO2S/O2S:<br>: NOx sensor; PMS: PM sensor;<br>P EGR: High/Low Pressure EGR;<br>d AIR; SFI/MFI: sequential/multiport<br>cooler; FFH: fuel fired heater; F/P/\$:<br>n trap; BCAN: bleed carbon canister;<br>functionalities of the after treatment<br>liquefied petroleum gas; E85: "85%"<br>o); M: manual transmission; SA: semi |  |  |  |  |  |  |

| 2020 MODEL YEAR: VEHICLE MODELS INFORMATION |                   |           |            |            |                       |            |     |  |  |  |
|---|-------------------|-----------|------------|------------|-----------------------|------------|-----|--|--|--|
| MAKE  | MODEL             | VEH CLASS | ENGINE (L) | TRANS TYPE | EVAPORATIVE<br>FAMILY | EXH<br>ECS | OBD |  |  |  |
| LAND ROVER                                  | DEFENDER          | LDT4      | 3.0        | SA8        | LJLXR0175P1Z          | 1          | F   |  |  |  |
| LAND ROVER                                  | RANGE ROVER       | LDT4      | 3.0        | SA8        | LJLXR0175P1Z          | 1          | F   |  |  |  |
| LAND ROVER                                  | RANGE ROVER SPORT | LDT4      | 3.0        | SA8        | LJLXR0175P1Z          | 1          | F   |  |  |  |