

Executive Order: A-413-0176

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP IN	FOF	RMATION					
MODEL	1 1	ST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY				FUEL TYPE	
2020	LV	GAT03.0NAQ			LDT4			PLUG-IN HYBRID ELECTRIC VEHICLE			GASOLINE		
ī	JSEFUL	LIFE (miles)	20	VEH	ICLE EMIS	SION C	ATE	GORY		INTERIM / IN	TERM	MEDIATE IN-USE STD	
EXH	/ORVR	EVAP		ı	TP		S	FTP	163-5948B	FTP		SFTP	
15	0000	150000	21	LEV3	ULEV125	LEV	3 (COMPOSITE	100 A 100 A	PM		PM	
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD	ST	TATUS	E	NGINE DISPLACEMENT (L)	
1 WU-TWC, TWC, WR-HO2S, HO2S, DFI, TC, CAC								FULL	T	*			
*	* *							PARTIAL	1	*	3.0		
*	* *							RTIAL WITH	Н	ALL MODELS			
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVA	P / ORV	R FAMILY	EVAP	ORATIVE	STD CATE	EGORY	VEHICLE CLASS				s	PECIAL FEATURES	
L	VGAR01	55NCV	LE	/ 3 OPTI	ON2 WITH	H FEL LDT4					*		
				E	MISSION	CREDIT	INF	ORMATIO	N				
ALLOWANCE FOR TEST GROUP TZEV NMOG+NOX FI AVE. CREDIT			DIT FOR NON-PZE			REDIT FOR EV ZERO- DOR		FOR OPTIONAL EXH. STE					
		k		N			1	Ŋ		И		N ·	
			*	NMOG	AND FLEE	T AVE	RAC	GE INFORM	IA٦	TION			
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO		O/NMHC ATIO				0 LVW) LD1		NMOG+NOX FLEET ST LDT (3751 LVW-8500 GVWR) + MDPV (g/mi		MDV (10,001-14,000	
*	*	1.10	(0.03		0.065				0.074		*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-413-0176

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have four (4) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the third and fourth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

day of March 2020.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this __

Illen Lyons, Chief

Emissions Certification and Compliance Division



Executive Order: A-413-0176

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

Support and		NMOG+NOx (g/mi)		1 100 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		NOx (g/mi)		HCHO (mg/mi)		P M (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	GASOLINE- TIER3 E10 PREM	*	*	*	*	*	*	2.8	*	*	*
FTP@UL	GASOLINE- TIER3 E10 PREM	0.0651	0.125	0.58	2.1	*	*	3.1	4	0.0010	0.003
50°F @4K	GASOLINE- TIER3 E10 PREM	0.0248	0.250	0.26	2.1	*	*	2.7	16		

HWFET @ 50K HWFET @ UL	FUEL TYPE	NMOG+N	lOx (g/mi)	CO (g/mi)		
	FUEL TYPE	CERT	STD	CERT	STD	
HWFET @ 50K	GASOLINE-TIER3 E10 PREM	0.008	*			
HWFET @ UL	GASOLINE-TIER3 E10 PREM	0.0368	0.125			
20°F @ 50K	COLD CO E10 PREMIUM GASOLINE (TIER3)			0.78	12.5	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC03	3	COMPOSITE			
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	
@ 4K	+	CERT	*	*	- 12 12 12	*	*				
		STD	*	*		*	*	1. 提供的 1. 数据			
		CERT	*	*	2.0	*	*	0.0536	0.80	. *	
@ UL	GASOLINE- TIER3 E10 PREM	STD	*	*	6	*	*	0.083	4.2	*	
	-	BIN						0.110	in the second		

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY			WHOLE \						
	FUEL TYPE	3DH	S (g/test) @	g UL	2DI	HS (g/test) (RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
LVGAR0155NCV	GASOLINE- TIER3 E10 PREM	0.246	0.500	0.500	0.215	0.500	0.500	0.00	0.05



Executive Order: A-413-0176

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
					FUEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY	ORVR (g/	ORVR (g/gallon) @ UL			FUEL TYPE		IG TEST) @ UL	2DHS RIG TEST (g/test) @ UL		BLEED CANISTE TEST (g/test) @ 4			
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD		
LVGAR0155NCV	GASOLINE- TIER3 E10 PREM	0.01	0.20	*		* *		·*	*	*	*		
E	FFECTIVE	LEAK D	IAMET	ER STAN	IDARI	O AND CE	RTIFICA	TION LE	/EL (INCH	IES)			
EVAPORATIVE FAMILY LEAK			K FAMIL	-Y		CERT			STD				
LVGAR0155NCV LVGAR015			155NCV	7-001 *			* 0.02						
	la constant I II a		a: DC: n	acconder of	or: ID	T: light_duty	truck: LD7	1. I DT<6	000#G\/\/F	0-3750#1\	VV- I DT2		

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LV LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits,

Y = credits,	S = credits for sor	ne/select mode	IS					
	2020	MODEL Y	EAR: VE	HICLE M	ODELS INF	ORMATION		
MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	BENTLEY	BENTAYGA	LDT4	3.0	SA8	LVGAR0155NCV	1	\$
	ELECT	RIC RANG	SE AND Z	EV ALLO	OWANCE II	NFORMATION	l .	
MODEL		UDDS AER	UDDS EAER	US06 AER	HIGHW	AY (MILES)	ZEV ALLOWANCE	
NUMBER	PHEV TYPE	(MILES)	(MILES)	(MILES)	AER	EAER		
1	*	28.78	28.8	*	30.72	30.4	0.00	