

Executive Order: A-401-0013-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
MOD		EST GROUP		VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE				
202	0 II	MLNV03.8M13		PC DEDI				DICATED SINGLE FUEL VEHICLE			GASOLINE			
	USEFU	L LIFE (miles)		VEH	ICLE EMISS	ION C	ATEC	ORY	Melate	INTERIM / INT	ERI	MEDIATE IN-USE STD		
EX	H/ORVR				FTP	-	SF	ГР	80000	FTP	SFTP			
150000 150000			)	CERTI:	LEV OPTION FYING TO LEV 2 SFTP LEV NMOG+ STANDARD NOX					*	*			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD STATUS				ENGINE DISPLACEMENT (L)		
1	2TWC	(2), 2H02S(	2),	SFI, AIR,	2TC, 2CAC	- 80		FULL	JLL *		10000			
*				Р	PARTIAL ALL MODELS		3.8							
*			*			melekundendan		PARTIAL WITH * FINES						
		E	VAPO	ORATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	Υ	INFORMATION				
EV	AP / OR	/R FAMILY	EV	APORATIVE	STD CATE	GORY	Y EVAP EMISSION STD VEHICLE CLASS				SPECIAL FEATURES			
	LMLNR0	164M13		L	LEV 2			PC				*		
				E	EMISSION C	REDIT	INFO	RMATION	-					
	REDIT F	OX FLEET AVE. OR EXTENDED RRANTY			EDIT FOR N	ON-P	PZEV NMOG CREDIT FOR DOI			REDIT FOR DOF	OPTIONAL EXH. STD FOR WORK TRUCKS			
		N			И					N ·		И		
				NMOG	AND FLEET	AVE	RAGE	INFORMA	T	ION				
NMO0 RAF	CH4 RAF	FTP NMOG/NMHO RATIO	НС	CHO/NMHC RATIO	DC-T111110-37			V) LDT	NMOG+NOX FLEET ST LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)			IMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.04		*	0	.125	_		0.125			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-401-0013-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-401-0013 dated April 10, 2019.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ZZND day of January 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division



Executive Order: A-401-0013-1

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 3 of 4

# **ATTACHMENT**

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

# EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

#### **FUEL TYPE**

		NMOG+NOx (g/mi)		CO (g/mi)		N( (g/		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE - CA PHASE 2	0.092	0.125	0.7	2.1	*	*	0.8	11	*	0.01
50°F @4K	GASOLINE - CA PHASE 2	0.099	0.250	1.5	2.1	*	*	1.8	16		

	FILE TYPE	NMOG+N	lOx (g/mi)	CO (g/mi)		
	FUEL TYPE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	*			
HWFET @ UL	GASOLINE - CA PHASE 2	0.043	0.125		A respict a	
20°F @ 50K	GASOLINE - CA PHASE 2			4.4	10.0	

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC03	3	COMPOSITE		
	FUEL TYPE		NMHC+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMHC+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	GASOLINE - TIER 2 UNLEADED	CERT	0.07	0.2		0.06	0.4			
		STD	0.14	8.0		0.20	2.7		14 17 16	
		CERT	*	*	*	*	*	0.095	*	*
@ UL	GASOLINE - TIER 2 UNLEADED	STD	*	*	*	*	*	0.083	*	*
		BIN	attaciple A 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A	and the second	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	11/20 <b>11</b> /40 11 11/40		0.100	1.00	

# WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

	FUEL TYPE		WHOLE \						
EVAPORATIVE FAMILY		3DH	S (g/test) @	D UL	2Dł	HS (g/test) (	RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
LMLNR0164M13	GASOLINE - TIER 2 UNLEADED	0.25	0.50	*	0.24	0.65	*	0.03	0.05



Executive Order: A-401-0013-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 4 of 4

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g	FUEL TYPE			IG TEST ) @ UL		RIG TEST	BLEED CANISTER TEST (g/test) @ 4K					
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD		
LMLNR0164M13	GASOLINE - L3 TIER 2 0.10 0.20 UNLEADED		*		*	*	*	*	*	*			
	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE	FAMILY	LEA	K FAMII	_Y CERT					STD				
*			*	*					*				

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC; EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits. S = credits for some/select models

#### 2020 MODEL YEAR: VEHICLE MODELS INFORMATION **EVAPORATIVE EXH** OBD TRANS TYPE ENGINE (L) MODEL **VEH CLASS** MAKE **ECS FAMILY** P PC 3.8 AMS7 LMLNR0164M13 1 540C COUPE MCLAREN 3.8 AMS7 LMLNR0164M13 1 P PC 570GT MCLAREN AMS7 LMLNR0164M13 1 P PC 3.8 MCLAREN 570S COUPE AMS7 LMLNR0164M13 1 P 3.8 PC 570S SPIDER MCLAREN 1 P AMS7 LMLNR0164M13 PC 3.8 600LT COUPE MCLAREN 1 P AMS7 LMLNR0164M13 PC 3.8 600LT SPIDER MCLAREN P 1 LMLNR0164M13 PC 3.8 AMS7 620R COUPE MCLAREN