

MCLÁREN AUTOMOTIVE LIMITED

Executive Order: A-401-0013

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

EXH/ORVR	NGLE FUEL	GASOLINE RMEDIATE IN-USE STD SFTP		
USEFUL LIFE (miles)	ITERIM / INTE	RMEDIATE IN-USE STD		
EXH/ORVR	FTP			
150000 150000 LEV2 ULEV OPTION CERTIFYING TO LEV3 ULEV NMOG+ NOX SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS 1 2TWC(2), 2H02S(2), SFI, AIR, 2TC, 2CAC * * * PARTIAL AI		SFTP		
150000 150000 CERTIFYING TO LEV 2 SFTP STANDARD SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS 1 2TWC(2), 2H02S(2), SFI, AIR, 2TC, 2CAC * * PARTIAL AI	,			
SYSTEMS 1 2TWC(2), 2H02S(2), SFI, AIR, 2TC, 2CAC *				
* * PARTIAL AI	US	ENGINE DISPLACEMENT (L)		
PARTIAL WITH	*			
PARTIAL WITH	L MODELS	3.8		
* * * FINES	*			
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INF	ORMATION			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY EVAP EMISSIC VEHICLE CL		SPECIAL FEATURES		
LMLNR0164M13 LEV 2 PC		*		
EMISSION CREDIT INFORMATION				
NMOG+NOX FLEET AVE: CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON-PZEV ZERO-EVAP NMOG CREDIT	IT FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS		
N N	ľ	И		
NMOG AND FLEET AVERAGE INFORMATION	1			
NINOG CH4 NMOG/NMHC RATIO PC+LDT (0-3750 LVW) LDT (375		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
* * 1.04 * 0.125	1 LVW-8500 MDPV (g/mi)	GVVVK) (g/iiii)		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



MCLAREN AUTOMOTIVE LIMITED

Executive Order: A-401-0013

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 10th day of April 2019.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



GASOLINE -

TIER 2

UNLEADED

0.25

0.50

LMLNR0164M13

MCLAREN AUTOMOTIVE LIMITED

Executive Order: A-401-0013

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

	S=/(1/1/	EXHA!	UST E	MISSIO	N STAN	IDARDS A	ND CER	TIFICA	TION L	EVELS	(FTP, HW	FET, 50°F, 20)°F)			
	FUE	FUEL TYPE		CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP												
				NMOG+NOx (g/mi)			CO (g/mi)		NOx (g/mi)			HCHO mg/mi)		PM (g/mi)		
				CERT	STE	CERT	T STI	D C	CERT STD		CER	T STD	CERT	STD		
FTP@5	0K	*		*	*.	*	*		*	*	2	*	*	*		
FTP@L	11	LINE PHASE	1 (0.092	0.12	5 0.7	2.	1	*	*	0.8	11	*	0.01		
50°F @	1121	LINE PHASE	1 (0.099	0.25	0 1.5	2.	1	*	*	1.8	16				
	* 1			FUEL TYPE							Ox (g/mi)	1 of Rgs 83 s	CO (g/mi)			
					TOLE TIPE				CERT		STD	STD CER		STD		
HWFE	T @ 50K				*						*					
HWFE	T@UL			GASOLI	NE - C	A PHASE	2		0.0	043	0.125		ga Na 108 Main bad			
20°F	20°F @ 50K GASOLINE - CA PHASE 2									4.4		10.0				
			SF	TP EXI	HAUST	EMISSION	STAND	ARDS A	AND C							
					US06				SC03			MPOSITE				
A. 图 电电子	FUEL T	YPE	NMHC+N (g/mi)			CO (g/mi)		M g/mi)	NMHC+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	(g/mi)	PM (mg/mi			
GASOLII TIER @ 4K UNLEAI		2 CERT		0.	07	0.2			0.	06	0.4					
			STD	0.	14	8.0	2400		0.	20	2.7	es altricher	al Alemana de la compansa de la c			
		ASOLINE - TIER 2 INLEADED BIN		XT *		*		*		*	*	0.095	*	*		
@ UL TIER	TIER			D *		*	* *		*		*	* 0.083		*		
	ONLINE			in Graffi Graffian								0.100				
		WHO	LE VE	HICLE	EVAPO	RATIVE E	MISSIO	N STAN	DARD	S AND	CERTIFIC	ATION LEVE	LS			
						WHOLE V	'EHICLE	EVAPO	ORATI	VE TES	TING					
EVAPORATIVE FUE				. TYPE 3DHS (g/test) @ UL				2DHS (g/test) @ UL				R	RL (g/mi) @ UL			
F.F	MILY										,					

0.24

0.65

0.03

0.05



MCLAREN AUTOMOTIVE LIMITED

Executive Order: A-401-0013

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

				FUEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY	ORVR (g/g	jallon) (D UL	FUEL TYPE	3DHS R (g/test	IG TEST) @ UL	2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K			
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD		
LMLNR0164M13	GASOLINE - TIER 2 0.10 UNLEADED		0.20			*	*	*	*	*		
	EFFECTIVE I	EAK D	IAMET	ER STANDAR	D AND CE	RTIFICA	TION LEV	EL (INC	HES)	Land 1		
EVAPORATIVE FAMILY LEAK FAM		K FAMIL	.Υ	CERT				STD				
*			*	1-13-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	*		Web at the		*			

not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ŽEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic: DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	ОВС
MCLAREN	540C COUPE	PC	3.8	AMS7	LMLNR0164M13	1	P
MCLAREN	570GT	PC	3.8	AMS7	LMLNR0164M13	1	P
MCLAREN	570S COUPE	PC	3.8	AMS7	LMLNR0164M13	1	P
MCLAREN	570S SPIDER	PC	3.8	AMS7	LMLNR0164M13	1	P
MCLAREN	600LT COUPE	PC	3.8	AMS7	LMLNR0164M13	1	P
MCLAREN	600LT SPIDER	PC	3.8	AMS7	LMLNR0164M13	1	P